



**Ceiling Types:**

- Type 1. K4011 - Kitchen - Hygienic mineral fibre bylin tiles with integrated service installations
- Type 2. K4012 - Suspended mineral fibre tile
- Type 3A. K4014 - Suspended bathhead with demountable high density glass wool acoustic fins and plasterboard edges (K1021). Contains integrated lighting, emergency lighting and sprinkler systems as required.
- Type 3B. K4015 - Suspended Acoustic Panels
- Type 4. M4010 & J - Painted concrete soffit - White finish and/or clear concrete sealant as specified (refer to finishes schedule). NOTE - Theatre concrete soffit to be "Blacked Out" - refer to Finishes Schedule
- Type 5. K1020 - Moisture-resistant suspended plasterboard ceiling (MC's & Wet Spaces)
- Type 6A. K1023 - MEDBURN MF suspended plasterboard ceiling with access panels as required. Two layers 12.5mm Fintex with 75mm acoustic insulation quilt. Acoustic resilient suspended ceiling. Fire & Acoustic rating. All penetrations and perimeter to be fire & acoustically sealed.
- Type 6B. K1023 - MEDBURN MF suspended plasterboard ceiling. Bulk flush with window head soffit to provide clearance to windows. Bulkhead 400mm deep from finished wall face.
- Type 6C. MEDBURN 15mm Fintex board mechanically fixed to underside of existing ceiling - typically in corridors with adjacent stairs land
- Type 12. K1023 - Existing ceiling finish to be removed and to be replaced with plasterboard ceiling and layer of insulation that follows shape of Phase 2 ONLY
- Type 7. Existing concrete soffit. M4010 A & J - Painted concrete soffit - White finish and/or clear concrete sealant as specified
- Type 8. H2010 - Timber Lining to External Soffit
- Type 10. K1021 - Perforated Plasterboard (Duroto 41) - high acoustic absorbance
- Type 11. K1311 - Suspended acoustic panel. Size: 1200x600x40
- Type 13. H10 & H4 - Rooflight - refer to SCCS\_ARCH\_1406
- Type 14. K1028 - Perforated Plasterboard (Rigilene 1023) Suspended Ceiling and plasterboard edges (K1021)
- Type 15. K1020 - Plain Plasterboard Suspended Ceiling (K1021 - Plain Plasterboard margins)
- Type 16. K4016 - Suspended system with demountable high density glass wool acoustic fins and plasterboard edges (K1021)
- Type 17. P1016 - Mineral fibre with a black tissue facing
- Type 18. M2014 - External Insulated Rendered Soffit
- Type 19. M2014 - External Insulated Rendered Soffit
- Type 20. K4017 - Suspended system with demountable acoustic fins area high impact
- K1312 - Acoustic baffles panels
- Steel beam at ceiling level concealed within proprietary fire board system (K1020 or K1036)
- External Insulated Rendered Soffit M2014
- Painted underside of steel deck DARK GREY - RAL colour 7012
- Painted underside of concrete slabs WHITE
- Line of ceiling steel to be fire lined to 40 minutes integrity and insulation (Locations are indicative - to be checked on site)
- Access Panel - Structural Opening 455x455mm. Outside edge of frame 500x500mm
- Access Panel - Structural Opening 305x305mm. Outside edge of frame 350x350mm
- Sprinkler head. Refer to H&K drawings for sprinkler information. Lines of exposed sprinkler pipe. Setting out shown above. Refer to Baro Haggopis Services for specification type
- Smoke Sensor - Setting out shown above. Refer to Baro Haggopis Services for specification type
- PIR - Setting out shown above. Refer to Baro Haggopis Services for specification type
- Supply Exhaust Ventilation - Setting out shown above. Refer to Baro Haggopis Services for grille specification

**Light Types:**

For light fitting colours the letter next to the light fitting symbol refers to B-Black, W-White, G-Grey

- H1 - MWP surface mounted light fitting
- H2 - MWP surface mounted light fitting (dim)
- K1 - Suspended pendant light fitting
- P - Wall mounted adjustable uplighter - ftc
- AD - Acoustic baffle light fitting with integrated speakers and emergency lighting. White/Black Lx L in Exception Mastersols
- C - IP rated recessed spot light
- IP - IP rated recessed spot lights with fire hood
- G - Ceiling and wall mounted light fitting. TFS. G fitting to be BAM in specific locations
- L1 - Linear fluorescent batten light fitting
- F1 - Hygienic White/corflite hygienic
- L - Linear recessed luminaire (rough fitting)
- S - Batten luminaire behind panels
- W - Wall/ceiling mounted light fitting (Type G replacement)
- X - Over smoker table - Phase 1 only
- R - Iguzzini Fall square BS72
- EX0 - Casper Die Cast
- EX11 - Product ftc
- L19 - Circular wall mounted light fitting - Ada range
- E - Emergency light fitting requirement

**General Notes:**

- Drawings to be read with Baro Haggopis / Grates layouts for - lighting, ventilation, security fire, speakers, small panels & data
- All levels to be checked on site
- All setting out to Architects approval
- Allow for ceiling access panels, as advised by Baro Haggopis. Setting out to be agreed with Architect
- Service distribution contained within service void in ceiling build up, unless shown otherwise. All exposed conduit routes to be set out and agreed with Architect. ALL routes are to be equally spaced, minimize crossover, NO cable baskets
- ALL service penetrations through ceiling to be fire & acoustically sealed. Access panels to also meet same requirements
- Ceiling voids exceeding 800mm clear require sprinkler void protection - reference to be made to Sprinkler specialist
- AD light rails typically contain lighting / PIR / smoke / sprinklers - all service routes (cables, conduits, trunking, etc) to be run on top of rail and not ceiling mounted unless agreed with Architects
- Sprinkler pipe distribution to be over rail unless agreed otherwise with Architect
- Final Fire Exit Sign
- Directional Fire Exit Sign to Final Exit
- Static CCTV Camera
- Pager system speaker recessed in ceiling
- PA in circulation installed in ceiling

ArCADE Plan 1:500

© This drawing is copyright.  
Notes:  
Do not scale from drawing. Use figured dimensions only. All dimensions to be checked on site.  
All drawings should be read in conjunction with Structural Engineer's and Services Engineer's documentation.

**bam**  
**Camden**

PROJECT: CAMDEN BSF SOUTH CAMDEN COMMUNITY SCHOOL  
SITE: Arcade - First Floor Plan RCP

DATE: 16/10/12  
SCALE: 1:75 @ AD

REV: 16/10/12  
DATE: 16/10/12  
NOTE: For Construction - See Bubbles

FOR CONSTRUCTION - SEE BUBBLES  
FOR CONSTRUCTION - SEE BUBBLES  
FOR CONSTRUCTION - SETTING OUT  
FOR CONSTRUCTION - SEE BUBBLES  
FOR CONSTRUCTION - SEE BUBBLES  
FOR CONSTRUCTION - SEE BUBBLES

PROJECT: CAMDEN BSF SOUTH CAMDEN COMMUNITY SCHOOL  
SITE: Arcade - First Floor Plan RCP  
DATE: 16/10/12  
SCALE: 1:75 @ AD  
DRAWING NO: SCCS\_ARCH\_11756