

PRODUCT SPECIFICATION CLAUSES

F10 BRICK/ BLOCKWORK WALLING

To be read with Preliminaries/ General Conditions

TYPE(S) OF WALLING

110 CLAY FACING BRICKWORK SHALL BE:

Product Name: Highbury

Size: 215mm x 102mm x 66mm

Supplied by: Modular Clay Products
Unit 18, Blackhouse Farm
Blackhouse Road
Colgate
Surrey
RH13 6HS
Contact: Sales
Tel no. 01293 854430
sales@modularclayproducts.co.uk

Bricks are to comply with the requirements of EN771-1

Durability Designation	F2
Soluble Salt Content	S2
Compressive Strength	>20N/mm ²
Water Absorption	<14% by weight
Dimensional Tolerance (mean + range)	T2 R1

Special Shapes: To BS4729 and as detailed in.....

Mortar Mix: As defined in BS5628 Part 3. Table 12 (see 460 below).

(Attention should be given to the exposure ratings of the building in selection of mortars and joint profile specified)

Special Colour Reference: as supplied by

Brickwork Bond: As shown on drawing SKA 1092

Joints Profile: (see 635 below)

Colour Mixing of Bricks Prior to Laying; Bricks are to be site mixed by hand from pallets delivered to site to proportions as stated on Architects details and to that as agreed on site reference panel.