

PLAN OF SECONDARY ESCAPE AND CYCLE STORE SCREEN ALONG PENTONVILLE ROAD

GENERAL NOTES

Drawing to be read in conjunction with all information by architects, structural engineer & service consultants.

The contractor is not to scale from this drawing. All written dimensions to be checked on site before work commences. Discrepancies, where identified, must be reported to the architect

NOTES:

All glazing to match the criteria specified by the Acoustic Consultant (RBA Acoustics) in their External Building Fabric Report 5181/EBF Revision Number 1

All sizes are indicative at present. The width of the bays vary throughout the building. Level of detail and dimensions to be confirmed on site by the SC in agreement with the architect.

Timber cornice:
Timber to be external grade European softwood or

Timber grade to be min J30 in accordance to BS EN 14220:2006

Timber preservative treatment to be in accordance with BS EN 942.

External arrisses to be softened by a 2mm. edge.

All coatings to timber to be in accordance with the performance requirements in BS 644. Colour to be confirmed.

E	-	AV	28/11/2014	CCTV and access control added. Cycle store door modified. Issued to discharge planning condition
D	DOR	AV	14/02/2014	Issued to discharge planning condition
С	DOR	AV	06/12/2013	Stall riser detail added, General revisions
В	DOR	AV	31/05/2012	Dimensions & spec notes added
Α	AV	BG	03/02/2012	Issued for Tender
Issue	Chkd	Drawn	Date	Description

CONSTRUCTION

Job No. Drwg No. 0706 Ε [31.1]02

Drawing Scale _1:20@A1 Scale _1:40@A3
'SHOPFRONT' BAY ELEVATION

SECONDARY ESCAPE DOOR & CYCLE STORE THE LIGHTHOUSE BLOCK

LONDON WC1X