

Expansion of Kingsgate Primary School and Redevelopment of Liddell Road

Flood Risk Assessment

Submitted in support of
Application 01 for Phase 01
Application 02 for Phase 02
December 2014



Expansion of Kingsgate Primary School & Redevelopment of Liddell Road

Flood Risk Assessment

Revision 04

Submitted in support of the Application for Phases 1 and 2

Prepared by: Kirsty Burwood MEng
October 2014
22885

Checked by: Dimitris Linardatos BEng MSc CEng MICE

Revisions

Rev	Date	By	Notes
DRAFT	17/10/14	KB	Draft Report
01	18/11/14	KB	Issue report for planning
02	21/11/14	KB	Issue report for planning
03	26/11/14	KB	Issue report for planning
04	04/12/14	KB	Issue report for planning

Contents

1	Introduction	3
2	Existing Development Site	4
2.1	Location and Description	4
2.2	Existing Hydraulic Features	4
2.3	Existing Sewerage Infrastructure	5
2.4	Geology and Hydrogeology	5
3	Development Proposals	6
4	Flood Risks	7
4.1	Flood Risk from Rivers and/or the Sea	7
4.2	The Sequential and Exception Tests	8
4.3	Groundwater Flood Risk	9
4.4	Sewers and Overland Flow Flood Risk	10
5	Run-off Assessment	15
5.1	Existing Run-off	15
5.2	Proposed Run-off	15
6	Conclusions and Recommendations	17
7	References	18
	APPENDIX A – Existing Thames Water Records	19
	APPENDIX B – Masterplan	20
	APPENDIX C – Utility Survey	21
	APPENDIX D – Greenfield Run-Off	22
	APPENDIX E – Surface Water Calculations	23

1 Introduction

Price & Myers have been commissioned to undertake a Flood Risk Assessment (FRA) in support of both planning applications for phase 1 and 2 of a proposed mixed use development. The existing industrial units are to be demolished as part of the works

This FRA is prepared in accordance with the National Planning Policy Framework (NPPF), NPPF accompanying Technical Guidance, The North London Strategic Flood Risk Assessment (SFRA) and the London Plan.

This report is based on a desk-top review of published information. The objectives of this FRA are to:

- Identify and assess the risks of all forms of flooding to and from the development and demonstrate how these flood risks will be managed (if possible).
- Provide evidence to the local planning authority for the purposes of a sequential test; and
- Establish whether the proposed development will be safe from all sources of flooding.

The location of the proposed site is shown below in Figure 1.




Figure 1 - Site Location (© Environment Agency copyright and database rights 2014. © Ordnance Survey Crown copyright. All rights reserved. Environment Agency, License Number 100026380.)

2 Existing Development Site

2.1 Location and Description

The existing industrial estate is located within West Hampstead in the London Borough of Camden. The postcode is NW6 2EW, national grid reference TQ 25129 84794. The location of the existing industrial estate is shown in the figure below.



Figure 2 – Existing Site Imagery © 2014. The GeoInformation Group, Map data © 2014 Google.

The site is bounded by the Thames Link and South Eastern Railway line in the north, an embankment sloping down to Maygrove Road in the South, Maygrove Peace Park in the West and commercial businesses to the East. The site is occupied by two blocks of single storey commercial units in the north and 17 single storey units in the south with associated parking. Liddell Road runs centrally through the site and joins with Maygrove Road in the southeast.

The site is approximately 1.2Ha in size and is set on a slope falling towards the southeast with a difference of levels of up to 4.5m.

2.2 Existing Hydraulic Features

There are no rivers or other water features within 500m of the site as seen in Figure 3.

The Hampstead and Highgate Ponds are approximately 2.5-3.5km to the north east of the site. They were constructed to increase London's water supply and are fed by the River Fleet. The River Fleet is a subterranean river which historically originates from the springs on Hampstead Heath and drains to the River Thames.




Figure 3 – Existing Watercourses and features © Environment Agency copyright and database rights 2014. © Ordnance Survey Crown copyright. All rights reserved. Environment Agency, 100026380. Contains Royal Mail data © Royal Mail copyright and database right 2014

2.3 Existing Sewerage Infrastructure

The Thames Water records show that a 305mm diameter combined drainage pipe currently runs from east to west along Maygrove Road to the south of the site. There is also an 1143x787 combined sewer beyond the northwest corner of the site. The Thames Water records can be seen in Appendix A.

Within the site there is a 150mm combined sewer in the east of Liddell Road which discharges to the south into Maygrove Road. This picks up the foul water from the industrial units to the south of Liddell Road and a couple of road gullies. The foul water from the units to the north of Liddell Road is taken to the west of the site where it is thought to discharge to the large combined sewer in the northwest. There is also an existing 400mm diameter concrete surface water pipe which runs from the east along Liddell Road to the west where it exits the site. This sewer picks up the surface water run-off from the buildings and the majority of the road gullies on Liddell Road.

2.4 Geology and Hydrogeology

GEA, Geotechnical & Environmental Associates have carried out a Ground Investigation Study. At the time of writing this report only a Summary of Ground Investigation Preliminary Findings [1] was available.

The report states that varying thicknesses of made ground was found to overlay the London Clay Formation. The made ground generally comprised of a concrete slab over very dark grey and blackish silty very gravelly sand with brick and concrete fragments, frequent coal, ash and rare pockets of clay. It extended to depths of between 2.90 – 4.60m. Below this the London Clay

comprised of brown clay with occasional grey markings to depths of between 10.60m and 12.20m, over grey clay which was encountered to the full depth investigated, of 25.00m.

The property is not located within a groundwater source protection zone or groundwater vulnerability zone as shown in Figure 4 below.




Figure 4 – Groundwater source protection zones and groundwater vulnerability zones. Existing Watercourses © Environment Agency copyright and database rights 2014. © Ordnance Survey Crown copyright. All rights reserved. Environment Agency, 100026380. Contains Royal Mail data © Royal Mail copyright and database right 2014

3 Development Proposals

The proposed mixed-use development will comprise of a school, employment and residential units with two vehicular accesses.

A master plan produced by Maccreanor Lavington Architects can be found in Appendix B.

The development has been split into two phases and a separate planning application has been submitted for each. This report supports both phases. Drawings showing the boundary of each phase can be found in Appendix B.

4 Flood Risks

The following possible sources of flooding will be considered for this site:

- Rivers and/or Sea
- Groundwater
- Sewers and Overland flow

4.1 Flood Risk from Rivers and/or the Sea

The Environment Agency's (EA) indicative flood outline map, shown below in Figure 5, shows that the site is not at risk of flooding from rivers.




Figure 5 - Flood Map for Flooding from Rivers and the Sea © Environment Agency copyright and database rights 2014. © Ordnance Survey Crown copyright. All rights reserved. Environment Agency, 100026380. Contains Royal Mail data © Royal Mail copyright and database right 2014

The two small reservoirs on Hampstead Heath are considered to present a low risk to the site as seen in Figure 6.




Figure 6 - Flood Map for Flooding from Reservoirs © Environment Agency copyright and database rights 2014. © Ordnance Survey Crown copyright. All rights reserved. Environment Agency, 100026380. Contains Royal Mail data © Royal Mail copyright and database right 2014

4.2 The Sequential and Exception Tests

The Sequential Test is to be carried out during the planning process. It aims to ensure that preference for developable land is given to land that has the lowest risk of flooding, based on the data available. The test begins by determining the system of 'Flood Zoning', a system that assesses the risk posed by rivers and in coastal areas; estuaries and the sea. This information is made available by the EA and the LPA. The flood zoning system in England is described in Table 1 below.

Flood Zone	Definition
Zone 1 Low Probability	This zone comprises land assessed as having a less than 1 in 1000 annual probability of river or sea flooding (<0.1%)
Zone 2 Medium Probability	This zone comprises land assessed as having between a 1 in 100 and 1 in 1000 annual probability of river flooding (1% - 0.1%) or between a 1 in 200 and 1 in 1000 annual probability of sea flooding (0.5% - 0.1%) in any year.
Zone 3a High Probability	This zone comprises land assessed as having a 1 in 100 or greater annual probability of river flooding (>1%), or a 1 in 200 or greater annual probability of flooding from the sea (>0.5%) in any year.
Zone 3b Functional Floodplain	This zone comprises land where water has to flow or be stored in times of flood. Local planning authorities should identify in their Strategic Flood Risk Assessments areas of functional floodplain and its boundaries accordingly, in agreement with the Environment Agency. The identification of functional floodplain should take account of local circumstances and not be defined solely on rigid probability parameters. But land which would flood with an annual probability of 1 in 20 (5%) or greater in any year, or is designed to flood in an extreme (0.1%) flood, should provide a starting point for consideration and discussions to identify the functional floodplain.

Table 1 - Flood Zone Descriptions from the Framework [2]

The aim of the Sequential Test is to propose development in land which lies within Zone 1, prior to developing in high risk Zones 2, 3a and 3b. It also considers the vulnerability of the site to flooding when considering developments within the higher risk flood zones. See Table 2 for the flood risk vulnerability and flood zone compatibility table used. Land uses which are more vulnerable to flooding should be constructed in lower flood risk zones.

Flood risk vulnerability classification		Essential infrastructure	Water compatible	Highly vulnerable	More vulnerable	Less vulnerable
Flood zone	Zone 1	✓	✓	✓	✓	✓
	Zone 2	✓	✓	Exception Test required	✓	✓
	Zone 3a	Exception Test required	✓	x	Exception Test required	✓
	Zone 3b	Exception Test required	✓	x	x	x

Table 2 - Flood Risk Vulnerability & Flood Zone Compatibility [3]


The school and residential uses of the proposed development are classified as “more vulnerable” whilst the rest is classified as “less vulnerable”. The EA’s map confirms that the site is within Flood Zone 1. Table 2 confirms that the proposed development is suitable in Zone 1 and the Exception Test is not required.

4.3 Groundwater Flood Risk

Flooding can occur in locations where groundwater naturally exists at shallow depths. Prolonged periods of rainfall can result in elevated groundwater levels that may reach the surface. This can pose a flood risk, particularly for basements and cellars. Elevated groundwater can prevent infiltration occurring and could promote the occurrence of overland flow. In addition, groundwater could leak into existing surface water drainage systems that have poor integrity, reducing their ability to accommodate surface water runoff.

The SFRA [4] states that very few groundwater flooding records have been provided by the EA, none of which have occurred within the London Borough of Camden, as seen in Figure 7. During the site investigation groundwater was encountered at a single location within the made ground at a depth of 4.75m, rising to 4.44m following drilling after an hour.

Considering the above and the fact the proposals do not include any basements or lower ground floors, the flood risk from groundwater is considered low.



Legend

- (Barnet Flooding Locations
- (Enfield Groundwater Flooding
- (Enfield Pluvial Flooding
- (London Fire Brigade Flood Calls
- (Transport For London Flooding
- (Emergency Planning Unit Flooding
- (Additional Haringey Flooding Incidents
- | Borough Boundaries
- Canals
- Watercourses


		Client North London Waste Plan			
		Project North London Strategic Flood Risk Assessment			
Purpose Information		Drawing Title Map 20: Flooding Incidents			
Drawn	SL	Check	KR	Approved	FP
Date	19/08/18	Date	19/08/18	Date	19/08/18
Draft	Scale (at A1 size)		Issuing Office	Sutton Coldfield	Drawing Number
Issue	1:40,000		Telephone	0121 355 8949	722586/020
					Rev

Figure 7 – Map of Groundwater Flooding Incidents

4.4 Sewers and Overland Flow Flood Risk

Sewer systems in London are often very old, and are sometimes only designed to convey storms of relatively low return periods such as a 1 in 10 year rainfall event. As a result sewer flooding events can often be frequent but with smaller consequences than associated with fluvial flooding. Some of the London sewer network is a combined system with storm and foul drainage served by a single sewer. This makes flash flood events particularly inconvenient and unpleasant as floodwaters will often be contaminated with sewage.

Thames Water have provided information on sewer flooding by truncated postcode over the last 10 years, the results of which can be seen in Figure 8.




Figure 8 – Sewer Flooding Incidents

As can be seen the site is located outside of a postcode where sewer flooding has been reported. The postcode immediately to the north of the property has suffered from a large number of incidents.

In August 2002 there were some serious floods in the London Borough of Camden. It inflicted considerable damage on some Camden residents and their homes, public services and facilities, and private businesses. High rainfall levels and flood events are a recurring feature in Camden due to the nature of summer thunderstorms and the topography of Hampstead. It has been found that there are similarities between these floods and those that hit Camden in 1975.

The flood event on the 7th August 2002 was caused by excessive rainfall causing the main sewer system to become completely inundated. The surcharge pressure forced the water to back onto the streets through manholes and gully gratings and into residents' homes at basement and ground floor level. Thames Water's confirmed that the flooding was caused by its sewer system reaching maximum capacity very quickly so that surface water could not be drained at the rate as the rain fell. The map in Figure 9 shows the roads affected by flooding during the August 2002 floods.




Figure 9 – Camden Flooding Map [4]

Figure 8 and Figure 9 show reasonable correlation although the Camden floods appear to be more widespread in Figure 8 than in the Thames Water records. This can be attributed to the fact that some of the properties flooded in 2002 will not be included on the Thames Water database unless they flood twice in ten years. The road to the south of the development, Maygrove Road appears to have flooded in 1975, but not in the 2002 floods.

Figure 10 below shows the levels of the surrounding area where it can be seen that the levels fall from north to south. Within the site the levels falls towards the south east with a change in level of up to 4.5m. During intense rainfall events the water should flow away from the site therefore not causing flooding within the development.




Figure 10 - Surrounding Area Topography (1:7000) Findmaps.co.uk Professional Mapping Intelligence © Crown Copyright 2014. License Number 100047514.

Taking the above into consideration it can be concluded that the site is at a low risk of flooding from sewer failure and overland flow as it is not within a valley, where overland flows will be collected during a storm event which can cause localised flooding. It is however important to ensure there is sufficient discharge capacity and that flood risk is not increased due to the development proposals.

The EA's surface water flood map, shown in Figure 11, also shows that the risk is low in this area. Overland flows will be maintained within the road channels and will flow downstream without affecting the surrounding areas.



Figure 11 – Risk of Flooding from Surface Water © Environment Agency copyright and database rights 2014. © Ordnance Survey Crown copyright. All rights reserved. Environment Agency, 100026380. Contains Royal Mail data © Royal Mail copyright and database right 2014

5 Run-off Assessment

As discussed in section 2 the existing surface water drainage exits the site in two different locations: into a combined sewer in the southeast and in a surface water sewer to the west.

5.1 Existing Run-off

The topographical survey drawing of the site shows that the impermeable area currently covers about 87% of the total site (10,480m²). The total run-off rate was estimated for the 1 in 100 year storm event using the modified rational method, as shown below.

$$Q_{100} = 2.78 \times A \times i$$

Where

A = Catchment area (Ha)

i = Rainfall intensity (mm/hr)

$$Q_{100} = 2.78 \times 1.048 \times 107.183 = 312 \text{ l/s}$$

Of this approximately 450m² of surface water can be seen to connect into the combined sewer in Maygrove Road. The existing discharge of which has been calculated below.

$$Q_{100} = 2.78 \times 0.045 \times 107.183 = 13.4 \text{ l/s}$$

The rest of the site discharges into the large surface water sewer which is taken off to the west of the site. It is unknown where this discharges into the Thames Water sewer. The utility survey can be seen in Appendix C.

5.2 Proposed Run-off

In accordance with the London Plan, EA guidelines, Building Regulations and Water Authorities advice the preferred means of surface water drainage for any new development is into a suitable soakaway or infiltration drainage system. Sustainable Drainage Systems (SUDS) can reduce the impact of urbanisation on watercourse flows, ensure the protection and enhancement of water quality and encourage recharge of groundwater in a manner that mimics natural conditions. If drainage to an infiltration system proved to be an unsuitable option for the site then drainage to public sewers will be assessed. Drainage to the public sewers can be considered only when all other options proved unsuitable.

The ground within the site is not suitable for accommodating infiltration systems as it is made ground underlain with London Clay. The proposed development will be reducing the amount of hardstanding area to approximately 83%. The proposed run-off for a 1 in 100year storm with 30% climate change has been calculated below.

$$Q_{100+30\%} = 2.78 \times 1.0 \times 139.338 = 387 \text{ l/s}$$

The London Plan requires attenuation to Greenfield run-off rates from new developments. Using the online "Greenfield Run-off Estimation for sites" the allowable discharge limit for the site based on the FEH method has been calculated as 14.97l/s for a 1 in 100 year storm with a 30% allowance for climate change. The summary sheet for this calculation can be found in Appendix D.

Preliminary calculations using MicroDrainage software, available in Appendix E, show that a storage volume of approximately 560m³ must be provided in order to attenuate surface water from the site to the Greenfield run-off rate.

The surface water is proposed to discharge in two locations, with an outfall for each phase.

Phase 1 (Planning Application 1)

The school which is the north/northeast of the site will discharge into Maygrove Road in the southeast of the site. The school takes up approximately 50% of the site, therefore a similar proportion of the allowable surface water run-off will discharge at this location. This calculation can be found in Appendix E.

It is proposed that the schools playground surfacing, will utilise permeable paving in order to attenuate the surface water run-off to the discharge limit. Preliminary calculations have been carried out and show that there is a sufficient area of paving available to be made porous. The site falls at around 1:80 and will require a depth of approximately 650mm of type 3 material to provide sufficient attenuation. Other sustainable drainage systems (SuDS), such as ponds and rain gardens, have been proposed as part of the landscape design. Their storage capacity will be developed during the detailed design stage, thus allowing a reduction in the depth of permeable fill.

Phase 2 (Planning Application 2)

The remaining 50% of the site will discharge into Maygrove Road in the south of the site. This area will require approximately 350m³ of storage. This calculation can also be found in Appendix E. This can be provided through the use of a number of SuDS, which will be determined during the detailed design stage:

- Cellular attenuation tank
- Linear planting strips
- Stockholm tree planting
- Permeable paving

6 Conclusions and Recommendations

The key flood risk conclusions and how they are to be managed are as follows:

- River and/or Sea
 - The site lies within Flood Zone 1 where there is less than 1 in 1000 annual probability of river or sea flooding (<0.1%).
 - The proposed mixed use development is classified as more vulnerable within the flood risk vulnerability classification. These are appropriate within Flood Zone 1.
- Groundwater
 - Groundwater is assumed to be deep.
 - The proposals will not affect the local hydrogeology. Therefore the proposed development will not increase the flood risk from groundwater on site or the surrounding areas.
 - The likelihood of groundwater emerging from the ground is considered to be very low.
 - Excavations must be made safely with due regard to ground water.
- Sewers and Overland Flow
 - The levels in the surrounding area fall from north to south therefore overland flow generated by the proposed development site or adjacent sites should flow away from the development.
 - In 2002 there were some extreme flood events in Camden due to the failure of the sewer network. The site was unaffected by these floods.
 - The site is at low risk of flooding from sewer failure and overland flow.
 - Consultation should continue with Thames Water regarding the proposed discharge into the existing sewer.
- Proposed Discharge
 - The overall existing surface water discharge from the site is 312 l/s
 - The surface water from the proposed development will be attenuated to meet the Greenfield Run-off Rate.

It can be concluded that the proposed mixed use development will not adversely affect onsite or neighbouring properties or their residual flood risk. This report has not identified any significant risks that should prevent the re-development of the site.


It is recommended that during the detailed design stage:

- Existing drainage infrastructure is confirmed; and
- Existing and proposed discharges allowances are confirmed.

7 References

- [1] Summary of Ground Investigation Preliminary Findings, GEA, Revision no. 1, August 2014.
- [2] National Planning Policy Framework, Department for Communities and Local Government, March 2012. <http://www.nationalarchives.gov.uk/doc/open-government-licence/>
- [3] Technical Guidance to the National Planning Policy Framework, Department for Communities and Local Government, March 2012
<http://www.nationalarchives.gov.uk/doc/open-government-licence/>
- [4] North London Strategic Flood Risk Assessment (SFRA), Final Report. Mouchel, August 2008
- [5] The London Plan, Spatial Development Strategy for Greater London. Greater London Authority, July 2011.

APPENDIX A – Existing Thames Water Records




The width of the displayed area is 254m and the centre of the map is located at OS coordinates 525144,184813

The position of the apparatus shown on this plan is given without obligation and warranty, and the accuracy cannot be guaranteed. Service pipes are not shown but their presence should be anticipated. No liability of any kind whatsoever is accepted by Thames Water for any error or omission. The actual position of mains and services must be verified and established on site before any works are undertaken.

Based on the Ordnance Survey Map with the Sanction of the controller of H.M. Stationery Office, License no. WU298557 Crown Copyright Reserved.

APPENDIX B – Masterplan



- KEY
- Existing tree
 - Proposed tree
 - Porous Tarmac
 - Existing vegetation
 - Proposed planting
 - Bonded rubber mulch softplay surface
 - Wetpour softplay surface
 - Permeable resin-bond surface
 - Linear concrete slabs
 - Grass mown/ wildflower meadows
 - Loose gravel
 - Concrete patio paving

N

JCLA

3A Iliffe Yard
LONDON SE17 3QA
Telephone
+44 (0)207 703 3270


www.jcla.co.uk

Notes

- Do not scale from drawings.
- To be read in conjunction with all relevant Architects', Services and Structural Engineers' drawings.
- All existing site, tree and building information has been compiled from different sources.
- All dimensions to be checked on site.

Revisions

Project	Kingsgate Liddell	Revision
Project No.	KL037	D
Client	London Borough of Camden	
Date	20 November 2014	
Scale	1:250 @ A1	
Drawing Name.	Stage D: Landscape plan	
Dwg No.	KL037.D.01.LP.RevD	



Application I: 11.718 m2



A site plan diagram showing a property boundary outlined in red. The property contains several grey-shaded rectangular areas, some of which are subdivided by dashed lines. There are also several overlapping circles in blue and yellow, primarily located along the left and bottom edges of the property. The text 'Application II: 5.977 m2' is written in red within the property boundary.

Application II: 5.977 m2

APPENDIX C – Utility Survey

ABBREVIATIONS	
1	1st Floor
2	2nd Floor
3	3rd Floor
4	4th Floor
5	5th Floor
6	6th Floor
7	7th Floor
8	8th Floor
9	9th Floor
10	10th Floor
11	11th Floor
12	12th Floor
13	13th Floor
14	14th Floor
15	15th Floor
16	16th Floor
17	17th Floor
18	18th Floor
19	19th Floor
20	20th Floor
21	21st Floor
22	22nd Floor
23	23rd Floor
24	24th Floor
25	25th Floor
26	26th Floor
27	27th Floor
28	28th Floor
29	29th Floor
30	30th Floor
31	31st Floor
32	32nd Floor
33	33rd Floor
34	34th Floor
35	35th Floor
36	36th Floor
37	37th Floor
38	38th Floor
39	39th Floor
40	40th Floor
41	41st Floor
42	42nd Floor
43	43rd Floor
44	44th Floor
45	45th Floor
46	46th Floor
47	47th Floor
48	48th Floor
49	49th Floor
50	50th Floor
51	51st Floor
52	52nd Floor
53	53rd Floor
54	54th Floor
55	55th Floor
56	56th Floor
57	57th Floor
58	58th Floor
59	59th Floor
60	60th Floor
61	61st Floor
62	62nd Floor
63	63rd Floor
64	64th Floor
65	65th Floor
66	66th Floor
67	67th Floor
68	68th Floor
69	69th Floor
70	70th Floor
71	71st Floor
72	72nd Floor
73	73rd Floor
74	74th Floor
75	75th Floor
76	76th Floor
77	77th Floor
78	78th Floor
79	79th Floor
80	80th Floor
81	81st Floor
82	82nd Floor
83	83rd Floor
84	84th Floor
85	85th Floor
86	86th Floor
87	87th Floor
88	88th Floor
89	89th Floor
90	90th Floor
91	91st Floor
92	92nd Floor
93	93rd Floor
94	94th Floor
95	95th Floor
96	96th Floor
97	97th Floor
98	98th Floor
99	99th Floor
100	100th Floor
101	101st Floor
102	102nd Floor
103	103rd Floor
104	104th Floor
105	105th Floor
106	106th Floor
107	107th Floor
108	108th Floor
109	109th Floor
110	110th Floor
111	111th Floor
112	112th Floor
113	113th Floor
114	114th Floor
115	115th Floor
116	116th Floor
117	117th Floor
118	118th Floor
119	119th Floor
120	120th Floor
121	121st Floor
122	122nd Floor
123	123rd Floor
124	124th Floor
125	125th Floor
126	126th Floor
127	127th Floor
128	128th Floor
129	129th Floor
130	130th Floor
131	131st Floor
132	132nd Floor
133	133rd Floor
134	134th Floor
135	135th Floor
136	136th Floor
137	137th Floor
138	138th Floor
139	139th Floor
140	140th Floor
141	141st Floor
142	142nd Floor
143	143rd Floor
144	144th Floor
145	145th Floor
146	146th Floor
147	147th Floor
148	148th Floor
149	149th Floor
150	150th Floor
151	151st Floor
152	152nd Floor
153	153rd Floor
154	154th Floor
155	155th Floor
156	156th Floor
157	157th Floor
158	158th Floor
159	159th Floor
160	160th Floor
161	161st Floor
162	162nd Floor
163	163rd Floor
164	164th Floor
165	165th Floor
166	166th Floor
167	167th Floor
168	168th Floor
169	169th Floor
170	170th Floor
171	171st Floor
172	172nd Floor
173	173rd Floor
174	174th Floor
175	175th Floor
176	176th Floor
177	177th Floor
178	178th Floor
179	179th Floor
180	180th Floor
181	181st Floor
182	182nd Floor
183	183rd Floor
184	184th Floor
185	185th Floor
186	186th Floor
187	187th Floor
188	188th Floor
189	189th Floor
190	190th Floor
191	191st Floor
192	192nd Floor
193	193rd Floor
194	194th Floor
195	195th Floor
196	196th Floor
197	197th Floor
198	198th Floor
199	199th Floor
200	200th Floor
201	201st Floor
202	202nd Floor
203	203rd Floor
204	204th Floor
205	205th Floor
206	206th Floor
207	207th Floor
208	208th Floor
209	209th Floor
210	210th Floor
211	211st Floor
212	212nd Floor
213	213rd Floor
214	214th Floor
215	215th Floor
216	216th Floor
217	217th Floor
218	218th Floor
219	219th Floor
220	220th Floor
221	221st Floor
222	222nd Floor
223	223rd Floor
224	224th Floor
225	225th Floor
226	226th Floor
227	227th Floor
228	228th Floor
229	229th Floor
230	230th Floor
231	231st Floor
232	232nd Floor
233	233rd Floor
234	234th Floor
235	235th Floor
236	236th Floor
237	237th Floor
238	238th Floor
239	239th Floor
240	240th Floor
241	241st Floor
242	242nd Floor
243	243rd Floor
244	244th Floor
245	245th Floor
246	246th Floor
247	247th Floor
248	248th Floor
249	249th Floor
250	250th Floor
251	251st Floor
252	252nd Floor
253	253rd Floor
254	254th Floor
255	255th Floor
256	256th Floor
257	257th Floor
258	258th Floor
259	259th Floor
260	260th Floor
261	261st Floor
262	262nd Floor
263	263rd Floor
264	264th Floor
265	265th Floor
266	266th Floor
267	267th Floor
268	268th Floor
269	269th Floor
270	270th Floor
271	271st Floor
272	272nd Floor
273	273rd Floor
274	274th Floor
275	275th Floor
276	276th Floor
277	277th Floor
278	278th Floor
279	279th Floor
280	280th Floor
281	281st Floor
282	282nd Floor
283	283rd Floor
284	284th Floor
285	285th Floor
286	286th Floor
287	287th Floor
288	288th Floor
289	289th Floor
290	290th Floor
291	291st Floor
292	292nd Floor
293	293rd Floor
294	294th Floor
295	295th Floor
296	296th Floor
297	297th Floor
298	298th Floor
299	299th Floor
300	300th Floor
301	301st Floor
302	302nd Floor
303	303rd Floor
304	304th Floor
305	305th Floor
306	306th Floor
307	307th Floor
308	308th Floor
309	309th Floor
310	310th Floor
311	311st Floor
312	312nd Floor
313	313rd Floor
314	314th Floor
315	315th Floor
316	316th Floor
317	317th Floor
318	318th Floor
319	319th Floor
320	320th Floor
321	321st Floor
322	322nd Floor
323	323rd Floor
324	324th Floor
325	325th Floor
326	326th Floor
327	327th Floor
328	328th Floor
329	329th Floor
330	330th Floor
331	331st Floor
332	332nd Floor
333	333rd Floor
334	334th Floor
335	335th Floor
336	336th Floor
337	337th Floor
338	338th Floor
339	339th Floor
340	340th Floor
341	341st Floor
342	342nd Floor
343	343rd Floor
344	344th Floor
345	345th Floor
346	346th Floor
347	347th Floor
348	348th Floor
349	349th Floor
350	350th Floor
351	351st Floor
352	352nd Floor
353	353rd Floor
354	354th Floor
355	355th Floor
356	356th Floor
357	357th Floor
358	358th Floor
359	359th Floor
360	360th Floor
361	361st Floor
362	362nd Floor
363	363rd Floor
364	364th Floor
365	365th Floor
366	366th Floor
367	367th Floor
368	368th Floor
369	369th Floor
370	370th Floor
371	371st Floor
372	372nd Floor
373	373rd Floor
374	374th Floor
375	375th Floor
376	376th Floor
377	377th Floor
378	378th Floor
379	379th Floor
380	380th Floor
381	381st Floor
382	382nd Floor
383	383rd Floor
384	384th Floor
385	385th Floor
386	386th Floor
387	387th Floor
388	388th Floor
389	389th Floor
390	390th Floor
391	391st Floor
392	392nd Floor
393	393rd Floor
394	394th Floor
395	395th Floor
396	396th Floor
397	397th Floor
398	398th Floor
399	399th Floor
400	400th Floor
401	401st Floor
402	402nd Floor
403	403rd Floor
404	404th Floor
405	405th Floor
406	406th Floor
407	407th Floor
408	408th Floor
409	409th Floor
410	410th Floor
411	411st Floor
412	412nd Floor
413	413rd Floor
414	414th Floor
415	415th Floor
416	416th Floor
417	417th Floor
418	418th Floor
419	419th Floor
420	420th Floor
421	421st Floor
422	422nd Floor
423	423rd Floor
424	424th Floor
425	425th Floor
426	426th Floor
427	427th Floor
428	428th Floor
429	429th Floor
430	430th Floor
431	431st Floor
432	432nd Floor
433	433rd Floor
434	434th Floor
435	435th Floor
436	436th Floor
437	437th Floor
438	438th Floor
439	439th Floor
440	440th Floor
441	441st Floor
442	442nd Floor
443	443rd Floor
444	444th Floor
445	445th Floor
446	446th Floor
447	447th Floor
448	448th Floor
449	449th Floor
450	450th Floor
451	451st Floor
452	452nd Floor
453	453rd Floor
454	454th Floor
455	455th Floor
456	456th Floor
457	457th Floor
458	458th Floor
459	459th Floor
460	460th Floor
461	461st Floor
462	462nd Floor
463	463rd Floor
464	464th Floor
465	465th Floor
466	466th Floor
467	467th Floor
468	468th Floor
469	469th Floor
470	470th Floor
471	471st Floor
472	472nd Floor
473	473rd Floor
474	474th Floor
475	475th Floor
476	476th Floor
477	477th Floor
478	478th Floor
479	479th Floor
480	480th Floor
481	481st Floor
482	482nd Floor
483	483rd Floor
484	484th Floor
485	485th Floor
486	486th Floor
487	487th Floor
488	488th Floor
489	489th Floor
490	490th Floor
491	491st Floor
492	492nd Floor
493	493rd Floor
494	494th Floor
495	495th Floor
496	496th Floor
497	497th Floor
498	498th Floor
499	499th Floor
500	500th Floor
501	501st Floor
502	502nd Floor
503	503rd Floor
504	504th Floor
505	505th Floor
506	506th Floor
507	507th Floor
508	508th Floor
509	509th Floor
510	510th Floor
511	511st Floor
512	512nd Floor
513	513rd Floor
514	514th Floor
515	515th Floor
516	516th Floor
517	517th Floor
518	518th Floor
519	519th Floor
520	520th Floor
521	521st Floor
522	522nd Floor
523	523rd Floor
524	524th Floor
525	525th Floor
526	526th Floor
527	527th Floor
528	528th Floor
529	529th Floor
530	530th Floor
531	531st Floor
532	532nd Floor
533	533rd Floor
534	534th Floor
535	535th Floor
536	536th Floor
537	537th Floor
538	538th Floor
539	539th Floor
540	540th Floor
541	541st Floor
542	542nd Floor
543	543rd Floor
544	544th Floor
545	545th Floor
546	546th Floor
547	547th Floor
548	548th Floor
549	549th Floor
550	550th Floor
551	551st Floor
552	552nd Floor
553	553rd Floor
554	554th Floor
555	555th Floor
556	556th Floor
557	557th Floor
558	558th Floor
559	559th Floor
560	560th Floor
561	561st Floor
562	562nd Floor
563	563rd Floor
564	564th Floor
565	565th Floor
566	566th Floor
567	567th Floor
568	568th Floor
569	569th Floor
570	570th Floor

APPENDIX D – Greenfield Run-Off

Site name: Liddell Road

Site location: West Hampstead

Site coordinates

Latitude: 51.54823° N

Longitude: 0.19645° W

This is an estimation of the greenfield runoff rate limits that are needed to meet normal best practice criteria in line with Environment Agency guidance "Preliminary rainfall runoff management for developments", W5-074/A/TR1/1 rev. E (2012) and the CIRIA SUDS Manual (2007). It is not to be used for detailed design of drainage systems. It is recommended that every drainage scheme uses hydraulic modelling software to finalise volume requirements and design details before drawings are produced.

Reference: gcpv780fnqs3 / 1.2

Date: 21 Nov 2014

Site characteristics

Total site area	1.2	ha
Significant public open space	0.2	ha
Area positively drained	1	ha

Methodology

Greenfield runoff method	FEH	
Qmed estimation method	Calculate from BFI and SAAR	
BFI and SPR estimation method	Specify BFI manually	
HOST class	N/A	
BFI / BFIHOST	0.24	
Qmed	4.13	l/s
Qbar / Qmed Conversion Factor	1.136	

Hydrological characteristics

	Default	Edited	
SAAR	640	640	mm
M5-60 Rainfall Depth	20	20	mm
'r' Ratio M5-60/M5-2 day	0.4	0.4	
FEH/FSR conversion factor	0.75	0.75	
Hydrological region	6	6	
Growth curve factor: 1 year	0.85	0.85	
Growth curve factor: 10 year	1.62	1.62	
Growth curve factor: 30 year	2.3	2.3	
Growth curve factor: 100 year	3.19	3.19	

Greenfield runoff rates

	Default	Edited	
Qbar	4.69	4.69	l/s
1 in 1 year	5.00	5.00	l/s
1 in 30 years	10.79	10.79	l/s
1 in 100 years	14.97	14.97	l/s

Please note that a minimum flow of 5 l/s applies to any site

APPENDIX E – Surface Water Calculations

Price & Myers

30 Newman Street
London
W1T 1LT

Date 17/10/2014
File Liddell Road FRA calcs....


Micro Drainage

Liddell Road

Designed by KB
Checked by


Source Control 2014.1.1

Page 1



Summary of Results for 100 year Return Period (+30%)							
Half Drain Time : 342 minutes.							
Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control E (l/s)	Max Outflow (l/s)	Max Volume (m³)	Status
15 min Summer	8.883	0.383	0.0	10.3	10.3	254.9	O K
30 min Summer	8.988	0.488	0.0	11.7	11.7	324.7	O K
60 min Summer	9.082	0.582	0.0	12.9	12.9	387.3	O K
120 min Summer	9.153	0.653	0.0	13.7	13.7	433.9	O K
180 min Summer	9.172	0.672	0.0	13.9	13.9	447.1	O K
240 min Summer	9.172	0.672	0.0	13.9	13.9	447.1	O K
360 min Summer	9.167	0.667	0.0	13.8	13.8	443.9	O K
480 min Summer	9.159	0.659	0.0	13.7	13.7	438.1	O K
600 min Summer	9.147	0.647	0.0	13.6	13.6	430.6	O K
720 min Summer	9.134	0.634	0.0	13.5	13.5	421.7	O K
960 min Summer	9.105	0.605	0.0	13.1	13.1	402.4	O K
1440 min Summer	9.046	0.546	0.0	12.4	12.4	363.4	O K
2160 min Summer	8.970	0.470	0.0	11.5	11.5	312.5	O K
2880 min Summer	8.908	0.408	0.0	10.7	10.7	271.4	O K
4320 min Summer	8.818	0.318	0.0	9.3	9.3	211.4	O K
5760 min Summer	8.757	0.257	0.0	8.3	8.3	170.7	O K
7200 min Summer	8.713	0.213	0.0	7.5	7.5	141.8	O K
8640 min Summer	8.681	0.181	0.0	6.9	6.9	120.5	O K
10080 min Summer	8.658	0.158	0.0	6.3	6.3	105.2	O K
15 min Winter	8.930	0.430	0.0	11.0	11.0	285.8	O K
Storm Event	Rain (mm/hr)		Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)		
15 min Summer	139.338		0.0	248.4	19		
30 min Summer	90.071		0.0	323.5	33		
60 min Summer	55.351		0.0	409.1	62		
120 min Summer	32.840		0.0	486.2	122		
180 min Summer	23.880		0.0	530.6	180		
240 min Summer	18.941		0.0	561.3	228		
360 min Summer	13.666		0.0	607.7	282		
480 min Summer	10.831		0.0	642.2	346		
600 min Summer	9.038		0.0	669.8	412		
720 min Summer	7.792		0.0	692.9	482		
960 min Summer	6.162		0.0	730.3	618		
1440 min Summer	4.421		0.0	784.5	892		
2160 min Summer	3.167		0.0	851.4	1280		
2880 min Summer	2.498		0.0	894.8	1668		
4320 min Summer	1.785		0.0	956.0	2380		
5760 min Summer	1.406		0.0	1009.8	3120		
7200 min Summer	1.167		0.0	1047.5	3824		
8640 min Summer	1.002		0.0	1078.4	4504		
10080 min Summer	0.881		0.0	1103.0	5248		
15 min Winter	139.338		0.0	279.2	18		


©1982-2014 XP Solutions

Price & Myers		Page 2
30 Newman Street London W1T 1LT	Liddell Road	
Date 17/10/2014 File Liddell Road FRA calcs....	Designed by KB Checked by	
Micro Drainage	Source Control 2014.1.1	

Summary of Results for 100 year Return Period (+30%)

Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control (l/s)	Max Σ Outflow (l/s)	Max Volume (m³)	Status
30 min Winter	9.048	0.548	0.0	12.5	12.5	364.4	O K
60 min Winter	9.155	0.655	0.0	13.7	13.7	435.6	O K
120 min Winter	9.237	0.737	0.0	14.5	14.5	489.9	O K
180 min Winter	9.263	0.763	0.0	14.8	14.8	507.2	O K
240 min Winter	9.266	0.766	0.0	14.8	14.8	509.6	O K
360 min Winter	9.254	0.754	0.0	14.7	14.7	501.6	O K
480 min Winter	9.241	0.741	0.0	14.6	14.6	493.1	O K
600 min Winter	9.224	0.724	0.0	14.4	14.4	481.3	O K
720 min Winter	9.203	0.703	0.0	14.2	14.2	467.8	O K
960 min Winter	9.160	0.660	0.0	13.7	13.7	438.8	O K
1440 min Winter	9.075	0.575	0.0	12.8	12.8	382.4	O K
2160 min Winter	8.969	0.469	0.0	11.5	11.5	311.6	O K
2880 min Winter	8.887	0.387	0.0	10.4	10.4	257.2	O K
4320 min Winter	8.775	0.275	0.0	8.6	8.6	183.0	O K
5760 min Winter	8.706	0.206	0.0	7.4	7.4	137.2	O K
7200 min Winter	8.662	0.162	0.0	6.4	6.4	107.8	O K
8640 min Winter	8.634	0.134	0.0	5.8	5.8	89.4	O K
10080 min Winter	8.623	0.123	0.0	5.1	5.1	81.5	O K

Storm Event	Rain (mm/hr)	Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)
30 min Winter	90.071	0.0	363.3	33
60 min Winter	55.351	0.0	458.7	62
120 min Winter	32.840	0.0	545.1	120
180 min Winter	23.880	0.0	594.9	176
240 min Winter	18.941	0.0	629.3	230
360 min Winter	13.666	0.0	681.2	296
480 min Winter	10.831	0.0	719.9	368
600 min Winter	9.038	0.0	750.8	446
720 min Winter	7.792	0.0	776.7	520
960 min Winter	6.162	0.0	818.6	668
1440 min Winter	4.421	0.0	879.4	952
2160 min Winter	3.167	0.0	954.0	1360
2880 min Winter	2.498	0.0	1002.7	1732
4320 min Winter	1.785	0.0	1071.8	2468
5760 min Winter	1.406	0.0	1131.2	3176
7200 min Winter	1.167	0.0	1173.6	3888
8640 min Winter	1.002	0.0	1208.4	4496
10080 min Winter	0.881	0.0	1236.7	5152

Price & Myers		Page 3
30 Newman Street London W1T 1LT	Liddell Road	
Date 17/10/2014	Designed by KB	
File Liddell Road FRA calcs....	Checked by	
Micro Drainage		Source Control 2014.1.1

Rainfall Details


Rainfall Model	FSR	Winter Storms	Yes
Return Period (years)	100	Cv (Summer)	0.750
Region	England and Wales	Cv (Winter)	0.840
M5-60 (mm)	21.000	Shortest Storm (mins)	15
Ratio R	0.435	Longest Storm (mins)	10080
Summer Storms	Yes	Climate Change %	+30

Time Area Diagram

Total Area (ha) 1.000

Time (mins)	Area
From:	To: (ha)

0	4 1.000
---	---------

Price & Myers		Page 4
30 Newman Street London W1T 1LT	Liddell Road	
Date 17/10/2014 File Liddell Road FRA calcs....	Designed by KB Checked by	
Micro Drainage	Source Control 2014.1.1	

Model Details

Storage is Online Cover Level (m) 10.000


Cellular Storage Structure

Invert Level (m) 8.500 Safety Factor 2.0
Infiltration Coefficient Base (m/hr) 0.00000 Porosity 0.95
Infiltration Coefficient Side (m/hr) 0.00000

Depth (m)	Area (m ²)	Inf. Area (m ²)	Depth (m)	Area (m ²)	Inf. Area (m ²)
0.000	700.0	700.0	0.900	0.0	788.0
0.800	700.0	788.0			

Pipe Outflow Control


Diameter (m) 0.100 Entry Loss Coefficient 0.500
Slope (1:X) 100.0 Coefficient of Contraction 0.600
Length (m) 8.000 Upstream Invert Level (m) 8.500
Roughness k (mm) 0.600


Price & Myers		Page 1
30 Newman Street London W1T 1LT		
Date 21/11/2014 16:06 File Permeable Paving - Lidd...		
Designed by kburwood Checked by		
Micro Drainage		Source Control 2014.1.1

Summary of Results for 100 year Return Period (+30%)							
Half Drain Time : 265 minutes.							
Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control (l/s)	Max E Outflow (l/s)	Max Volume (m³)	Status
15 min Summer	0.360	0.360	0.0	6.6	6.6	101.8	O K
30 min Summer	0.444	0.444	0.0	6.6	6.6	130.5	O K
60 min Summer	0.516	0.516	0.0	6.6	6.6	155.1	O K
120 min Summer	0.560	0.560	0.0	6.6	6.6	170.2	O K
180 min Summer	0.564	0.564	0.0	6.6	6.6	171.5	O K
240 min Summer	0.553	0.553	0.0	6.6	6.6	167.8	O K
360 min Summer	0.529	0.529	0.0	6.6	6.6	159.6	O K
480 min Summer	0.505	0.505	0.0	6.6	6.6	151.5	O K
600 min Summer	0.482	0.482	0.0	6.6	6.6	143.3	O K
720 min Summer	0.457	0.457	0.0	6.6	6.6	134.8	O K
960 min Summer	0.408	0.408	0.0	6.6	6.6	118.1	O K
1440 min Summer	0.325	0.325	0.0	6.6	6.6	89.8	O K
2160 min Summer	0.231	0.231	0.0	6.6	6.6	57.6	O K
2880 min Summer	0.171	0.171	0.0	6.5	6.5	37.2	O K
4320 min Summer	0.123	0.123	0.0	5.7	5.7	20.7	O K
5760 min Summer	0.104	0.104	0.0	4.7	4.7	14.8	O K
7200 min Summer	0.092	0.092	0.0	4.0	4.0	11.7	O K
8640 min Summer	0.084	0.084	0.0	3.4	3.4	9.6	O K
10080 min Summer	0.077	0.077	0.0	3.0	3.0	8.2	O K
15 min Winter	0.399	0.399	0.0	6.6	6.6	115.2	O K

Storm Event	Rain (mm/hr)	Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)
15 min Summer	137.494	0.0	106.7	18
30 min Summer	88.809	0.0	139.4	33
60 min Summer	54.549	0.0	172.5	62
120 min Summer	32.365	0.0	205.7	122
180 min Summer	23.543	0.0	224.8	180
240 min Summer	18.683	0.0	238.1	222
360 min Summer	13.462	0.0	257.6	280
480 min Summer	10.666	0.0	272.2	346
600 min Summer	8.898	0.0	283.8	414
720 min Summer	7.671	0.0	293.6	484
960 min Summer	6.064	0.0	309.3	608
1440 min Summer	4.349	0.0	332.2	866
2160 min Summer	3.115	0.0	355.9	1212
2880 min Summer	2.456	0.0	372.9	1556
4320 min Summer	1.755	0.0	397.2	2208
5760 min Summer	1.381	0.0	414.3	2936
7200 min Summer	1.147	0.0	427.2	3672
8640 min Summer	0.985	0.0	437.5	4400
10080 min Summer	0.866	0.0	445.9	5136
15 min Winter	137.494	0.0	120.1	18

©1982-2014 XP Solutions

Price & Myers		Page 2					
30 Newman Street London W1T 1LT							
Date 21/11/2014 16:06 File Permeable Paving - Lidd...							
Designed by kburwood Checked by							
Micro Drainage		Source Control 2014.1.1					
<u>Summary of Results for 100 year Return Period (+30%)</u>							
Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control (l/s)	Max E Outflow (l/s)	Max Volume (m³)	Status
30 min Winter	0.495	0.495	0.0	6.6	6.6	147.9	O K
60 min Winter	0.577	0.577	0.0	6.6	6.6	175.9	O K
120 min Winter	0.631	0.631	0.0	6.6	6.6	194.6	O K
180 min Winter	0.641	0.641	0.0	6.6	6.6	197.7	O K
240 min Winter	0.632	0.632	0.0	6.6	6.6	194.9	O K
360 min Winter	0.601	0.601	0.0	6.6	6.6	184.1	O K
480 min Winter	0.572	0.572	0.0	6.6	6.6	174.1	O K
600 min Winter	0.540	0.540	0.0	6.6	6.6	163.3	O K
720 min Winter	0.507	0.507	0.0	6.6	6.6	152.1	O K
960 min Winter	0.436	0.436	0.0	6.6	6.6	127.6	O K
1440 min Winter	0.308	0.308	0.0	6.6	6.6	83.9	O K
2160 min Winter	0.180	0.180	0.0	6.5	6.5	40.1	O K
2880 min Winter	0.129	0.129	0.0	6.0	6.0	22.9	O K
4320 min Winter	0.099	0.099	0.0	4.4	4.4	13.4	O K
5760 min Winter	0.085	0.085	0.0	3.5	3.5	9.8	O K
7200 min Winter	0.075	0.075	0.0	2.9	2.9	7.8	O K
8640 min Winter	0.069	0.069	0.0	2.5	2.5	6.5	O K
10080 min Winter	0.064	0.064	0.0	2.2	2.2	5.5	O K
Storm Event	Rain (mm/hr)	Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)			
30 min Winter	88.809	0.0	156.8	33			
60 min Winter	54.549	0.0	193.9	62			
120 min Winter	32.365	0.0	231.1	118			
180 min Winter	23.543	0.0	252.5	176			
240 min Winter	18.683	0.0	267.4	230			
360 min Winter	13.462	0.0	289.3	294			
480 min Winter	10.666	0.0	305.7	368			
600 min Winter	8.898	0.0	318.8	446			
720 min Winter	7.671	0.0	329.7	522			
960 min Winter	6.064	0.0	347.4	666			
1440 min Winter	4.349	0.0	373.2	922			
2160 min Winter	3.115	0.0	399.9	1236			
2880 min Winter	2.456	0.0	419.2	1528			
4320 min Winter	1.755	0.0	446.8	2208			
5760 min Winter	1.381	0.0	466.3	2936			
7200 min Winter	1.147	0.0	481.3	3672			
8640 min Winter	0.985	0.0	493.2	4408			
10080 min Winter	0.866	0.0	503.1	5136			
©1982-2014 XP Solutions							

Price & Myers		Page 3
30 Newman Street London W1T 1LT		
Date 21/11/2014 16:06 File Permeable Paving - Lidd...	Designed by kburwood Checked by	
Micro Drainage	Source Control 2014.1.1	


Rainfall Details

Rainfall Model	FSR	Winter Storms	Yes
Return Period (years)	100	Cv (Summer)	0.750
Region	England and Wales	Cv (Winter)	0.840
M5-60 (mm)	20.700	Shortest Storm (mins)	15
Ratio R	0.438	Longest Storm (mins)	10080
Summer Storms	Yes	Climate Change %	+30

Time Area Diagram

Total Area (ha) 0.436

Time (mins)	Area
From:	To: (ha)
0	4 0.436

Price & Myers		Page 4
30 Newman Street London W1T 1LT		
Date 21/11/2014 16:06 File Permeable Paving - Lidd...	Designed by kburwood Checked by	
Micro Drainage Source Control 2014.1.1		

Model Details

Storage is Online Cover Level (m) 1.000

Porous Car Park Structure

Infiltration Coefficient Base (m/hr)	0.00000	Width (m)	114.0
Membrane Percolation (mm/hr)	1000	Length (m)	10.0
Max Percolation (l/s)	316.7	Slope (1:X)	80.0
Safety Factor	5.0	Depression Storage (mm)	5
Porosity	0.30	Evaporation (mm/day)	3
Invert Level (m)	0.000	Cap Volume Depth (m)	0.650

Hydro-Brake Optimum® Outflow Control


Unit Reference	MD-SHE-0125-6600-0645-6600
Design Head (m)	0.645
Design Flow (l/s)	6.6
Flush-Flo™	Calculated
Objective	Minimise upstream storage
Diameter (mm)	125
Invert Level (m)	0.000
Minimum Outlet Pipe Diameter (mm)	150
Suggested Manhole Diameter (mm)	1200

Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	0.645	6.6
Flush-Flo™	0.212	6.6
Kick-Flo®	0.462	5.6
Mean Flow over Head Range	-	5.5

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake Optimum® as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	4.5	1.200	8.8	3.000	13.5	7.000	20.3
0.200	6.6	1.400	9.4	3.500	14.6	7.500	21.0
0.300	6.4	1.600	10.1	4.000	15.5	8.000	21.7
0.400	6.1	1.800	10.6	4.500	16.4	8.500	22.4
0.500	5.8	2.000	11.2	5.000	17.3	9.000	23.0
0.600	6.3	2.200	11.7	5.500	18.1	9.500	23.6
0.800	7.3	2.400	12.2	6.000	18.9		
1.000	8.1	2.600	12.7	6.500	19.5		

©1982-2014 XP Solutions

Price & Myers		Page 1
30 Newman Street London W1T 1LT		
Date 21/11/2014 16:33 File WEST SITE - LIDDELL ROA...	Designed by kburwood Checked by	
Micro Drainage		
Source Control 2014.1.1		

Summary of Results for 100 year Return Period (+30%)

Half Drain Time : 341 minutes.

Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control (l/s)	Max Σ Outflow (l/s)	Max Volume (m³)	Status
15 min Summer	8.892	0.392	0.0	8.4	8.4	164.0	O K
30 min Summer	8.999	0.499	0.0	8.4	8.4	208.8	O K
60 min Summer	9.095	0.595	0.0	8.4	8.4	248.6	O K
120 min Summer	9.166	0.666	0.0	8.4	8.4	278.3	O K
180 min Summer	9.186	0.686	0.0	8.4	8.4	286.6	O K
240 min Summer	9.184	0.684	0.0	8.4	8.4	285.9	O K
360 min Summer	9.164	0.664	0.0	8.4	8.4	277.4	O K
480 min Summer	9.142	0.642	0.0	8.4	8.4	268.2	O K
600 min Summer	9.118	0.618	0.0	8.4	8.4	258.5	O K
720 min Summer	9.095	0.595	0.0	8.4	8.4	248.5	O K
960 min Summer	9.047	0.547	0.0	8.4	8.4	228.7	O K
1440 min Summer	8.959	0.459	0.0	8.4	8.4	191.7	O K
2160 min Summer	8.850	0.350	0.0	8.4	8.4	146.2	O K
2880 min Summer	8.770	0.270	0.0	8.2	8.2	112.7	O K
4320 min Summer	8.676	0.176	0.0	7.7	7.7	73.4	O K
5760 min Summer	8.637	0.137	0.0	6.8	6.8	57.4	O K
7200 min Summer	8.619	0.119	0.0	5.9	5.9	49.7	O K
8640 min Summer	8.607	0.107	0.0	5.2	5.2	44.6	O K
10080 min Summer	8.598	0.098	0.0	4.6	4.6	41.0	O K
15 min Winter	8.941	0.441	0.0	8.4	8.4	184.3	O K

Storm Event	Rain (mm/hr)	Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)
15 min Summer	139.338	0.0	166.2	18
30 min Summer	90.071	0.0	215.6	33
60 min Summer	55.351	0.0	268.0	62
120 min Summer	32.840	0.0	318.3	122
180 min Summer	23.880	0.0	347.3	182
240 min Summer	18.941	0.0	367.3	240
360 min Summer	13.666	0.0	397.6	304
480 min Summer	10.831	0.0	420.2	362
600 min Summer	9.038	0.0	438.3	424
720 min Summer	7.792	0.0	453.5	492
960 min Summer	6.162	0.0	478.2	624
1440 min Summer	4.421	0.0	514.3	882
2160 min Summer	3.167	0.0	554.7	1256
2880 min Summer	2.498	0.0	583.1	1612
4320 min Summer	1.785	0.0	624.0	2292
5760 min Summer	1.406	0.0	657.1	2952
7200 min Summer	1.167	0.0	681.8	3680
8640 min Summer	1.002	0.0	702.3	4408
10080 min Summer	0.881	0.0	719.2	5136
15 min Winter	139.338	0.0	186.4	18

Price & Myers

30 Newman Street

London


W1T 1LT

Date 21/11/2014 16:33

File WEST SITE - LIDDELL ROA...

Micro Drainage

Page 2



Designed by kburwood

Checked by


Source Control 2014.1.1

Summary of Results for 100 year Return Period (+30%)

Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control (l/s)	Max E Outflow (l/s)	Max Volume (m³)	Status
30 min Winter	9.062	0.562	0.0	8.4	8.4	234.9	O K
60 min Winter	9.172	0.672	0.0	8.4	8.4	280.8	O K
120 min Winter	9.259	0.759	0.0	8.4	8.4	317.1	O K
180 min Winter	9.288	0.788	0.0	8.4	8.4	329.5	O K
240 min Winter	9.294	0.794	0.0	8.4	8.4	331.8	O K
360 min Winter	9.279	0.779	0.0	8.4	8.4	325.7	O K
480 min Winter	9.243	0.743	0.0	8.4	8.4	310.5	O K
600 min Winter	9.209	0.709	0.0	8.4	8.4	296.2	O K
720 min Winter	9.174	0.674	0.0	8.4	8.4	281.7	O K
960 min Winter	9.103	0.603	0.0	8.4	8.4	252.0	O K
1440 min Winter	8.969	0.469	0.0	8.4	8.4	195.9	O K
2160 min Winter	8.811	0.311	0.0	8.3	8.3	129.9	O K
2880 min Winter	8.710	0.210	0.0	8.0	8.0	87.8	O K
4320 min Winter	8.633	0.133	0.0	6.6	6.6	55.5	O K
5760 min Winter	8.609	0.109	0.0	5.3	5.3	45.6	O K
7200 min Winter	8.596	0.096	0.0	4.4	4.4	40.1	O K
8640 min Winter	8.587	0.087	0.0	3.8	3.8	36.4	O K
10080 min Winter	8.580	0.080	0.0	3.4	3.4	33.6	O K

Storm Event	Rain (mm/hr)	Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)
30 min Winter	90.071	0.0	241.7	33
60 min Winter	55.351	0.0	300.4	62
120 min Winter	32.840	0.0	356.6	120
180 min Winter	23.880	0.0	389.1	178
240 min Winter	18.941	0.0	411.6	234
360 min Winter	13.666	0.0	445.5	346
480 min Winter	10.831	0.0	470.8	440
600 min Winter	9.038	0.0	491.1	466
720 min Winter	7.792	0.0	508.1	540
960 min Winter	6.162	0.0	535.7	684
1440 min Winter	4.421	0.0	576.3	954
2160 min Winter	3.167	0.0	621.4	1320
2880 min Winter	2.498	0.0	653.2	1644
4320 min Winter	1.785	0.0	699.3	2288
5760 min Winter	1.406	0.0	736.0	2992
7200 min Winter	1.167	0.0	763.8	3680
8640 min Winter	1.002	0.0	786.8	4408
10080 min Winter	0.881	0.0	806.0	5144

©1982-2014 XP Solutions

Price & Myers		Page 3
30 Newman Street London W1T 1LT		
Date 21/11/2014 16:33 File WEST SITE - LIDDELL ROA...	Designed by kburwood Checked by	
Micro Drainage Source Control 2014.1.1		

Rainfall Details


Rainfall Model	FSR	Winter Storms	Yes
Return Period (years)	100	Cv (Summer)	0.750
Region	England and Wales	Cv (Winter)	0.840
M5-60 (mm)	21.000	Shortest Storm (mins)	15
Ratio R	0.435	Longest Storm (mins)	10080
Summer Storms	Yes	Climate Change %	+30

Time Area Diagram

Total Area (ha) 0.650

Time (mins)	Area
From:	To: (ha)
0	4 0.650

©1982-2014 XP Solutions

Price & Myers		Page 4
30 Newman Street London W1T 1LT		
Date 21/11/2014 16:33 File WEST SITE - LIDDELL ROA...	Designed by kburwood Checked by	
Micro Drainage Source Control 2014.1.1		

Model Details

Storage is Online Cover Level (m) 10.000

Cellular Storage Structure

Invert Level (m) 8.500 Safety Factor 2.0
Infiltration Coefficient Base (m/hr) 0.00000 Porosity 0.95
Infiltration Coefficient Side (m/hr) 0.00000

Depth (m)	Area (m ²)	Inf. Area (m ²)	Depth (m)	Area (m ²)	Inf. Area (m ²)
0.000	440.0	440.0	0.900	0.0	507.2
0.800	440.0	507.2			

Hydro-Brake Optimum® Outflow Control

Unit Reference MD-SHE-0131-8400-1200-8400
Design Head (m) 1.200
Design Flow (l/s) 8.4
Flush-Flo™ Calculated
Objective Minimise upstream storage
Diameter (mm) 131
Invert Level (m) 8.500
Minimum Outlet Pipe Diameter (mm) 150
Suggested Manhole Diameter (mm) 1200

Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	1.200	8.4
Flush-Flo™	0.355	8.4
Kick-Flo®	0.768	6.8
Mean Flow over Head Range	-	7.3

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake Optimum® as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	4.7	1.200	8.4	3.000	12.9	7.000	19.3
0.200	7.9	1.400	9.0	3.500	13.9	7.500	20.0
0.300	8.3	1.600	9.6	4.000	14.8	8.000	20.6
0.400	8.3	1.800	10.1	4.500	15.6	8.500	21.2
0.500	8.2	2.000	10.6	5.000	16.4	9.000	21.8
0.600	7.9	2.200	11.1	5.500	17.2	9.500	22.4
0.800	6.9	2.400	11.6	6.000	17.9		
1.000	7.7	2.600	12.0	6.500	18.6		

©1982-2014 XP Solutions