

LEVOLUX

Drawing No.

CI/SfB

57

G.A. 950/SCR/140/01

Specification

system supplied and installed by Levolux Limited Tel: 020 8863 9111 or Levolux A.T. Limited Tel: 01452 500007. Manufacturer and reference: Levolux 140 XL screening louvre

stainless steel cleats. louvre mounted on mullions fixed to structure with adjustable Description: Levolux 140 XL continuous appearance screening

Blade Pitch: 140mm

Material: Manufactured from extruded aluminium alloy 6063 T6.

microns/anodised AA25/mill/PVDF. Finish: Polyester powder coated to RAL, average 60

support arms 1800mm. Dimensions: As shown on drawings; maximum span between

Performance: To have sight cut off at approximately 0°

Fixing: To subcontractors details

screening system:-Accessories: The following accessories are available with the

- Bird/insect mesh
- Insulated/blanking plate
- Single or double door access
- Screen may be mitred/flashed

LEVOLUX

LEVOLUX LIMITED
Forward Drive, Harrow, Middlesex HA3 8NT
Telephone (+44) 020 8863 9111
Facsimile (+44) 020 8863 8760

LEVOLUX A.T. LIMITED

24 Eastville Close, Gloucester GL4 3SJ Telephone (+44) 01452 500007 Facsimile (+44) 01452 527496 web: www.levolux.com



00 LOUVRES TO.....

Drawing references:....

Manufacturer and reference: Levolux 950 140XL screen louvre system supplied

and installed by Levolux Ltd. Tel: 020 8863 9111.

Description: Extruded aluminium Z profile louvre fixed to structural mullions at 1500mm centres, fixed back to the cladding rails with stainless steel cleats

Blade Pitch: 140mm inverted

Material: Manufactured from extruded aluminium to BS1474 Alloy to 6063 T6.

Finish: Polyester powder coated to RAL

(anodised AA25 louvers only)

Dimensions: As shown on drawings.

Corners: Mitred or alternative corner flashing

Fixing: minimum grade A2 fixings

Accessories: Single/double doors using high quality extruded aluminium door

design with bespoke extrusions especially for the purpose of louvres.

