



# SIEMENS MRI Chiller Installation Guide

## Applicable for;

|                     |           |            |
|---------------------|-----------|------------|
| Aera with SEP 45    | use model | ICE076/MRI |
| Aera with SEP 60    | use model | ICE090/MRI |
| Avanto with SEP 45  | use model | ICE076/MRI |
| Avanto with SEP 60  | use model | ICE090/MRI |
| Espreo with SEP     | use model | ICE076/MRI |
| Essenza ICS Passive | use model | ICE029/MRI |
| Skyra with SEP 60   | use model | ICE090/MRI |
| Symphony with RCA   | use model | ICE046/MRI |
| Sonata              | Use model | ICE076/MRI |
| Trio with SEP       | use model | ICE090/MRI |
| Verio with SEP      | use model | ICE090/MRI |

This document is provided to help with the planning and installation of Parker Hiross ICE chillers when used with Siemens MRI Scanners and should be used together with the Hiross Operation and Maintenance Manual.

All sections of this guide are relevant to the chiller installation.

## INDEX

- 1) Chiller Positioning/Drawings
- 2) Pipe Work
- 3) Flow Meter
- 4) Mains Water Auto Top-Up Kit
- 5) Electrical Connection
- 6) Remote Panel Wiring
- 7) Glycol / Chemicals
- 8) Pre-Commissioning
- 9) Noise Information
- 10) Centrifugal Fan Option
- 11) Contacts

# 1) Chiller Positioning

Chiller are normally located externally. If located internally, centrifugal fans may be required to allow ductwork to be installed to reject heat outside the building.


The unit should be positioned with an area of free space on all four sides to accommodate service and maintenance requirements.

The condensers on both sides of the unit require an un-inhibited passage of air in order to work correctly. Ideally a minimum gap of 750mm should be left. Refer to chiller GA drawing for dimensions. Please seek advice if site limitations restrict free space.

If the chiller is located directly onto steelwork and/or onto a roof, it should be mounted on "anti vibration mounts".


**WARNING; The chillers operational performance will be compromised if air-flow is significantly restricted, or warm air from other equipment is being drawn through the chillers' condensers.**

Fig. 4 Overall dimensions ICE076 – 116 (axial version)



| model  | weight (Kg) | refrigerant / charge R407C (Kg) | F.L.A. [A] (400V 3~ 50Hz) |          |           | max. water inlet temperature | ambient temperature |           | in/out water connections | max. water pressure |          |       |
|--------|-------------|---------------------------------|---------------------------|----------|-----------|------------------------------|---------------------|-----------|--------------------------|---------------------|----------|-------|
|        |             |                                 | compressors               | fans     | pump (P3) |                              | pump (P1)           | pump (P5) |                          |                     | min.     | max.  |
| ICE076 | 800         | 2 x 8.5                         | 2 x 19.2                  | 3 x 1.35 | 4.6       | 2.9                          | 2 x 4.6             | 30 °C     | 5 °C                     | 45 °C               | 2" BSP-F | 6 bar |
| ICE090 | 900         | 2 x 9.5                         | 2 x 25.6                  | 3 x 1.35 | 4.9       | 2.9                          | 2 x 4.6             |           |                          |                     |          |       |
| ICE116 | 1000        | 2 x 13                          | 2 x 27.8                  | 3 x 1.35 | 4.9       | 2.9                          | 2 x 4.6             |           |                          |                     |          |       |


Fig. 2 Overall dimensions (ICE039–046)



- Model  
 A ICE039 = 380  
 ICE046 = 370  
 B ICE039 = 160  
 ICE046 = 150  
 C ICE039 = 380  
 ICE046 = 370

| model  | weight (Kg) | refrigerant / charge R407C (Kg) | compressor | fan  | E.L.A. [A] (400V 3~ 50Hz) |                |                | max. water inlet temperature 30 °C | ambient temperature |      | in/out water connections 1½" BSP-F | max. water pressure 6 bar |
|--------|-------------|---------------------------------|------------|------|---------------------------|----------------|----------------|------------------------------------|---------------------|------|------------------------------------|---------------------------|
|        |             |                                 |            |      | pump (P3) std.            | pump (P1) opt. | pump (P5) opt. |                                    | min.                | max. |                                    |                           |
| ICE039 | 390         | 8.62                            | 19.2       | 1.15 | 2.4                       | 2.2            | 5.2            | 5 °C                               | 45 °C               |      |                                    |                           |
| ICE046 | 410         | 9.6                             | 25.6       | 1.15 | 4.4                       | 2.2            | 5.2            |                                    |                     |      |                                    |                           |

Fig. 2 Overall dimensions (ICE029)



| model  | weight (Kg) | refrigerant / charge R407C (Kg) | compressor | fan  | E.L.A. [A] (400V 3~50Hz) |                |                | max. water inlet temperature | ambient temperature |       | in/out water connections | max. water pressure |
|--------|-------------|---------------------------------|------------|------|--------------------------|----------------|----------------|------------------------------|---------------------|-------|--------------------------|---------------------|
|        |             |                                 |            |      | pump (P3) std.           | pump (P1) opt. | pump (P5) opt. |                              | min.                | max.  |                          |                     |
| ICE029 | 360         | 6.8                             | 16         | 1.35 | 2.4                      | 2.2            | 5.2            | 30 °C                        | 5 °C                | 45 °C | 1 1/2" BSP-F             | 6 bar               |

Code: 271643 - Hyperchill


## 2) Pipe Work

### a) Connections

Care should be taken when making up pipe work to the threaded connections on the chiller. Ensure adequate retention of the chiller connections when tightening to prevent chiller connections rotating inside the chiller.

### b) Schematic Drawing

Recommended pipe work layout.




### 3) Flow Meter

A Flow Meter should be fitted as indicated in the pipe work schematic. The unit should be capable of accurately measuring the specified nominal flow (see table below) based on the Siemens Planning Guide.

The Flow Meter is critical for setting flows during the commissioning process.

|                     |              |                |
|---------------------|--------------|----------------|
| Aera with SEP 45    | Nominal Flow | 80 Litres/Min  |
| Aera with SEP 60    | Nominal Flow | 100 Litres/Min |
| Avanto with SEP 45  | Nominal Flow | 90 Litres/Min  |
| Avanto with SEP 60  | Nominal Flow | 110 Litres/Min |
| Esprea with SEP     | Nominal Flow | 90 Litres/Min  |
| Essenza ICS Passive | Nominal Flow | 30 Litres/Min  |
| Skyra with SEP 60   | Nominal Flow | 100 Litres/Min |
| Symphony with RCA   | Nominal Flow | 60 Litres/Min  |
| Sonata              | Nominal Flow | 90 Litres/Min  |
| Trio with SEP       | Nominal Flow | 90 Litres/Min  |
| Verio with SEP      | Nominal Flow | 90 Litres/Min  |

A typical unit available from RS Components.







## 4) Pressurised Auto Mains Fill Kit

This kit needs to be installed onto the chiller and negates the need for any flood-back protection as the chilled water circuit runs as a closed loop.

A mains water feed (with local isolating valve) is required to connect into the pressure regulating valve as shown below. **A double check valve should be fitted into the mains water feed to comply with local water regulations.**



## 5) Electrical Connection

Initial Checks;

After electrical installation the unit should be checked for correct phase rotation.

**IMPORTANT:**

This should be done before switching the unit on by manually engaging the fan contactor (KM5) and observing correct rotation of the fan blades. Air movement should be vertically upwards.

Reverse rotation will cause damage to the chiller and invalidate the manufacturers warranty.

Under no circumstances should the pump be run without the chiller tank being full of water.

**WARNING; 400/415 Volts Live Panel !**

### Chiller Maximum Running Currents

|            |        |
|------------|--------|
| ICE090/MRI | 58amps |
| ICE076/MRI | 48amps |
| ICE046/MRI | 31amps |
| ICE029/MRI | 19amps |

## 6) Remote Panel

The chillers' main controller has been factory configured to operate with the remote panel connected or disconnected.


A 6-way telephone/data cable should be installed from remote panel to the interface board located inside the chiller electrical panel. For reference, the RS Components part numbers are as follows;

|               |          |
|---------------|----------|
| Cable         | 361-232  |
| Plugs         | 331-6364 |
| Crimping tool | 443-895  |
| Die set       | 443-930  |

### New Hiross Remote Panel



# Remote Panel Wiring Diagram



## 7) Glycol

The ICE MRI chiller range have built-in Frost Protection by way of Frost Stat with Pump Override, however;

Ethylene Glycol (blended with inhibitors) can also be added to the water system to provide anti-freeze protection (during power failure) and to help maintain the fluid system condition. A mix of 20% by volume is recommended.

The fluid system should be flushed and leak tested with water prior to refilling with the Anti-Freeze mix.

**WARNING; The chiller water circuit contains the following metals;**

- Copper
- Aluminium
- Stainless Steel

**Care must be taken to ensure any chemical used to flush, clean, or maintain the water system is compatible with the above metals.**

## 8) Pre-Commissioning

Parker Hiross can provide a Pre-Commissioning visit by a Service Engineer to help initialise the chiller and set flow rate (through bypass at scanner end) **prior to Siemens Engineers commissioning the scanner.**

This visit can be booked with Parker Hiross to coincide, or following completion of;

- a. Chiller installed with power and remote cable.
- b. Mains water feed connected.
- c. Chilled water pipe work installed, pressure tested and flushed.

Please contact to book visit;

Parker Hiross - Tel; 01926 317803  
Fax; 01927 317855

Or

Gary Downs - Mob; 07980210927  
Gary.Downs@parker.com

## 9) Noise Information

For the purpose of providing accurate noise data the Hiross ICE MRI chillers have been independently noise tested to the criteria set out in BS EN ISO 3746:1996.

The data below can be used by acoustic engineers to design noise attenuation where necessary.

| Chiller Model    | Acoustic Sound Power Level At Source dB LA-w/Lp-w At Preferred Octave Band Centres Hz |       |       |       |       |       |       |       |    |    |
|------------------|---|-------|-------|-------|-------|-------|-------|-------|----|----|
|                  | 63  | 125   | 250   | 500   | 1k    | 2k    | 4k    | 8k    | A  | AP |
| 022 Axial 1 fan  | 57/83   | 69/85 | 71/80 | 77/80 | 81/81 | 78/77 | 70/69 | 61/62 | 85 | 92 |
| 029 Axial 1 fan  | 54/80   | 65/81 | 72/81 | 78/81 | 82/82 | 79/78 | 70/69 | 62/63 | 85 | 92 |
| 039 Axial 2 fan  | 54/80   | 66/82 | 73/82 | 80/83 | 83/83 | 80/79 | 70/69 | 63/64 | 86 | 93 |
| 046 Axial 2 fans | 54/80   | 67/83 | 75/84 | 82/85 | 84/84 | 81/80 | 72/71 | 64/65 | 88 | 94 |
| 057 Axial 3 fans | 55/81   | 68/84 | 76/85 | 84/87 | 86/86 | 82/81 | 73/72 | 65/66 | 89 | 95 |
| 076 Axial 3 fans | 55/81   | 69/85 | 78/87 | 87/90 | 87/87 | 81/80 | 75/74 | 66/67 | 91 | 96 |
| 090 Axial 3 fans | 55/81   | 69/85 | 79/88 | 87/90 | 88/88 | 84/83 | 77/76 | 67/68 | 92 | 97 |

## 10) Centrifugal Fan Option

The chiller can be supplied with centrifugal fans fitted for projects where the chiller needs to be located internally and ductwork fitted to the fans.

### Important

It is essential that VCD's (variable control dampers) are fitted to all three ducts above each fan to allow for correct commissioning.

Drawings and costings are available on request.

## 11) Contacts

### Main Contact - Technical Sales & Support

Gary Downs

Mob: 07980210927

[Gary.Downs@parker.com](mailto:Gary.Downs@parker.com)

### Parker Hiross Technical Support

Kirk Reid

Office

Tel: 01926 317803

Fax: 01926 317855

[Kirk.Reid@parker.com](mailto:Kirk.Reid@parker.com)