Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)





SAFETY DATA SHEET

WEATHERSHIELD SMOOTH MASONRY PAINT

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1. Product identifier Product name	: WEATHERSHIELD SMOOTH MASONRY PAINT
1.2. Relevant identified uses	of the substance or mixture and uses advised against
Product use	: Waterborne coating for exterior use.
1.3. Details of the supplier of t	he safety data sheet ICI Paints AkzoNobel, Wexham Road, Slough, Berkshire, SL2 5DS, U.K. Tel.: +44 (0) 333 222 70 70 www.duluxtrade.co.uk
e-mail address of person responsible for this SDS	: duluxtrade.advice@akzonobel.com
1.4 Emergency telephone num Telephone number	iber : Emergency Telephone:Slough +44 (0) 1753 550000

Version	:	5
Date of previous issue	:	15-7-2014.

SECTION 2: Hazards identification

2.1. Classification of the sul	ostance or mixture
Product definition	: Mixture
Classification according to Aquatic Chronic 3, H412	Regulation (EC) No. 1272/2008 [CLP/GHS]
Ingredients of unknown toxicity	: 0%
Ingredients of unknown ecotoxicity	: 0%
Classification according to	Directive 1999/45/EC [DPD]
The product is classified as	a dangerous according to Directive 1999/45/EC and its amendments.
Classification	: R52/53
Environmental hazards	: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SECTION 2: Hazards identification

See Section 16 for the full text of the R phrases or H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2. Label elements		
Signal word	:	No signal word.
Hazard statements	1	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
General	1	P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	4	P262 - Do not get in eyes, on skin, or on clothing.
Response	1	312 - Call a POISON CENTER or physician if you feel unwell.
Storage	1	Not applicable.
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
Supplemental label elements	:	Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 1, 2-benzisothiazol-3(2H)-one and octhilinone (ISO). May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3. Other hazards		

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

			<u>Cla</u>	<u>ssification</u>	
Product/ingredient name	Identifiers	% (w/w)	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
pronopol (INN)	EC: 200-143-0 CAS: 52-51-7 Index: 603-085-00-8	<0,1	Xn; R21/22 Xi; R41, R37/38 N; R50	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 (Respiratory tract irritation) Aquatic Acute 1, H400	[1]
Terbutryn	EC: 212-950-5	>=0, 0025 - <0,025	Xn; R22	Acute Tox. 4, H302	[1]
	CAS: 886-50-0 Index: 3.1: self classification 3.2: Selfclassified		R43 N; R50/53	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	
pyrithione zinc	EC: 236-671-3 CAS: 13463-41-7	<0,1	T; R23 Xn; R22 Xi; R41 N; R50	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Aquatic Acute 1, H400	[1]

SECTION 3: Composition/information on ingredients

	_		-	1
octhilinone (ISO)	EC: 247-761-7	<0,025	T; R23/24	Acute Tox. 4, H302
	CAS: 26530-20-1		Xn; R22	Acute Tox. 3, H311
	Index: 613-112-00-5		C; R34	Acute Tox. 3, H331
			R43	Skin Corr. 1B, H314
			N; R50/53	Eye Dam. 1, H318
				Skin Sens. 1, H317
				Aquatic Acute 1, H400
				Aquatic Chronic 1, H410
			See Section 16 for	See Section 16 for the
			the full text of the R-	full text of the H
			phrases declared	statements declared
			above.	above.
			45010.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1. Description of first aid measures

the second se	
General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	 Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aid	ers : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the EC 1272/2008 regulation and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

WEATHERSHIELD SMOOTH MASONRY PAINT

SECTION 4: First aid measures

Specific treatments

: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures				
5.1. Extinguishing media Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray.			
Unsuitable extinguishing media	: Do not use water jet.			
5.2. Special hazards arising	from the substance or mixture			
Hazards from the substance or mixture	: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.			
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.			
5.3. Advice for firefighters				
Special protective actions for fire-fighters	: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.			
Special protective equipment for fire-fighters	: Appropriate breathing apparatus may be required.			

SECTION 6: Accidental release measures

6.1. Personal precautions, pro	ote	ective equipment and emergency procedures
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2. Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.
6.3. Methods and material for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.
6.4. Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling	 Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used.
	Reep away from heat, sparks and hame. No sparking tools should be used.

SECTION 7: Handling and storage

	 Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses. Information on fire and explosion protection Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
7.2 Conditions for safe	Store in accordance with local regulations.
storage, including any incompatibilities	Notes on joint storage Keep away from: oxidising agents, strong alkalis, strong acids.
	Additional information on storage conditions
	Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker or exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Recommended monitoring If this product contains ingredients with exposure limits, personal, workplace 2 atmosphere or biological monitoring may be required to determine the procedures effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres -General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering	: Provide adequate ventilation. Where reasonably practicable, this should be
controls	achieved by the use of local exhaust ventilation and good general extraction. If
	these are not sufficient to maintain concentrations of particulates and solvent
	vapours below the OEL, suitable respiratory protection must be worn.

SECTION 8: Exposure controls/personal protection

•	· ·
Individual protection measu	<u>'es</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Use safety eyewear designed to protect against splash of liquids.
Skin protection	
Hand protection	
There is no one glove met	orial or combination of materials that will give unlimited resistance to any individual or

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has

occurred.	
Gloves	 For prolonged or repeated contact use protective gloves. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred. Skin should be washed after contact. Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended gloves: Viton® or
	Nitrile Breakthrough Time: 480 min
	When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended.
	NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.
	The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.
Body protection	 Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

SECTION 8: Exposure controls/personal protection

Respiratory protection	: Fworkers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
	OLD LEAD-BASED PAINTS:
	When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead-pigmented paint might be present There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.
	Where possible wet sanding or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry sanding cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.
	Respiratory protection in case of dust or spray mist formation. (particle filter EN143 type P2) Rrespiratory protection in case of vapour formation. (half mask with combination filter A2-P2 till concentrations of 0,5 Vol%.)
	The current Control of Lead at Work Regulations approved code of practice should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting contractor as Hazardous Waste.
	Extra precautions will also need to be taken when burning off old lead-based paints because fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Similar precautions to those given above about sanding should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.
	Avoid the inhalation of dust. Wear suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.
Environmental exposure controls	: Do not allow to enter drains or watercourses.

SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties

1	Liquid.
1	Not available.
4	Not available.
:	100°C
4	Not applicable.
1	Not available.
:	Not available.

SECTION 9: Physical and chemical properties

	• •
Vapour pressure	: Not available.
Vapour density	: Not available.
Relative density	: 1,361
Solubility(ies)	: Easily soluble in the following materials: cold water.
Solubility in water	: Not available.
Partition coefficient: n-octanol/ water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 5,15 cm ² /s
Explosive properties	: Not available.
Oxidising properties	: Not available.
9.2. Other information	

No additional information.

SECTION 10: Stability and reactivity 10.1. Reactivity : No specific test data related to reactivity available for this product or its ingredients. : Stable under recommended storage and handling conditions (see Section 7). **10.2.** Chemical stability 10.3. Possibility of : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4. Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products. **10.5.** Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. Under normal conditions of storage and use, hazardous decomposition products 10.6. Hazardous should not be produced. decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the EC 1272/2008 regulation and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Conclusion/Summary : Not available.

Acute toxicity estimates

Not available.

Irritation/Corrosion

SECTION 11: Toxicological information

			1		
Product/ingredient name	Result	Species	Score	Exposure	Observation
bronopol (INN)	Skin - Moderate irritant	Human	-	-	-
	Skin - Mild irritant	Rabbit	-	-	-
	Skin - Moderate irritant	Rabbit	-	-	-
Terbutryn	Eyes - Moderate irritant	Rabbit	-	-	-
	Skin - Mild irritant	Rabbit	-	-	-
octhilinone (ISO)	Eyes - Severe irritant	Rabbit	-	-	-
Conclusion/Summary	: Not available.				
Sensitisation					
Conclusion/Summary	: Not available.				
Mutagenicity					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
Teratogenicity					
Conclusion/Summary	: Not available.				
Specific target organ toxicit	<u>y (single exposure)</u>				

Product/ingredient name	Category	Route of exposure	Target organs
bronopol (INN)	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Other information

: Not available.

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the EC 1272/2008 regulation and is classified for ecotoxicological properties accordingly. See sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
Terbutryn	Acute EC50 1,4 to 2,66 mg/l Acute IC50 0,0036 mg/l	Daphnia Algae - (Selenastrum capricornutum	48 hours 72 hours
	Acute LC50 1,3 mg/l Acute LC50 1,1 mg/l	Fish - Lepomis Macrochirus Fish - Oncorhynchus Mykiss	96 hours 96 hours

Conclusion/Summary

: Not available.

12.2. Persistence and degradability

Conclusion/Summary	: Not available.
12.3. Bioaccumulative pote	ential
12.4. Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

SECTION 12: Ecological information

12.5. Results of PBT and vPvB	B assessment
PBT	: Not applicable.
	P: Not available. B: Not available. T: Not available.
vPvB	: Not applicable.
	vP: Not available. vB: Not available.
12.6. Other adverse effects	: No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	The classification of the product may meet the criteria for a hazardous waste.
Disposal considerations	Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.
Packaging	
Methods of disposal	The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Disposal considerations	 Vising information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

	ADR	IMDG
14.1. UN number	Not regulated.	Not regulated.
14.2. UN proper shipping name	-	-
14.3. Transport hazard class(es) Class	-	-
Subsidiary class	-	-
14.4. Packing group	-	-
14.5. Environmental hazards		

Date of issue/Date of revision : 20-9-2014.

•	No. Not available. sport in closed containers that are upright and oduct know what to do in the event of an accident Not applicable.		
t within user's premises: always trans nsure that persons transporting the pro Not available.	Not available. sport in closed containers that are upright and oduct know what to do in the event of an accident		
nsure that persons transporting the pro Not available.	sport in closed containers that are upright and oduct know what to do in the event of an accident		
nsure that persons transporting the pro Not available.	oduct know what to do in the event of an accident		
	Not applicable.		
: Not applicable.	Not applicable.		
: Not applicable.			
-	-		
tory information			
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV Annex XIV None of the components are listed. Substances of very high concern None of the components are listed. Annex XIV None of the components are listed. Annex XIV II - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Other EU regulations VOC : Not available. Europe inventory : At least one component is not listed. Seveso II Directive Fils product is not controlled under the Seveso II Directive. International regulations Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed. Stockholm Convention on Persistent Organic Pollutants Not listed. Rotterdam Convention on Prior Inform Consent (PIC) Not listed. UNECE Aarhus Protocol on POPs and Heavy Metals			
	At least one component is not listed under the Seveso II Directive. Directive. A. B. C. E) ersistent Organic Pollutants rior Inform Consent (PIC)		

SECTION 15: Regulatory information

15.2 Chemical Safety Assessment : Not applicable.

SECTION 16: Other information

CEPE code

 \checkmark Indicates information that has changed from previously issued version.

: 1

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate
-	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classificat	ion	Justification
Aquatic Chronic 3, H412		Calculation method
Full text of abbreviated H : statements	▶302 H311 H312 H314 H315 H317 H318 H331 H335 (Respiratory tract irritation) H400 H410 H412	Harmful if swallowed. Toxic in contact with skin. Harmful in contact with skin. Causes severe skin burns and eye damage. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic if inhaled. May cause respiratory irritation. (Respiratory tract irritation) Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.
Full text of classifications : [CLP/GHS]	Acute Tox. 3, H311 Acute Tox. 3, H331 Acute Tox. 4, H302 Acute Tox. 4, H302 Acute Tox. 4, H312 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Aquatic Chronic 3, H412 Eye Dam. 1, H318 Skin Corr. 1B, H314 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 (Respiratory tract irritation)	
Full text of abbreviated R : phrases	R22- Harmful if swallowed R21/22- Harmful in contac R34- Causes burns. R41- Risk of serious dama R37/38- Irritating to respir R43- May cause sensitisa R50- Very toxic to aquatio R50/53- Very toxic to aquat the aquatic environment.	ct with skin and if swallowed. age to eyes. atory system and skin. tion by skin contact.

SECTION 16: Other information

Full text of classifications [DSD/DPD]	: T - Toxic C - Corrosive Xn - Harmful Xi - Irritant
	N - Dangerous for the environment
Date of printing	: 24-9-2014.
Date of issue/ Date of revision	: 20-9-2014.
Date of previous issue	: 15-7-2014.
Version	: 5
Notice to reader	

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

Akzo Nobel Decorative Coatings B.V, Rijksstraatweg 31, 2171 AJ Sassenheim, the Netherlands