

**BOX LINTELS**

**BOX 100**


Used to support openings in 100mm wide walls. Lintels may be propped to facilitate speed of construction. See Lintel Installation on page 12.



<b>BOX 100</b>							
Manufactured length 150mm increments	600- 1500	1650- 2100	2250- 2400	2550- 2700	2850- 3600	3750- 4200	4350- 4800
Height 'h'	75	150	150	150	215	215	215
Thickness	1.6	2.0	2.0	2.0	2.5	2.5	2.5
Total UDL kN	15	30	25	20	30	25	20

Used to support openings in 100mm wide walls.


**Standard Load**



<b>BOX 140</b>							
Manufactured length 150mm increments	600- 1500	1650- 2100	2250- 2400	2550- 2700	2850- 3600	3750- 4200	4350- 4800
Height 'h'	150	150	150	150	215	215	215
Thickness	1.6	2.0	2.0	2.0	2.5	2.5	2.5
Total UDL kN	15	30	25	20	35	30	25

Used to support openings in 150mm wide walls.

**Standard Load**



<b>BOX 200</b>							
Manufactured length 150mm increments	600- 1500	1650- 2100	2250- 2400	2550- 2700	2850- 3600	3750- 4200	4350- 4800
Height 'h'	150	150	150	150	215	215	215
Thickness	1.6	2.0	2.0	2.0	2.5	2.5	2.5
Total UDL kN	15	30	25	20	30	25	20

The flange of the BOX 200 is designed to support a nominal masonry load only up to a maximum of 3kN per metre run. Used to support openings in 215mm wide walls.

**Standard Load**

