

## Surface Water Drainage Pro-forma for new developments

This pro-forma accompanies our advice note on surface water drainage. Developers should complete this form and submit it to the Local Planning Authority, referencing from where in their submission documents this information is taken. The pro-forma is supported by the [Defra/EA guidance on Rainfall Runoff Management](http://www.UKsuds.com) and uses the storage calculator on [www.UKsuds.com](http://www.UKsuds.com). This pro-forma is based on current industry best practice and focuses on ensuring surface water drainage proposals meet national and local policy requirements. The pro-forma should be considered alongside other supporting SUDS Guidance.

### 1. Site Details

Site	73-75 AVENUE ROAD		
Address & post code or LPA reference	73-75 AVENUE ROAD, LONDON NW8 6TD		
Grid reference	526920, 183820		
Is the existing site developed or Greenfield?	DEVELOPED		
Is the development in a LFRZ or in an area known to be at risk of surface or ground water flooding?	NO		
Total Site Area served by drainage system (excluding open space) (Ha)*			

\* The Greenfield runoff off rate from the development which is to be used for assessing the requirements for limiting discharge flow rates and attenuation storage from a site should be calculated for the area that forms the drainage network for the whatever size of site and type of drainage technique. Please refer to the Rainfall Runoff Management document or CIRIA manual for detail on this.

### 2. Impermeable Area

	Existing	Proposed	Difference (Proposed-Existing)	Notes for developers
Impermeable area (ha)	0.073	0.105	0.032	If proposed > existing, then runoff rates and volumes will be increasing. Section 6 must be filled in. If proposed ≤ existing, then section 6 can be skipped & section 7 filled in.
Drainage Method (infiltration/sewer/watercourse)	Sewer	Sewer	N/A	If different from the existing, please fill in section 3. If existing drainage is by infiltration and the proposed is not, discharge volumes may increase. Fill in section 6.

3. Proposing to Discharge Surface Water via

	Yes	No	Evidence that this is possible	Notes for developers
Infiltration		✓	UNSUITABLE Ground CONDITION	e.g. soakage tests. Section 6 (infiltration) must be filled in if infiltration is proposed
To watercourse		✓	NO WATERCOURSE IN VICINITY	e.g. Is there a watercourse near by?
To surface water sewer	✓		THAMES WATER SEWER	Confirmation from sewer provider that sufficient capacity exists for this connection.
Combination of above		✓	N/A	e.g. part infiltration part discharge to sewer or watercourse. Provide evidence above

4. Peak Discharge Rates – This is the maximum flow rate at which storm water runoff leaves the site during a particular storm event.

	Existing Rates (l/s)	Proposed Rates (l/s)	Difference (l/s) (Proposed-Existing)	% Difference (difference /existing x 100)	Notes for developers
Greenfield QBAR	0.37	N/A	N/A	N/A	QBAR is approx. 1 in 2 storm event. Provide this if Section 6 (QBAR) is proposed.
1 in 1	11	5	-6	55	Proposed discharge rates (with mitigation) should aim to be equivalent to greenfield rates for all corresponding storm events. As a minimum, peak discharge rates must be reduced by 50% from the existing sites for all corresponding rainfall events.  The proposed 1 in 100 +CC peak discharge rate (with mitigation) should aim to be equivalent to greenfield rates. As a minimum, proposed 1 in 100 +CC peak discharge rate must be reduced by 50% from the existing 1 in 100 runoff rate sites.
1 in 30	26	5	-19	73	
1 in 100	34	5	-29	85	
1 in 100 plus climate change	N/A	5	-39	89	

5. Calculate additional volumes for storage – The total volume of water leaving the development site. New hard surfaces potentially restrict the amount of stormwater that can go to the ground, so this needs to be controlled so not to make flood risk worse to properties downstream.

	Existing Volume (m <sup>3</sup> )	Proposed Volume (m <sup>3</sup> )	Difference (m <sup>3</sup> ) (Proposed-Existing)	Notes for developers
GREENFIELD RUN OFF VOLUME	36	N/A	N/A	
1 in 1	30	28	-2	Proposed discharge volumes (with mitigation) should be constrained to a value as close as is reasonably practicable to the greenfield runoff volume wherever practicable and as a minimum should be no greater than existing volumes for all corresponding storm events. Any increase in volume increases flood risk elsewhere. Where volumes are increased section 6 must be filled in.  The proposed 1 in 100 +CC discharge volume should be constrained to a value as close as is reasonably practicable to the greenfield runoff volume wherever practicable. As a minimum, to mitigate for climate change the proposed 1 in 100 +CC volume discharge from site must be no greater than the existing 1 in 100 storm event. If not, flood risk increases under climate change.
1 in 30	27	38	1	
1 in 100 6 hour	63	75	12	
1 in 100 6 hour plus climate change	74	92	18	

6. Calculate attenuation storage – Attenuation storage is provided to enable the rate of runoff from the site into the receiving watercourse to be limited to an acceptable rate to protect against erosion and flooding downstream. The attenuation storage volume is a function of the degree of development relative to the greenfield discharge rate.

		Notes for developers
Storage Attenuation volume (Flow rate control) required to meet greenfield run off rates (m <sup>3</sup> )	59	Volume of water to attenuate on site if discharging at a greenfield run off rate. Can't be used where discharge volumes are increasing
Storage Attenuation volume (Flow rate control) required to reduce rates by 50% (m <sup>3</sup> )	22	Volume of water to attenuate on site if discharging at a 50% reduction from existing rates. Can't be used where discharge volumes are increasing
Storage Attenuation volume (Flow rate control) required to meet [OTHER RUN OFF RATE (as close to greenfield rate as possible)] (m <sup>3</sup> )	38	Volume of water to attenuate on site if discharging at a rate different from the above – please state in 1 <sup>st</sup> column what rate this volume corresponds to. On previously developed sites, runoff rates should not be more than three times the calculated greenfield rate. Can't be used where discharge volumes are increasing
Storage Attenuation volume (Flow rate control) required to retain rates as existing (m <sup>3</sup> )	10	Volume of water to attenuate on site if discharging at existing rates. Can't be used where discharge volumes are increasing

**7. How is Storm Water stored on site?**

Storage is required for the additional volume from site but also for holding back water to slow down the rate from the site. This is known as attenuation storage and long term storage. The idea is that the additional volume does not get into the watercourses, or if it does it is at an exceptionally low rate. You can either infiltrate the stored water back to ground, or if this isn't possible hold it back with on site storage. Firstly, can infiltration work on site?

Infiltration	State the Site's Geology and Known Source Protection Zones (SPZ)	N/A	Notes for developers Avoid infiltrating in made ground. Infiltration rates are highly variable and refer to Environment Agency website to identify and source protection zones (SPZ)
	Are Infiltration rates suitable?	NO	Infiltration rates should be no lower than $1 \times 10^{-4}$ m/s
	State the distance between a proposed infiltration device base and the ground water (GW) level	N/A	Need 1m (min) between the base of the infiltration device & the water table to protect Groundwater quality & ensure GW doesn't enter infiltration devices. Avoid infiltration where this isn't possible.
	Were infiltration rates obtained by desk study or infiltration test?	N/A	Infiltration rates can be estimated from desk studies at most stages of the planning system if a back up attenuation scheme is provided.
	Is the site contaminated? If yes, consider advice from others on whether infiltration can happen.	No	Advice on contaminated Land in Camden can be found on our supporting documents webpage. Water should not be infiltrated through land that is contaminated. The Environment Agency may provide bespoke advice in planning consultations for contaminated sites that should be considered.
In light of the above, is infiltration feasible?	Yes/No? If the answer is No, please identify how the storm water will be stored prior to release	WITHIN SUB-BASE OF PERMEABLE PAVING	If infiltration is not feasible how will the additional volume be stored? The applicant should then consider the following options in the next section.

**Storage requirements**

The developer must confirm that either of the two methods for dealing with the amount of water that needs to be stored on site.

**Option 1 Simple** – Store both the additional volume and attenuation volume in order to make a final discharge from site at the greenfield runoff rate. This is preferred if no infiltration can be made on site. This very simply satisfies the runoff rates and volume criteria.

**Option 2 Complex** – If some of the additional volume of water can be infiltrated back into the ground, the remainder can be discharged at a very low rate of 2 l/sec/hectare. A combined storage calculation using the partial permissible rate of 2 l/sec/hectare and the attenuation rate used to slow the runoff from site.

Please confirm what option has been chosen and how much storage is required on site.	OPTION 2 BUT AT SUs WITH 38m <sup>3</sup> OF STORAGE	Notes for developers The developer at this stage should have an idea of the site characteristics and be able to explain what the storage requirements are on site and how it will be achieved.
--	--	---

**8. Please confirm**

Which Drainage Systems measures have been used?	Flow control CHANGE AND SUB-BASE ATTENUATION	Notes for developers
Drainage system can contain in the 1 in 30 storm event without flooding	YES	SUDS can be adapted for most situations even where infiltration isn't feasible e.g. impermeable liners beneath some SUDS devices allows treatment but not infiltration. See CIRIA SUDS Manual C697.
Drainage system can contain in the 1 in 100 storm event without flooding	YES	This a requirement for sewers for adoption & is good practice even where drainage system is not adopted. National standards require that the drainage system is designed so that flooding does not occur during a 1 in 100 year rainfall event in any part of a building (including a basement), or in any utility plant susceptible to water (e.g. pumping station or electricity substation) within the development.
Drainage system can contain in the 1 in 100 +CC storm event without flooding	YES	
Any flooding between the 1 in 30 & 1 in 100 plus climate change storm events will be safely contained on site.	-/es	Safety: not causing property flooding or posing a hazard to site users i.e. no deeper than 300mm on roads/footpaths. Flood waters

<p>How are rates being restricted (hydrobrake etc)</p>		<p>must drain away at section 6 rates. Existing rates can be used where runoff volumes are not increased Hydrobrakes to be used where rates are between 2l/s to 5l/s. Orifices not to be used below 5l/s as the pipes may block. Pipes with flows &lt; 2l/s are prone to blockage. If these are multiple owners then a drawing illustrating exactly what features will be within each owner's remit must be submitted with this Proforma. If the features are to be maintained directly by the owners as stated in answer to the above question please answer yes to this question and submit the relevant maintenance schedule for each feature. If it is to be maintained by others than above please give details of each feature and the maintenance schedule. Clear details of the maintenance proposals of all elements of the proposed drainage system must be provided. Details must demonstrate that maintenance and operation requirements are economically proportionate. Poorly maintained drainage can lead to increased flooding problems in the future.</p>
<p>Please confirm the owners/adapters of the entire drainage systems throughout the development. Please list all the owners.</p>	<p>Flow control chamber with hydrobrake PRIVATE RESIDENTIAL DEVELOPMENT</p>	
<p>How is the entire drainage system to be maintained?</p>	<p>PRIVATE OWNER TO BE IN CHARGE OF MAINTENANCE</p>	

9. Evidence Please identify where the details quoted in the sections above were taken from. i.e. Plans, reports etc. Please also provide relevant drawings that need to accompany your proforma, in particular exceedance routes and ownership and location of SUDS (maintenance access strips etc

Pro-forma Section	Document reference where details quoted above are taken from	Page Number
Section 2		
Section 3	REFER TO ATTACHED FLOOD RISK ASSESSMENT + SURFACE WATER MANAGEMENT PLAN	
Section 4		
Section 5		
Section 6		
Section 7		
Section 8		

The above form should be completed using evidence from the Flood Risk Assessment and site plans. It should serve as a summary sheet of the drainage proposals and should clearly show that the proposed rate and volume as a result of development will not be increasing. If there is an

UNCLASSIFIED

Increase in rate or volume, the rate or volume section should be completed to set out how the additional rate/volume is being dealt with.

This form is completed using factual information from the Flood Risk Assessment and Site Plans and can be used as a summary of the surface water drainage strategy on this site.

Form Completed By..... **MARK SYMONDS** .....

Qualification of person responsible for signing off this pro-forma .....

Company..... **MEYNE TILWETT STEEL** .....

On behalf of (Client's details) .....

Date:..... **29/05/2015** .....

UNCLASSIFIED

