



ZIP 4-7 ZIP Retractable Ladder

ZIP 4-7 Overview

The retractable Zip ladder provides the simple solution to ceiling and loft access. Incorporating deep and wide anti-slip treads, a counterbalance spring ensures that the stairway can be operated with a minimum of effort.

Mounted on a headboard for easy installation.

STANDARD FEATURES

- 350mm x 140mm anti-slip treads as standard
- Two heavy duty Counter balanced springs
- 18mm thick block wood backboard
- Manufactured from diecast aluminium

Materials:

Die cast aluminium alloy and Aluminium non-slip treads.

Operation:

Counter balanced springs are incorporated into the pivot bracket for easy opening.

Head Board:

The timber headboard is 18mm thick 'block wood'. This should not be attached to the hatch

Treads:

Standard tread width is 350mm by 140mm depth.
Alternate sizes between 200mm - 380mm (140mm depth) also available.

Loading:

200Kg per tread. 500kg/m² overall structure.

Options:

Telescopic handrail
Additional Grab rail
Additional steps

STANDARD SIZES

Model	Headboard	Min. Aperture	Min. Hatch Length	Dimension 'X'	No. of Treads	WT. (Kg)
ZIP 4	Up to 2500	600 x 700	750	1210 x 1310	9	28
ZIP 5	2501 - 2790	600 x 750	800	1310 x 1410	10	30
ZIP 6	2791 - 3090	600 x 850	900	1410 x 1510	11	32
ZIP 7	3091 - 3390	600 x 900	950	1510 x 1610	12	34

Note: Add 50mm to minimum aperture (length & Width) to allow frame thickness of Jakdor ceiling door.
It is up to the customer to ensure the aperture size is large enough for their requirements.

