

- Toshiba multi-splits are equipped with Toshiba DC hybrid inverter, an enhanced feature that ensures improved performance and reliability
- Wide range of indoor units available
- Environmentally conscious, R410A refrigerant
- Superior reliability due to Toshiba's unique inverter compressor
- Vertical pipe lengths of up to 15 metres



Multi-Split Outdoor

MODEL OUTDOOR UNIT CAPACITY CODE INDOOR UNITS CONNECTED	RAS- MIN.-MAX. MIN.-MAX.	M14GAV-E 20 - 23 2 - 2	M18UAV-E 20 - 29 2 - 2	3M26UAV-E 20 - 50 2 - 3	4M27UAV-E 20 - 47 2 - 4	5M34UAV-E1 20 - 68 2 - 5	
Cooling Capacity (Min. - Max.)	(kW)	4.0 (1.4 - 4.5)	5.2 (1.4 - 6.2)	7.5 (4.1 - 9.0)	8.0 (4.2 - 9.3)	10.0 (3.7 - 11.0)	
Heating Capacity (Min. - Max.)	(kW)	4.4 (0.9 - 5.2)	5.6 (0.9 - 8.3)	9.0 (2.0 - 11.2)	9.0 (3.0 - 11.7)	12.0 (3.4 - 14.0)	
Operating Range Cooling / Heating	(°C)	43 to 5 / 24 to -10					
Cooling	EER / SEER	3.7 / 5.8 - 6.0	3.00 / 6.10 - 6.39	2.56 / 5.66 - 6.32	2.56 / 5.77 - 6.32	2.56 / 5.19 - 6.61	
	Seasonal Energy Consumption	(kWh/a)	229 / 240	256 / 298	303 / 455	303 / 484	324 / 587
	Power Consumption / Energy Efficiency Class		0.70 - 1.30 / A+	0.22 - 2.17 / A++	0.64 - 2.8 / A+ / A++	0.64 - 2.90 / A / A++	0.65 - 2.7 / A / A++
Heating	COP / SCOP	4.36 / 3.84 - 3.86	2.78 / 4.58 - 4.61	2.44 / 4.41 - 4.43	2.44 / 4.10 - 4.43	2.44 / 4.05 - 4.25	
	Seasonal Energy Consumption	(kWh/a)	870 / 875	913 / 916	1445 / 1651	1495 / 1717	2068 / 2342
	Power Consumption / Energy Efficiency Class		0.77 - 6.33 / A	0.17 - 2.53 / A+ / A++	0.30 - 3.25 / A+		0.30 - 4.2 / A+
Standard Air Flow H	(l/s)	506	667	696		989	
Standard Air Flow H	(m3/h)	1820	2400	2507		3562	
Sound Pressure Level H/L	(dBA)	46 / 48	49 / 51	48 / 49		51 / 54	
Sound Power Level H/L	(dBA)	61 / 63	64 / 66	63 / 64		66 / 69	
Refrigerant Base Charge / Chargeless To	(kg / m)	0.9 / 20	1.2 / 20	2.4 / 40		2.99 / 40	
Refrigerant Additional Charge Main Liquid Side	(g/m)	20					
Maximum Piping Length To Indoor	(m)	20		25			
Minimum / Maximum Piping Length	(m)	2 / 30		3 / 70		3 / 80	
Height Difference Outdoor To Indoor	(m)	±10		±15			
Pipe connections Gas side A	(mm / ")	9.5 - 3/8		12.7 - 1/2			
Pipe connections Liquids side A	(mm / ")	6.4 - 1/4		6.4 - 1/4			
Pipe connections Gas side B	(mm / ")	9.5 - 3/8		12.7 - 1/2	9.5 - 3/8	12.7 - 1/2	
Pipe connections Liquid side B	(mm / ")	6.4 - 1/4					
Pipe connections Gas side C	(mm / ")	-		9.5 - 3/8			
Pipe connections Liquid side C	(mm / ")	-		6.4 - 1/4			
Pipe connections Gas side D	(mm / ")	-		9.5 - 3/8			
Pipe connections Liquid side D	(mm / ")	-		6.4 - 1/4			
Pipe connections Gas side E	(mm / ")	-		9.5 - 3/8			
Pipe connections Liquid side E	(mm / ")	-		6.4 - 1/4			
Drain Port Connector Hose Inner Diameter	(mm)	16					
Height / Width / Depth	(mm)	550 / 780 / 290			800 / 900 / 320		
Total Weight	(kg)	36	41	69	75		
Maximum Run Current	(Amps)	6.33	11.22	14.42		19.48	
Power Supply		1 phase 230v 50Hz					
Suggested Fused Supply	(Amps)	16		20		25	