

There is a risk of injury or death in construction if the works are not properly planned and supervised. The contractor must not undertake any element of the work without first having carried out the necessary risk assessments and prepared detailed method statements.

Portland stone parapet.

Portland stone chimney flue cap.

Electrically operated sliding gate. Gate to be black painted metal.

Metal garden gate painted black with suitable metal gloss paint. Yellow London stock brick.

27) Featow London's stock brok.
28) Portland stone chimney breast.
29) Brick voussoirs in yellow london stock.
30) Cantilevered concrete planters with painted render finish.
31) Sliding folding double glazed screens in bronze finished hardwood to achieve 1.2 W/m2K. 32) External wall to achieve 8DB improvment over current Building Regulations;Part E.

 Portland stone steps
 Decorative vermiculation to window surround to detail For details of below ground construction see Structural Engineer's reports

(45) For details of soil and ground water conditions see Structural Engineers reports (46) For details of services see Services Engineers reports

47) Lead lired roof to minimum falls to achieve u value of 0.1 W/nm2k 48 External wall.

dwg. type: PLANNING dwg. status: PLANNING approved by NC drawn by NC checked by NC scale 1:50 at A1 size job number drawing n 14/11/11

P203

**P**\*

2724

Barrett Lloyd Davis Associates Ltd. 535, Kings Road, London, SW10 0SZ

Tel: 020 7838 5555 Fax: 020 7838 5556 e-mail: mail@blda.co.uk www.blda.co.uk