



No. Notes

1 Dimensions to be verified on site. Only figured dimensions to be used and any discrepancies in dimensions are to be reported to the architect. No dimensions are to be scaled from printed drawings. Any areas indicated on this drawing are for guidance only. No responsibility is taken for their accuracy.

2 There is a risk of injury or death in construction if the works are not properly planned and supervised. The contractor must not undertake any element of the work without first having carried out the necessary risk assessments and prepared detailed method statements.

- ① Graduated welsh slate roof with leadflashing to parapet and upstand
- ② Sand cement render walls painted to match existing adjacent and to achieve 0.14 W/m²K
- ③ Lead clad insulated timber roof to achieve 0.10 W/m²K
- ④ Lift overrun
- ⑤ 95 sq m of PV array to achieve 12Kwp
- ⑥ Metal rainwater goods painted black.
- ⑦ Hardwood timber door with glazed side lights to achieve 1.2 W/m²K.
- ⑧ Painted metal acoustic louvers to achieve required acoustic attenuation to plant. See Services report
- ⑨ York stone open jointed pavers of suitable bed to permit free drainage.
- ⑩ For details of planting see Planting Schedule.
- ⑪ Metal framed glazed rooflights to achieve 1.2 W/m²K.
- ⑫ Obscured tilt and turn sidelights with bronze finish to hardwood frame to achieve 1.2 W/m²K
- ⑬ Garden wall repointed, repaired or replaced as necessary to match existing.
- ⑭ Existing tree retained.
- ⑮ Level access to dwelling to Lifetime Homes standards.
- ⑯ Double glazed bronze finished hardwood casement windows to achieve 1.2 W/m²K

- ⑰ Rustication to coirns to detail.
- ⑱ Decorative jointing to stucco to detail.
- ⑲ Metal balustrade painted black with metal based goss paint.
- ⑳ Decorative stucco coricing to detail.
- ㉑ Lead Clad dormer windows.
- ㉒ Portland stone cill.
- ㉓ Portland stone parapet.
- ㉔ Portland stone chimney flue cap.
- ㉕ Electrically operated sliding gate. Gate to be black painted metal.
- ㉖ Metal garden gate painted black with suitable metal gloss paint.
- ㉗ Yellow London stock brick.
- ㉘ Portland stone chimney breast.
- ㉙ Brick voussiors in yellow London stock.
- ㉚ Cantilevered concrete planters with painted render finish.
- ㉛ Sliding folding double glazed screens in bronze finished hardwood to achieve 1.2 W/m²K.
- ㉜ External wall to achieve 8dB improvement over current Building Regulations, Part E.

- ⑳ Hardwood framed glazed door to achieve u-value of 1.2 W/m²K
- ㉑ Biomass boiler flue.
- ㉒ Kitchen extract
- ㉓ Painted hardwood timber gate
- ㉔ SUDS technology to front garden handstanding.
- ㉕ External refuse storage in secure enclosure
- ㉖ Composting bins.
- ㉗ Secure cycle storage.
- ㉘ Portland stone coping
- ㉙ Portland stone steps
- ㉚ Decorative vermiculation to window surround to detail
- ㉛ For details of below ground construction see Structural Engineer's reports
- ㉜ For details of soil and ground water conditions see Structural Engineers reports
- ㉝ For details of services see Services Engineers reports
- ㉞ Lead lined roof to minimums to achieve u value of 0.1 W/m²K.
- ㉟ External wall.

no. revision

job: 1 NORFOLK ROAD
LONDON
proj: LONG SECTION
dwg: PROPOSED
B-B

dwg. type: PLANNING
dwg. status: PROPOSED
drawn by SRH checked by NC approved by NC
scale 1:50at A1 size A1 date 27/09/11
job number drawing number revision
2724 P231 P*

date.

blda
architects

Barrett Lloyd Davis Associates Ltd.
535, Kings Road, London, SW10 0SZ

Tel: 020 7838 5555
Fax: 020 7838 5556

e-mail: mail@blda.co.uk
www.blda.co.uk