

- Dimensions to be verified on site. Only figured dimensions to be used and any discrepandes in dimensions are to be reported to the architlect. No dimensions are to be scaled from printed drawings. Any areas indicated on this drawing are for guidance only. No responsibility is taken for their accuracy.
- There is a risk of injury or death in construction if the works are not properly planned and supervised. The contractor must not undertake any element of the work without first having carried out the necessary risk assessments and prepared detailed method statements.
- Graduated welsh slate roof with lead flashing to parapet and upstand
- Sand cement render walls painted to match existing adjacent and to achieve 014 W/m2K
- 4 Lift overun
- 95 sq m of PV array to achieve 12Kwp
- Metal rainwater goods painted black.
- Hardwood timber door with glazed side lights to achieve 1.2 W/m2K.
- Painted metal acoustic louvers to achieve required acoustic attenuation to plant. See Sevices
- York stone open jointed pavers of suitable bed to permit free drainage.
- For details of planting see Planting Schedule.
- Metal framed glazed rooflights to achieve 1.2 W/m2K.
- Obscured tilt and turn sidelights with bronze finish to hardwood frame to achieve 1.2 W/m2K
- Garden wall repointed, repaired or replaced as necessary to match existing.
- (14) Existing tree retained.
- (5) Level access to dwelling to Lifetime Homes standards.
 (6) Double glazed bronze finished hardwood casement windows to achieve 1.2 W/m2K

- 18 Decorative jointing to stucco to detail. 3. Lead clad insulated timber roof to achieve 0.10 W/m2K (9) Metal balustrade painted black with metal based gloss paint.
 - Decorative stucco cornicing to detail.
 Lead Clad dormer windows.

 - (22) Portland stone cill.
 - 23) Portland stone parapet.
 - 24) Portland stone chimney flue cap.

 - Electrically operated sliding gate. Gate to be black painted metal.
 Metal garden gate painted black with suitable metal gloss paint.
 Yellow London stock brick.

 - (28) Portland stone chimney breast.

 - 30) Cantilevered concrete planters with painted render finish. 31 Sliding folding double glazed screens in bronze finished hardwood to achieve 1.2 W/m2K.
 - 32 External wall to achieve 8DB improvment over current Building Regulations;Part E.

- becorative vermiculation to wincow surround a detail
 For details of below ground construction see Structural Engineer's reports
 For details of soil and ground water conditions see Structural Engineers reports
 For details of services see Services Engineers reports
 Lead lined roof to minimum falls to achieve u value of 0.1 W/m2k.
 External wall.

no. revision.

Job.	T NORT OLK ROAD		
	LONDON		
proj.	LONG SECTION		
dwg:	PROPOSED		
	C-C		

dwg. t	ype: F	PLANNING	3				
dwg. status: PROPOSED							
drawn by	SRH	checked by	NC	approved by	NC		
scale	1:50at A1	size	A1	date	27/09/11		
San Barraman Barrama			dans dans and a second				

P232

date. 2724

blda

Barrett Lloyd Davis Associates Ltd. 535, Kings Road, London, SW10 0SZ

Tel: 020 7838 5555 Fax: 020 7838 5556 e-mail: mail@blda.co.uk www.blda.co.uk