


1 NORTH-WEST PARTIAL ELEVATION Scale: 1:50





- Dimensions to be verified on site. Only figured dimensions to be used and any discrepancies in dimensions are to be reported to the architect. No dimensions are to be scaled from printed drawings. Any areas indicated on this drawing are for guidance only. No responsibility is taken for their accuracy.
- There is a risk of injury or death in construction if the works are not properly planned and supervised. The contractor must not undertake any element of the work without first having carried out the necessary risk assessments and prepared detailed method statements.
- Graduated welsh slate roof with lead flashing to parapet
- Sand cement render walls painted to match existing adjacent and to achieve 014 WV/m2K
 Lead dad insulated timber roof to achieve 0.14 W/m2K
- 4. Lift overun
- 5.) PV array to achieve 35Kwp
- Metal rainwater goods painted black.
- 7.) Hardwood timber door with glazed side lights to achieve: 1.2 W/m2K.
- 8. Painted metal acoustic louvers to achieve
- 10. For planting see Planting Schedule.
- (1) Metal framed glazed rooflights to achieve 1.2 W/m2K.
 (2) Obscured tilt and turn sidelights with bronze finish to hardwood frame to achieve 1.2 W/m2K
- Garden wall repointed, repaired or replaced as necessary to match existing.

 Existing tree retained.

- Existing tree retained.
 Level access to dwelling to Lifetime Homes standards.
 Double glazed bronze finished hardwood casement windows to achieve 1.2 Winn2K
 Rustication to coins to detail.
- Decorative jointing to stucco to detail.
 Metal balustrade painted black with metal based gloss praint.
- becarding the student committee of the state of the

- Electrically operated skiding gale. Gate to be black painted metal.
 Metal garden gate painted black with suitable metal gloss paint.
 Yellow London stock brick.

- Yellow London stock brick
 Portland stone chimney breast.
 Brick voussoirs
 Cantlevered concrete planters with painted render finish.
 Stiding folding double glazed screens in bronze finished hardwood to achieve 12 W/m/2k
 External wall to achieve 8DB improvment over current Building Regulations/Part E.
 Hardwood framed glazed door to achieve u-value of 1.2 W/m/2k

- Biomass boiler flue.
 Richard started gazes don't during a started and started gazes don't during a started gazes don't duri

- Secure cycle storage.
 Portland stone coping
 Portland stone steps
 Decorative vermiculation to window surround to detail
- 44) For details of below ground construction see Structural Engineer's reports

- Engineer's reports

 To ridetalls of soil and ground water conditions see Structural Engineers reports

 46) For details of services see Services Engineers reports

 47) Lead lined roof to minimum fills to achieve u value of 0.1 W/m2k.

 48) External wall.

blda

architects

Barrett Lloyd Davis Associates Ltd.

535, Kings Road, London, SW10 0SZ

Tel: 020 7838 5555 Fax: 020 7838 5556 e-mail: mail@blda.co.uk

www.blda.co.uk

job: 1 NORFOLK ROAD ST JOHNS WOOD, NW8

proj: PRIVATE RESIDENCE

dwg: PARTIAL SECTIONS EXTERNAL VENTILATION SHAFT

dwg. type: PROPOSED dwg. status: PLANNING

drawn by SRH checked by NC approved by Architect scale 1:50 at A1 size A1 date 25/04/12

2724 P240