



neo™

# neo™

neo™, Residential Property in Kent. For the full case study visit:  
[www.therooflightcompany.co.uk/case-studies](http://www.therooflightcompany.co.uk/case-studies)



# Why specify neo™ ?

A roof window range suitable for pitched roofs between 20° and 60°.

## Designed from the architects' point of view

Representing an innovative concept in roof window design, **neo™** results from a collaboration between the Rooflight Company design team and a group of architects. The result is a roof window where form and function are equally balanced.

## Frameless Appearance

Due to its edge-to-edge glazing and ultra-low profile, **neo™** does not dominate the roof; the overall appearance is one of a sheet of glass. These aesthetic advantages are cleverly combined with blinds to suit your interior.

## Clear, uncluttered Views

All models are top hinged and choice of concealed motors, a discreet handle at the cill or a telescopic polewinder is available. Linings have simple, clean lines so that all you can see is natural light.

## Choice

Choose from 15 sizes in Portrait, Landscape or Square format. For a limitless run of rooflights, a linking system is available for **neo™** Steel. See page 22 for details of the linking options available.

## Neat and Easy Installation

The flashing kit ensures neat and easy on-site fitment which blends seamlessly into most roof tile types.

## Performance and Quality

**neo™** is CE Marked to EN 14351-1:2006+A1:2010.

**neo™** Steel achieves a whole window u-value ( $U_w$ ) of  $1.4\text{Wm}^2\text{K}$  in accordance with EN ISO 10077-2:2012. The u-value results are for the window orientated in the vertical plane.

**neo** Fortecom® achieves a whole window u-value ( $U_w$ ) of  $1.3\text{Wm}^2\text{K}$  in accordance with EN ISO 10077-2:2012. The u-value results are for the window orientated in the vertical plane.



Les Bardeaux, BAS MOOARC Architects

"The roof windows are wonderful and in sympathy with the crisp lines of the design." Jamie Falla.



Twelve **neo™** roof windows were specified for this project as they matched the minimalist design of the overall building.

# neo™ Case Studies

## Broadclyst Primary School, Devon

When architects at NPS South West were briefed to design five new classrooms for Broadclyst Primary School in Devon, they knew they were facing a challenge as the original school building is one of the oldest in the country - a Grade II Listed Georgian building co-owned by the National Trust and Devon County Council.

When it came to the specification of the roof windows both clients were most insistent that they be flush fitting. **neo™** roof windows from the Rooflight Company presented an ideal solution - it lies flush with the roof, and also has a contemporary appearance. As Project Architect David Price states: "**The neo™ appealed to me as it is completely flush and frameless.**" Fortunately the National Trust and both sets of planners concurred.



Broadclyst Primary School, Devon by NPS South West. **neo™** 57P.

## Residence, Cambridge

A major component in the success of this attic conversion in a Victorian end-of terrace house in Cambridge was the selection of **neo™**. As well as providing light and ventilation, the top-hung **neo™** windows can be opened to 600mm. Some other roof windows stand out from the roof and have exposed opening mechanisms, whereas **neo™** has a totally frameless appearance both inside and out.

Architectural Designer, Judith Perry says: "I am delighted with the result. The **neo™** roof windows have clean lines and lie completely flush with the slate roof and their oak linings (available on Fortecom®) compliment the specially designed oak doors and windows."



Residence, Cambridge by Sohnius Perry. **neo™** 94P.

## Wheal Friendly Garden, Cornwall

The objective to provide sustainable living accommodation in an idyllic setting has been achieved for six eco-homes in St Agnes, Cornwall. Award-winning architects Simon Conder Associates have designed into the scheme various energy-saving features such as a ground source heat pump, warm and cooling air distributed through an energy-efficient ventilation system and super insulation. The decision to specify the largest square size of **neo** Fortecom® was based on a desire to maintain a contemporary appearance and have a completely flush frameless roof window that would not detract from the timber roof. On the inside it is minimalist in appearance and finished with simple oak linings.



The first of six eco-houses in St Agnes, Cornwall designed by Simon Conder Associates. **neo™** 93S.

## Les Bardeaux, Guernsey

Les Bardeaux is a newly-built open-plan family home set within a wooded enclave in Guernsey. Jamie Falla, the Project Architect, was tasked with creating an elegant, sustainable home for the future - ensuring that environmentally sympathetic materials were used to meet the Level 4 and 5 Code for Sustainable Homes. High performance glazing, together with the latest insulating techniques and a renewable energy-heating source, resulted in a house that far exceeds regulations for thermal performance. The use of existing site conditions was a key element of the brief, and the Architect maximised the level of natural light through the use of **neo** Fortecom®. Featuring a sleek, contemporary design and flush edge-to-edge glazing, the **neo™** specified by Jamie Falla offers a roof window that combines unique properties with a frameless, minimalist appearance to complement modern architecture and interiors perfectly.



Les Bardeaux was shortlisted for the RIBA South East Downland Prize 2010.

# Specification Details for neo™

## Frame Construction

neo™ is available in a choice of two materials; Fortecom® and Steel:

### Fortecom®

Fortecom® is a pultruded fibre-reinforced composite which is slim, strong and designed to withstand the most hostile environments. Considered to be in the 'high-tech' league of modern materials, it has a proven track record in demanding environments such as those found in the oil exploration and aerospace industries. With its inherent high mechanical strength and anti-corrosive properties it offers many benefits over traditional materials and the frame comes with a 12 year guarantee.\*

neo Fortecom® meets the requirements of BS 6375-1:2009 exposures category 2000 and the pultrusion process receives and 'A' rating in the BRE "Green Guide to Composites".

### Steel

The neo™ Steel frame consists of 3mm steel with a protective coating plus polyester powder coating and the frame has a guarantee of 12 years.

## Glazing

A typical glazing specification produces a glass centre pane u-value of 1.0Wm²K for neo™ Steel and 1.1Wm²K for neo Fortecom®. Within our standard range we offer 8 different glazing specifications covering the most popular options and purposes. Please ask for details of our standard options or to enquire about any other to suit your particular needs

## Rooflights to match any roof covering

The standard colour for the Fortecom® and the Steel version is Umber Grey (RAL 7022). Black (RAL 9005) is readily available as an option. Any RAL colour can be specified to match the roof covering.



\*Dependent on location and maintenance regime undertaken.  
See [www.therooflightcompany.co.uk](http://www.therooflightcompany.co.uk) for details  
Any RAL colour can be specified to match the roof covering.

## Linings

Both neo Fortecom® and neo™ Steel roof windows are provided with moisture resistant linings which can be painted on-site to suit the room interior.



An oak lining is available with neo™ Fortecom®.

## Openings

neo™ is operable via use of a sleek manual handle for within hand reach, a telescopic polewinder for out of hand reach (please check where access and height restrictions apply), or with concealed motors for electric actuation. For more information on motors see page 38. neo™ is also available fixed shut.



Sleek handle for manual opening.




Polewinder for out of hand reach.



Fixed shut option for neo™



# Cross Section of the neo™ Fortecom®



jamba only until the Flashing Kit is installed and the jamb aprons are slid under them. Then they are fixed home.

11. Rooflight cill flashing piece. This is part of the rooflight assy.

12. Clay roof tiles. The jamb tiles are dry-bedded on the jamb weathering foam (12a) which is bent over and compressed under them as they are fixed down. Additional fixing holes or a mortar bed may be required under some tiles where only one batten fixing is possible.

13. Rooflight baseplate. Rooflight casement (13a).

14. Head flashing (supplied as part of the Flashing Kit). In severe exposures consider clipping down roof tiles. Jamb flashing assembly (14a) - UPVC soaker upstand.

15. General roofing membrane.


16. Rooflight linings. These are part of the rooflight assembly. The linings (16a & 16b) are preinstalled. The baseplate linings (16b) must be removed during installation to allow the fixing (17) of the Rooflight. Ensure the linings are refitted afterwards.

17. Fixing coachbolts (supplied with rooflight). These are screwed to the structural bearers through yellow-marked holes in the baseplate.

18. General roof insulation. Roof insulation between jack bearers (18a).

19. Internal finishes abutment to rooflight lining. To be specified by project designer. Here shown as a timber architrave to match the rooflight lining.

## Cross Section of the neo™ Steel





**Please Note:** These sectional details are provided as an installation suggestion. Due to the differing nature of installations we strongly advise you to consult your rooftop installer to verify fitness for purpose. This drawing does not constitute a structural proposal. Sufficiency of structural supports to be checked by rooftop purchaser's structural consultant.

**17.** Jamb weathering foam which is bent over and compressed under tiles as they are fixed down. Additional fixing holes or a mortar bed may be required under some tiles where only one batten fixing is possible.

Carry flashing up the roof and lap **UNDER** general roofing membrane **10**

# neo™ Steel Sizes

|                            |                              |                                                  | Clear Viewable Width (mm)                       |                 |                 |                 |                  |                 |                    |                  |                    |      |
|----------------------------|------------------------------|--------------------------------------------------|-------------------------------------------------|-----------------|-----------------|-----------------|------------------|-----------------|--------------------|------------------|--------------------|------|
|                            |                              |                                                  | 277                                             | 379             | 461             | 531             | 616              | 835             | 941                | 956              | 1451               | 1536 |
|                            |                              |                                                  | Clear Structural Width (mm)                     |                 |                 |                 |                  |                 |                    |                  |                    |      |
|                            |                              |                                                  | 543                                             | 645             | 727             | 797             | 882              | 1101            | 1207               | 1222             | 1717               | 1802 |
|                            |                              |                                                  | Between the Rafter Clear Structural Width* (mm) |                 |                 |                 |                  |                 |                    |                  |                    |      |
|                            |                              |                                                  | 663                                             | 765             | 847             | 917             | 1002             | 1221            | 1327               | 1342             | 1837               | 1922 |
| Clear Viewable Length (mm) |                              |                                                  |                                                 |                 |                 |                 |                  |                 |                    |                  |                    |      |
|                            | 436                          | 702                                              | 962                                             | neo-S1<br>35kgs |                 |                 |                  |                 |                    |                  |                    |      |
|                            | 539                          | 805                                              | 1065                                            |                 | neo-S2<br>43kgs |                 |                  |                 |                    |                  |                    |      |
|                            | 616                          | 882                                              | 1142                                            |                 |                 |                 | neo-S14<br>56kgs |                 | neo-S11<br>76kgs   | neo-S12<br>99kgs |                    |      |
|                            | 761                          | 1027                                             | 1287                                            |                 |                 | neo-S4<br>56kgs |                  |                 |                    |                  |                    |      |
|                            | 842                          | 1108                                             | 1368                                            |                 | neo-S3<br>55kgs |                 | neo-S6<br>62kgs  |                 |                    |                  |                    |      |
|                            | 941                          | 1207                                             | 1467                                            |                 |                 |                 |                  |                 | neo-S15<br>87kgs   |                  | neo-S13*<br>124kgs |      |
|                            | 956                          | 1222                                             | 1482                                            |                 |                 |                 | neo-S7<br>71kgs  |                 |                    |                  |                    |      |
|                            | 1147                         | 1413                                             | 1673                                            |                 |                 |                 |                  | neo-S9<br>92kgs |                    |                  |                    |      |
|                            | 1156                         | 1422                                             | 1682                                            |                 |                 | neo-S5<br>72kgs |                  |                 |                    |                  |                    |      |
|                            | 1451                         | 1717                                             | 1977                                            |                 |                 |                 | neo-S8<br>94kgs  |                 |                    |                  |                    |      |
|                            | 1536                         | 1802                                             | 2062                                            |                 |                 |                 |                  |                 | neo-S10*<br>118kgs |                  |                    |      |
| Clear Viewable Length (mm) | Clear Structural Length (mm) | Between the Rafter Clear Structural Length* (mm) |                                                 |                 |                 |                 |                  |                 |                    |                  |                    |      |



\*Where **neo™** is required to sit flush to the roofline within narrow roof build-ups below 103mm (from the top of the structural rafter to the outer face of the roof tile) we recommend a between-the-rafter installation.