



STRICTLY PRIVATE & CONFIDENTIAL

PROTECTED PREMISES

Bank Machine sample site

PREPARED BY: -Chris Nunn

DISCIPLINE: -
(CCTV): BS EN 50132-7 New Installation



NAC/G/1448

FIR/G/1448

Head Office AIS Total Security Limited, Cowlairst, Southglade Business Park, Nottingham, NG5 9RA

Tel: 0115 913 8981 - Fax: 0115 913 8982

Email: sales@ais-totalsecurity.com - Web: www.ais-totalsecurity.com

Registered in England 2369621 VAT 567838483

INTRUDER - CCTV - ACCESS CONTROL - FIRE - GATES & BARRIERS

Customer

New Wave Installations Ltd
Hope Street
Rotherham
S Yorks

S60 1LH

Installation Address

Costcutter
100 Charlton Street
London
NW1 1ES

System Description

TO PROVIDE A STANDALONE CCTV SYSTEM FOR SURVEILLANCE OF ATM FROM OUTSIDE THE PREMISES FEEDING INTO A DEDICATED DIGITAL RECORDER WITH MONITOR IN A SECURE LOCATION WITHIN THE PREMISES.

Equipment Schedule

External Static Camera

One external static vandal resistant mini dome camera located building mounted outside the premises above the ATM to view the general area.

Key Features

High Quality Imaging

Class leading 700TVL resolution colour and monochrome images deliver maximum scene detail

23 x 850nm internal LEDS with true day/night operation

The switching IR cut filter allows the camera to be used with the integral IR LED's, providing discrete illumination (0 lux) up to a distance of 25m (dependent on reflective scene content)

Advanced processing

With 2D-DNR, ATR (Adaptive Tone Reproduction - which helps to balance the image in widely contrasting scenes of view), BLC and HLC (Peak White Inversion) it ensures that a majority of lighting conditions can be resolved

Protecting sensitive and personal information

4 user-selectable privacy zones ensure that personal and sensitive information remains protected

Vandal Resistant

The rugged aluminium casing (built to IK10) and IP66 rating make this camera suitable for external, internal and hostile applications

External Dimensions

170(W) x 170(H) x 170(D) mm



Digital Recorder

One four channel 500gb digital recorder fitted located on customers furniture in the office.

Key Features

- H.264 technology: Extremely efficient H.264 compression provides economical storage of high quality images, with the option of recording speeds in 400ips @ CiF,200ips @2CiF and 100ips @ D1
- I-Phone and Android APPs: These free of charge applications allow remote monitoring of the DVR from mobile handsets
- 4CIF (D1) resolution recording: Allows for high quality recorded evidence
- Real time recording: Records 25ips per camera, up to 400ips global recording
- Scalable: Any camera can be set to record at any quality & resolution and at different image rates per second Intuitive set-up menus: Driven from the front panel, mouse or remote control making it easy for the installer to set-up and the end user to operate
- Multiprotocol RS485 & Coaxial telemetry: Allowing to integrate to the majority of popular camera control systems, Vista coax telemetry, Vista, Pelco P and Pelco D Rs485 protocols are supplied as standard. Whilst the inclusion of Fsk coaxial telemetry control allows the control of remote devices via single coax cable
- Audio input per video input: Allows for audio tracks to be recorded for each camera also used to initiate different recording modes



Monitor

One 17" CCTV monitor located with the recorder

