

DER WorkSheet: New dwelling design stage

Type 1: After Renewable Energy

User Details:

Assessor Name:

Stroma Number:

Software Name: Stroma FSAP 2012

Software Version:

Version: 1.0.1.25

Property Address: L2 2BF West

Address : , NW1 1JD

1. Overall dwelling dimensions:

	Area(m ²)		Av. Height(m)		Volume(m ³)
Ground floor	80	(1a) x	3.15	(2a) =	252
Total floor area TFA = (1a)+(1b)+(1c)+(1d)+(1e)+.....(1n)	80	(4)			
Dwelling volume				(3a)+(3b)+(3c)+(3d)+(3e)+.....(3n) =	252

2. Ventilation rate:

	main heating		secondary heating		other		total		m ³ per hour
Number of chimneys	0	+	0	+	0	=	0	x 40 =	0
Number of open flues	0	+	0	+	0	=	0	x 20 =	0
Number of intermittent fans							0	x 10 =	0
Number of passive vents							0	x 10 =	0
Number of flueless gas fires							0	x 40 =	0

Infiltration due to chimneys, flues and fans = (6a)+(6b)+(7a)+(7b)+(7c) = 0 ÷ (5) = 0 (8)

If a pressurisation test has been carried out or is intended, proceed to (17), otherwise continue from (9) to (16)

Number of storeys in the dwelling (ns) 0 (9)

Additional infiltration [(9)-1]x0.1 = 0 (10)

Structural infiltration: 0.25 for steel or timber frame or 0.35 for masonry construction 0 (11)

if both types of wall are present, use the value corresponding to the greater wall area (after deducting areas of openings); if equal user 0.35

If suspended wooden floor, enter 0.2 (unsealed) or 0.1 (sealed), else enter 0 0 (12)

If no draught lobby, enter 0.05, else enter 0 0 (13)

Percentage of windows and doors draught stripped 0 (14)

Window infiltration 0.25 - [0.2 x (14) ÷ 100] = 0 (15)

Infiltration rate (8) + (10) + (11) + (12) + (13) + (15) = 0 (16)

Air permeability value, q50, expressed in cubic metres per hour per square metre of envelope area 3 (17)

If based on air permeability value, then (18) = [(17) ÷ 20]+(8), otherwise (18) = (16) 0.15 (18)

Air permeability value applies if a pressurisation test has been done or a degree air permeability is being used

Number of sides sheltered 0 (19)

Shelter factor (20) = 1 - [0.075 x (19)] = 1 (20)

Infiltration rate incorporating shelter factor (21) = (18) x (20) = 0.15 (21)

Infiltration rate modified for monthly wind speed

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Monthly average wind speed from Table 7

(22)m=

5.1	5	4.9	4.4	4.3	3.8	3.8	3.7	4	4.3	4.5	4.7
-----	---	-----	-----	-----	-----	-----	-----	---	-----	-----	-----

Wind Factor (22a)m = (22)m ÷ 4

(22a)m=

1.27	1.25	1.23	1.1	1.08	0.95	0.95	0.92	1	1.08	1.12	1.18
------	------	------	-----	------	------	------	------	---	------	------	------

DER WorkSheet: New dwelling design stage

Adjusted infiltration rate (allowing for shelter and wind speed) = (21a) x (22a)m

0.19	0.19	0.18	0.16	0.16	0.14	0.14	0.14	0.15	0.16	0.17	0.18
------	------	------	------	------	------	------	------	------	------	------	------

Calculate effective air change rate for the applicable case

If mechanical ventilation:

0.5 (23a)

If exhaust air heat pump using Appendix N, (23b) = (23a) x Fmv (equation (N5)) , otherwise (23b) = (23a)

0.5 (23b)

If balanced with heat recovery: efficiency in % allowing for in-use factor (from Table 4h) =

64.6 (23c)

a) If balanced mechanical ventilation with heat recovery (MVHR) (24a)m = (22b)m + (23b) x [1 - (23c) ÷ 100]

(24a)m=

0.37	0.36	0.36	0.34	0.34	0.32	0.32	0.32	0.33	0.34	0.35	0.35
------	------	------	------	------	------	------	------	------	------	------	------

 (24a)

b) If balanced mechanical ventilation without heat recovery (MV) (24b)m = (22b)m + (23b)

(24b)m=

0	0	0	0	0	0	0	0	0	0	0	0
---	---	---	---	---	---	---	---	---	---	---	---

 (24b)

c) If whole house extract ventilation or positive input ventilation from outside

if (22b)m < 0.5 x (23b), then (24c) = (23b); otherwise (24c) = (22b) m + 0.5 x (23b)

(24c)m=

0	0	0	0	0	0	0	0	0	0	0	0
---	---	---	---	---	---	---	---	---	---	---	---

 (24c)

d) If natural ventilation or whole house positive input ventilation from loft

if (22b)m = 1, then (24d)m = (22b)m otherwise (24d)m = 0.5 + [(22b)m² x 0.5]

(24d)m=

0	0	0	0	0	0	0	0	0	0	0	0
---	---	---	---	---	---	---	---	---	---	---	---

 (24d)

Effective air change rate - enter (24a) or (24b) or (24c) or (24d) in box (25)

(25)m=

0.37	0.36	0.36	0.34	0.34	0.32	0.32	0.32	0.33	0.34	0.35	0.35
------	------	------	------	------	------	------	------	------	------	------	------

 (25)

3. Heat losses and heat loss parameter:

ELEMENT	Gross area (m ²)	Openings m ²	Net Area A ,m ²	U-value W/m ² K	A X U (W/K)	k-value kJ/m ² -K	A X k kJ/K
Windows Type 1			2.85	x1/[1/(1.3)+0.04] =	3.52		(27)
Windows Type 2			12.65	x1/[1/(1.3)+0.04] =	15.63		(27)
Windows Type 3			2.85	x1/[1/(1.3)+0.04] =	3.52		(27)
Walls	64	29.75	34.25	x 0.11 =	3.77		(29)
Total area of elements, m ²			64				(31)
Party wall			19	x 0 =	0		(32)
Party wall			32	x 0 =	0		(32)
Party floor			80				(32a)
Party ceiling			80				(32b)
Internal wall **			74				(32c)

* for windows and roof windows, use effective window U-value calculated using formula 1/[1/U-value+0.04] as given in paragraph 3.2

** include the areas on both sides of internal walls and partitions

Fabric heat loss, W/K = S (A x U) (26)...(30) + (32) =

40.53

 (33)

Heat capacity Cm = S(A x k) ((28)...(30) + (32) + (32a)...(32e) =

29383.5

 (34)

Thermal mass parameter (TMP = Cm ÷ TFA) in kJ/m²K Indicative Value: Medium

250

 (35)

For design assessments where the details of the construction are not known precisely the indicative values of TMP in Table 1f can be used instead of a detailed calculation.

Thermal bridges : S (L x Y) calculated using Appendix K

7

 (36)

if details of thermal bridging are not known (36) = 0.15 x (31)

Total fabric heat loss (33) + (36) =

47.53

 (37)

Ventilation heat loss calculated monthly (38)m = 0.33 x (25)m x (5)

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

DER WorkSheet: New dwelling design stage

(38)m=	30.62	30.31	30	28.44	28.13	26.57	26.57	26.26	27.19	28.13	28.75	29.38	(38)
--------	-------	-------	----	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

Heat transfer coefficient, W/K

$$(39)m = (37) + (38)m$$

(39)m=	78.15	77.84	77.53	75.97	75.66	74.1	74.1	73.79	74.72	75.66	76.28	76.91	
Average = Sum(39) _{1...12} / 12 =												75.89	(39)

Heat loss parameter (HLP), W/m²K

$$(40)m = (39)m \div (4)$$

(40)m=	0.98	0.97	0.97	0.95	0.95	0.93	0.93	0.92	0.93	0.95	0.95	0.96	
Average = Sum(40) _{1...12} / 12 =												0.95	(40)

Number of days in month (Table 1a)

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
(41)m=	31	28	31	30	31	30	31	31	30	31	30	31	(41)

4. Water heating energy requirement:

kWh/year:

Assumed occupancy, N	2.46	(42)
if TFA > 13.9, N = 1 + 1.76 x [1 - exp(-0.000349 x (TFA - 13.9)²)] + 0.0013 x (TFA - 13.9)		
if TFA ≤ 13.9, N = 1		

Annual average hot water usage in litres per day Vd,average = (25 x N) + 36	92.69	(43)
<i>Reduce the annual average hot water usage by 5% if the dwelling is designed to achieve a water use target of not more than 125 litres per person per day (all water use, hot and cold)</i>		

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
<i>Hot water usage in litres per day for each month Vd,m = factor from Table 1c x (43)</i>													
(44)m=	101.96	98.25	94.55	90.84	87.13	83.42	83.42	87.13	90.84	94.55	98.25	101.96	
Total = Sum(44) _{1...12} =												1112.32	(44)

Energy content of hot water used - calculated monthly = 4.190 x Vd,m x nm x DTm / 3600 kWh/month (see Tables 1b, 1c, 1d)

(45)m=	151.21	132.25	136.47	118.97	114.16	98.51	91.28	104.75	106	123.53	134.85	146.44	
Total = Sum(45) _{1...12} =												1458.42	(45)

If instantaneous water heating at point of use (no hot water storage), enter 0 in boxes (46) to (61)

(46)m=	22.68	19.84	20.47	17.85	17.12	14.78	13.69	15.71	15.9	18.53	20.23	21.97	(46)
--------	-------	-------	-------	-------	-------	-------	-------	-------	------	-------	-------	-------	------

Water storage loss:

Storage volume (litres) including any solar or WWHRS storage within same vessel	0	(47)
---	---	------

If community heating and no tank in dwelling, enter 110 litres in (47)

Otherwise if no stored hot water (this includes instantaneous combi boilers) enter '0' in (47)

Water storage loss:

a) If manufacturer's declared loss factor is known (kWh/day):	0	(48)
---	---	------

Temperature factor from Table 2b	0	(49)
----------------------------------	---	------

Energy lost from water storage, kWh/year	(48) x (49) =	110	(50)
--	---------------	-----	------

b) If manufacturer's declared cylinder loss factor is not known:

Hot water storage loss factor from Table 2 (kWh/litre/day)	0.02	(51)
--	------	------

If community heating see section 4.3

Volume factor from Table 2a	1.03	(52)
-----------------------------	------	------

Temperature factor from Table 2b	0.6	(53)
----------------------------------	-----	------

Energy lost from water storage, kWh/year	(47) x (51) x (52) x (53) =	1.03	(54)
--	-----------------------------	------	------

Enter (50) or (54) in (55)	1.03	(55)
----------------------------	------	------

Water storage loss calculated for each month $(56)m = (55) \times (41)m$

(56)m=	32.01	28.92	32.01	30.98	32.01	30.98	32.01	32.01	30.98	32.01	30.98	32.01	(56)
--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

If cylinder contains dedicated solar storage, $(57)m = (56)m \times [(50) - (H11)] \div (50)$, else $(57)m = (56)m$ where (H11) is from Appendix H

(57)m=	32.01	28.92	32.01	30.98	32.01	30.98	32.01	32.01	30.98	32.01	30.98	32.01	(57)
--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

DER WorkSheet: New dwelling design stage

Primary circuit loss (annual) from Table 3 0 (58)

Primary circuit loss calculated for each month (59)m = (58) ÷ 365 × (41)m

(modified by factor from Table H5 if there is solar water heating and a cylinder thermostat)

(59)m=

23.26	21.01	23.26	22.51	23.26	22.51	23.26	23.26	22.51	23.26	22.51	23.26
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

 (59)

Combi loss calculated for each month (61)m = (60) ÷ 365 × (41)m

(61)m=

0	0	0	0	0	0	0	0	0	0	0	0
---	---	---	---	---	---	---	---	---	---	---	---

 (61)

Total heat required for water heating calculated for each month (62)m = 0.85 × (45)m + (46)m + (57)m + (59)m + (61)m

(62)m=

206.48	182.17	191.74	172.47	169.44	152	146.56	160.03	159.5	178.81	188.34	201.71
--------	--------	--------	--------	--------	-----	--------	--------	-------	--------	--------	--------

 (62)

Solar DHW input calculated using Appendix G or Appendix H (negative quantity) (enter '0' if no solar contribution to water heating)

(add additional lines if FGHRs and/or WWHRs applies, see Appendix G)

(63)m=

0	0	0	0	0	0	0	0	0	0	0	0
---	---	---	---	---	---	---	---	---	---	---	---

 (63)

Output from water heater

(64)m=

206.48	182.17	191.74	172.47	169.44	152	146.56	160.03	159.5	178.81	188.34	201.71
--------	--------	--------	--------	--------	-----	--------	--------	-------	--------	--------	--------

Output from water heater (annual)_{1...12} 2109.26 (64)

Heat gains from water heating, kWh/month $0.25 \times [0.85 \times (45)m + (61)m] + 0.8 \times [(46)m + (57)m + (59)m]$

(65)m=

94.5	83.91	89.6	82.35	82.18	75.55	74.57	79.05	78.04	85.3	87.63	92.91
------	-------	------	-------	-------	-------	-------	-------	-------	------	-------	-------

 (65)

include (57)m in calculation of (65)m only if cylinder is in the dwelling or hot water is from community heating

5. Internal gains (see Table 5 and 5a):

Metabolic gains (Table 5), Watts

(66)m=

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
(66)m=	123.14	123.14	123.14	123.14	123.14	123.14	123.14	123.14	123.14	123.14	123.14	123.14

 (66)

Lighting gains (calculated in Appendix L, equation L9 or L9a), also see Table 5

(67)m=

19.56	17.38	14.13	10.7	8	6.75	7.3	9.48	12.73	16.16	18.86	20.11
-------	-------	-------	------	---	------	-----	------	-------	-------	-------	-------

 (67)

Appliances gains (calculated in Appendix L, equation L13 or L13a), also see Table 5

(68)m=

219.44	221.72	215.98	203.76	188.34	173.85	164.17	161.89	167.63	179.84	195.27	209.76
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

 (68)

Cooking gains (calculated in Appendix L, equation L15 or L15a), also see Table 5

(69)m=

35.31	35.31	35.31	35.31	35.31	35.31	35.31	35.31	35.31	35.31	35.31	35.31
-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

 (69)

Pumps and fans gains (Table 5a)

(70)m=

0	0	0	0	0	0	0	0	0	0	0	0
---	---	---	---	---	---	---	---	---	---	---	---

 (70)

Losses e.g. evaporation (negative values) (Table 5)

(71)m=

-98.51	-98.51	-98.51	-98.51	-98.51	-98.51	-98.51	-98.51	-98.51	-98.51	-98.51	-98.51
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

 (71)

Water heating gains (Table 5)

(72)m=

127.01	124.87	120.43	114.38	110.46	104.93	100.23	106.25	108.39	114.65	121.71	124.88
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

 (72)

Total internal gains = (66)m + (67)m + (68)m + (69)m + (70)m + (71)m + (72)m

(73)m=

425.96	423.91	410.48	388.79	366.74	345.47	331.64	337.57	348.69	370.59	395.78	414.69
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

 (73)

6. Solar gains:

Solar gains are calculated using solar flux from Table 6a and associated equations to convert to the applicable orientation.

Orientation:	Access Factor Table 6d	Area m ²	Flux Table 6a	g_ Table 6b	FF Table 6c	Gains (W)
Southeast 0.9x	0.54	12.65	36.79	0.7	1.11	175.94 (77)
Southeast 0.9x	0.77	2.85	36.79	0.7	1.11	169.56 (77)

DER WorkSheet: New dwelling design stage

Southeast 0.9x	0.54	x	12.65	x	62.67	x	0.7	x	1.11	=	299.69	(77)
Southeast 0.9x	0.77	x	2.85	x	62.67	x	0.7	x	1.11	=	288.83	(77)
Southeast 0.9x	0.54	x	12.65	x	85.75	x	0.7	x	1.11	=	410.04	(77)
Southeast 0.9x	0.77	x	2.85	x	85.75	x	0.7	x	1.11	=	395.19	(77)
Southeast 0.9x	0.54	x	12.65	x	106.25	x	0.7	x	1.11	=	508.06	(77)
Southeast 0.9x	0.77	x	2.85	x	106.25	x	0.7	x	1.11	=	489.66	(77)
Southeast 0.9x	0.54	x	12.65	x	119.01	x	0.7	x	1.11	=	569.07	(77)
Southeast 0.9x	0.77	x	2.85	x	119.01	x	0.7	x	1.11	=	548.45	(77)
Southeast 0.9x	0.54	x	12.65	x	118.15	x	0.7	x	1.11	=	564.96	(77)
Southeast 0.9x	0.77	x	2.85	x	118.15	x	0.7	x	1.11	=	544.49	(77)
Southeast 0.9x	0.54	x	12.65	x	113.91	x	0.7	x	1.11	=	544.68	(77)
Southeast 0.9x	0.77	x	2.85	x	113.91	x	0.7	x	1.11	=	524.95	(77)
Southeast 0.9x	0.54	x	12.65	x	104.39	x	0.7	x	1.11	=	499.16	(77)
Southeast 0.9x	0.77	x	2.85	x	104.39	x	0.7	x	1.11	=	481.08	(77)
Southeast 0.9x	0.54	x	12.65	x	92.85	x	0.7	x	1.11	=	443.99	(77)
Southeast 0.9x	0.77	x	2.85	x	92.85	x	0.7	x	1.11	=	427.9	(77)
Southeast 0.9x	0.54	x	12.65	x	69.27	x	0.7	x	1.11	=	331.22	(77)
Southeast 0.9x	0.77	x	2.85	x	69.27	x	0.7	x	1.11	=	319.22	(77)
Southeast 0.9x	0.54	x	12.65	x	44.07	x	0.7	x	1.11	=	210.73	(77)
Southeast 0.9x	0.77	x	2.85	x	44.07	x	0.7	x	1.11	=	203.1	(77)
Southeast 0.9x	0.54	x	12.65	x	31.49	x	0.7	x	1.11	=	150.57	(77)
Southeast 0.9x	0.77	x	2.85	x	31.49	x	0.7	x	1.11	=	145.11	(77)
Southwest 0.9x	0.77	x	2.85	x	36.79	x	0.7	x	1.11	=	169.56	(79)
Southwest 0.9x	0.77	x	2.85	x	62.67	x	0.7	x	1.11	=	288.83	(79)
Southwest 0.9x	0.77	x	2.85	x	85.75	x	0.7	x	1.11	=	395.19	(79)
Southwest 0.9x	0.77	x	2.85	x	106.25	x	0.7	x	1.11	=	489.66	(79)
Southwest 0.9x	0.77	x	2.85	x	119.01	x	0.7	x	1.11	=	548.45	(79)
Southwest 0.9x	0.77	x	2.85	x	118.15	x	0.7	x	1.11	=	544.49	(79)
Southwest 0.9x	0.77	x	2.85	x	113.91	x	0.7	x	1.11	=	524.95	(79)
Southwest 0.9x	0.77	x	2.85	x	104.39	x	0.7	x	1.11	=	481.08	(79)
Southwest 0.9x	0.77	x	2.85	x	92.85	x	0.7	x	1.11	=	427.9	(79)
Southwest 0.9x	0.77	x	2.85	x	69.27	x	0.7	x	1.11	=	319.22	(79)
Southwest 0.9x	0.77	x	2.85	x	44.07	x	0.7	x	1.11	=	203.1	(79)
Southwest 0.9x	0.77	x	2.85	x	31.49	x	0.7	x	1.11	=	145.11	(79)

Solar gains in watts, calculated for each month

(83)m = Sum(74)m ... (82)m

(83)m=	515.06	877.34	1200.42	1487.37	1665.98	1653.94	1594.57	1461.32	1299.8	969.65	616.93	440.79	(83)
--------	--------	--------	---------	---------	---------	---------	---------	---------	--------	--------	--------	--------	------

Total gains – internal and solar (84)m = (73)m + (83)m , watts

(84)m=	941.02	1301.25	1610.9	1876.16	2032.72	1999.41	1926.21	1798.89	1648.49	1340.24	1012.71	855.47	(84)
--------	--------	---------	--------	---------	---------	---------	---------	---------	---------	---------	---------	--------	------

7. Mean internal temperature (heating season)

Temperature during heating periods in the living area from Table 9, Th1 (°C)

21 (85)

Utilisation factor for gains for living area, h1,m (see Table 9a)

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

DER WorkSheet: New dwelling design stage

(86)m=	0.95	0.84	0.67	0.49	0.35	0.24	0.17	0.19	0.31	0.58	0.87	0.97	(86)
--------	------	------	------	------	------	------	------	------	------	------	------	------	------

Mean internal temperature in living area T1 (follow steps 3 to 7 in Table 9c)

(87)m=	20.5	20.8	20.94	20.99	21	21	21	21	21	20.98	20.79	20.44	(87)
--------	------	------	-------	-------	----	----	----	----	----	-------	-------	-------	------

Temperature during heating periods in rest of dwelling from Table 9, Th2 (°C)

(88)m=	20.1	20.11	20.11	20.13	20.13	20.15	20.15	20.15	20.14	20.13	20.12	20.12	(88)
--------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

Utilisation factor for gains for rest of dwelling, h2,m (see Table 9a)

(89)m=	0.94	0.81	0.63	0.45	0.31	0.21	0.14	0.15	0.27	0.53	0.85	0.96	(89)
--------	------	------	------	------	------	------	------	------	------	------	------	------	------

Mean internal temperature in the rest of dwelling T2 (follow steps 3 to 7 in Table 9c)

(90)m=	19.48	19.87	20.05	20.12	20.13	20.15	20.15	20.15	20.14	20.11	19.88	19.4	(90)
--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------	------

$fLA = \text{Living area} \div (4) =$	0.4	(91)
---------------------------------------	-----	------

Mean internal temperature (for the whole dwelling) = $fLA \times T1 + (1 - fLA) \times T2$

(92)m=	19.89	20.24	20.41	20.47	20.48	20.49	20.49	20.49	20.48	20.46	20.24	19.81	(92)
--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

Apply adjustment to the mean internal temperature from Table 4e, where appropriate

(93)m=	19.89	20.24	20.41	20.47	20.48	20.49	20.49	20.49	20.48	20.46	20.24	19.81	(93)
--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

8. Space heating requirement

Set Ti to the mean internal temperature obtained at step 11 of Table 9b, so that $Ti,m=(76)m$ and re-calculate the utilisation factor for gains using Table 9a

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
(94)m=	0.94	0.81	0.65	0.47	0.33	0.22	0.15	0.17	0.29	0.55	0.85	0.96	(94)

Useful gains, hmGm, W = $(94)m \times (84)m$

(95)m=	882.04	1058.14	1040.7	873.31	663.4	436.2	288.04	301.72	476.74	735.42	860.54	817.45	(95)
--------	--------	---------	--------	--------	-------	-------	--------	--------	--------	--------	--------	--------	------

Monthly average external temperature from Table 8

(96)m=	4.3	4.9	6.5	8.9	11.7	14.6	16.6	16.4	14.1	10.6	7.1	4.2	(96)
--------	-----	-----	-----	-----	------	------	------	------	------	------	-----	-----	------

Heat loss rate for mean internal temperature, Lm, W = $[(39)m \times ((93)m - (96)m)]$

(97)m=	1218.45	1194.35	1078.23	878.76	664.01	436.24	288.04	301.73	476.95	746.07	1002.45	1200.69	(97)
--------	---------	---------	---------	--------	--------	--------	--------	--------	--------	--------	---------	---------	------

Space heating requirement for each month, kWh/month = $0.024 \times [(97)m - (95)m] \times (41)m$

(98)m=	250.28	91.53	27.92	3.93	0.45	0	0	0	0	7.93	102.17	285.13	
--------	--------	-------	-------	------	------	---	---	---	---	------	--------	--------	--

$\text{Total per year (kWh/year)} = \text{Sum}(98)_{1...5,9...12} =$	769.35	(98)
--	--------	------

Space heating requirement in kWh/m²/year

	9.62	(99)
--	------	------

9b. Energy requirements – Community heating scheme

This part is used for space heating, space cooling or water heating provided by a community scheme.

Fraction of space heat from secondary/supplementary heating (Table 11) '0' if none (301)

Fraction of space heat from community system 1 – (301) = (302)

The community scheme may obtain heat from several sources. The procedure allows for CHP and up to four other heat sources; the latter includes boilers, heat pumps, geothermal and waste heat from power stations. See Appendix C.

Fraction of heat from Community CHP (303a)

Fraction of community heat from heat source 2 (303b)

Fraction of total space heat from Community CHP (302) x (303a) = (304a)

Fraction of total space heat from community heat source 2 (302) x (303b) = (304b)

Factor for control and charging method (Table 4c(3)) for community heating system (305)

DER WorkSheet: New dwelling design stage

Distribution loss factor (Table 12c) for community heating system		1.4	(306)
Space heating		kWh/year	
Annual space heating requirement		769.35	
Space heat from Community CHP	(98) x (304a) x (305) x (306) =	646.26	(307a)
Space heat from heat source 2	(98) x (304b) x (305) x (306) =	430.84	(307b)
Efficiency of secondary/supplementary heating system in % (from Table 4a or Appendix E)		0	(308)
Space heating requirement from secondary/supplementary system	(98) x (301) x 100 ÷ (308) =	0	(309)
Water heating			
Annual water heating requirement		2109.26	
If DHW from community scheme:			
Water heat from Community CHP	(64) x (303a) x (305) x (306) =	1771.78	(310a)
Water heat from heat source 2	(64) x (303b) x (305) x (306) =	1181.19	(310b)
Electricity used for heat distribution	0.01 x [(307a)...(307e) + (310a)...(310e)] =	40.3	(313)
Cooling System Energy Efficiency Ratio		0	(314)
Space cooling (if there is a fixed cooling system, if not enter 0)	= (107) ÷ (314) =	0	(315)
Electricity for pumps and fans within dwelling (Table 4f): mechanical ventilation - balanced, extract or positive input from outside		305.6	(330a)
warm air heating system fans		0	(330b)
pump for solar water heating		0	(330g)
Total electricity for the above, kWh/year	=(330a) + (330b) + (330g) =	305.6	(331)
Energy for lighting (calculated in Appendix L)		345.49	(332)
Electricity generated by PVs (Appendix M) (negative quantity)		-380.25	(333)
Electricity generated by wind turbine (Appendix M) (negative quantity)		0	(334)
12b. CO2 Emissions – Community heating scheme			
Electrical efficiency of CHP unit		35	(361)
Heat efficiency of CHP unit		40	(362)
	Energy kWh/year	Emission factor kg CO2/kWh	Emissions kg CO2/year
Space heating from CHP	(307a) x 100 ÷ (362) =	1615.64	x 0.22 = 348.98 (363)
less credit emissions for electricity	-(307a) x (361) ÷ (362) =	565.47	x 0.52 = -293.48 (364)
Water heated by CHP	(310a) x 100 ÷ (362) =	4429.45	x 0.22 = 956.76 (365)
less credit emissions for electricity	-(310a) x (361) ÷ (362) =	1550.31	x 0.52 = -804.61 (366)
Efficiency of heat source 2 (%)	If there is CHP using two fuels repeat (363) to (366) for the second fuel	85	(367b)
CO2 associated with heat source 2	[(307b)+(310b)] x 100 ÷ (367b) x	0.22	= 409.64 (368)
Electrical energy for heat distribution	[(313) x	0.52	= 20.92 (372)
Total CO2 associated with community systems	(363)...(366) + (368)...(372)		= 638.21 (373)
CO2 associated with space heating (secondary)	(309) x	0	= 0 (374)

DER WorkSheet: New dwelling design stage

CO2 associated with water from immersion heater or instantaneous heater	(312) x	0.22	=	0	(375)
Total CO2 associated with space and water heating	(373) + (374) + (375) =			638.21	(376)
CO2 associated with electricity for pumps and fans within dwelling	(331) x	0.52	=	158.6	(378)
CO2 associated with electricity for lighting	(332)) x	0.52	=	179.31	(379)
Energy saving/generation technologies (333) to (334) as applicable Item 1		0.52	x 0.01 =	-197.35	(380)
Total CO2, kg/year	sum of (376)...(382) =			778.78	(383)
Dwelling CO2 Emission Rate	(383) ÷ (4) =			9.73	(384)
EI rating (section 14)				91.65	(385)

DRAFT