

# DER WorkSheet: New dwelling design stage

## Type 2: After Energy Demand Reduction

User Details:

Assessor Name:

Stroma Number:

Software Name: Stroma FSAP 2012

Software Version:

Version: 1.0.1.25

Property Address: L2 2BF East

Address : , NW1 1JD

### 1. Overall dwelling dimensions:

|   | Area(m <sup>2</sup> ) | Av. Height(m)                      | Volume(m <sup>3</sup> ) |
|---|-----------------------|------------------------------------|-------------------------|
| Ground floor  | 80 (1a)               | 3.15 (2a)                          | 252 (3a)                |
| Total floor area TFA = (1a)+(1b)+(1c)+(1d)+(1e)+.....(1n) | 80 (4)                |                                    |                         |
| Dwelling volume   |                       | (3a)+(3b)+(3c)+(3d)+(3e)+.....(3n) | 252 (5)                 |

### 2. Ventilation rate:

|                              | main heating | secondary heating | other | total | m <sup>3</sup> per hour |
|------------------------------|--------------|-------------------|-------|-------|-------------------------|
| Number of chimneys           | 0            | 0                 | 0     | 0     | 0 (6a)                  |
| Number of open flues         | 0            | 0                 | 0     | 0     | 0 (6b)                  |
| Number of intermittent fans  |              |                   |       | 0     | 0 (7a)                  |
| Number of passive vents      |              |                   |       | 0     | 0 (7b)                  |
| Number of flueless gas fires |              |                   |       | 0     | 0 (7c)                  |

|   |   |       |
|---|---|-------|
| Infiltration due to chimneys, flues and fans = (6a)+(6b)+(7a)+(7b)+(7c) = | 0 | 0 (8) |
|---|---|-------|

If a pressurisation test has been carried out or is intended, proceed to (17), otherwise continue from (9) to (16)

|  |   |       |
|--|---|-------|
| Number of storeys in the dwelling (ns) | 0 | 0 (9) |
|--|---|-------|

|                         |               |        |
|-------------------------|---------------|--------|
| Additional infiltration | [(9)-1]x0.1 = | 0 (10) |
|-------------------------|---------------|--------|

|  |   |        |
|--|---|--------|
| Structural infiltration: 0.25 for steel or timber frame or 0.35 for masonry construction | 0 | 0 (11) |
|--|---|--------|

if both types of wall are present, use the value corresponding to the greater wall area (after deducting areas of openings); if equal user 0.35

|   |   |        |
|---|---|--------|
| If suspended wooden floor, enter 0.2 (unsealed) or 0.1 (sealed), else enter 0 | 0 | 0 (12) |
|---|---|--------|

|   |   |        |
|---|---|--------|
| If no draught lobby, enter 0.05, else enter 0 | 0 | 0 (13) |
|---|---|--------|

|  |   |        |
|--|---|--------|
| Percentage of windows and doors draught stripped | 0 | 0 (14) |
|--|---|--------|

|                     |                             |        |
|---------------------|-----------------------------|--------|
| Window infiltration | 0.25 - [0.2 x (14) ÷ 100] = | 0 (15) |
|---------------------|-----------------------------|--------|

|                   |  |        |
|-------------------|--|--------|
| Infiltration rate | (8) + (10) + (11) + (12) + (13) + (15) = | 0 (16) |
|-------------------|--|--------|

|   |   |        |
|---|---|--------|
| Air permeability value, q50, expressed in cubic metres per hour per square metre of envelope area | 3 | 3 (17) |
|---|---|--------|

|  |      |           |
|--|------|-----------|
| If based on air permeability value, then (18) = [(17) ÷ 20] + (8), otherwise (18) = (16) | 0.15 | 0.15 (18) |
|--|------|-----------|

Air permeability value applies if a pressurisation test has been done or a degree air permeability is being used

|                           |   |        |
|---------------------------|---|--------|
| Number of sides sheltered | 0 | 0 (19) |
|---------------------------|---|--------|

|                |                             |        |
|----------------|-----------------------------|--------|
| Shelter factor | (20) = 1 - [0.075 x (19)] = | 1 (20) |
|----------------|-----------------------------|--------|

|  |                      |           |
|--|----------------------|-----------|
| Infiltration rate incorporating shelter factor | (21) = (18) x (20) = | 0.15 (21) |
|--|----------------------|-----------|

Infiltration rate modified for monthly wind speed

| Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|

Monthly average wind speed from Table 7

|        |     |   |     |     |     |     |     |     |   |     |     |     |
|--------|-----|---|-----|-----|-----|-----|-----|-----|---|-----|-----|-----|
| (22)m= | 5.1 | 5 | 4.9 | 4.4 | 4.3 | 3.8 | 3.8 | 3.7 | 4 | 4.3 | 4.5 | 4.7 |
|--------|-----|---|-----|-----|-----|-----|-----|-----|---|-----|-----|-----|

Wind Factor (22a)m = (22)m ÷ 4

|         |      |      |      |     |      |      |      |      |   |      |      |      |
|---------|------|------|------|-----|------|------|------|------|---|------|------|------|
| (22a)m= | 1.27 | 1.25 | 1.23 | 1.1 | 1.08 | 0.95 | 0.95 | 0.92 | 1 | 1.08 | 1.12 | 1.18 |
|---------|------|------|------|-----|------|------|------|------|---|------|------|------|

# DER WorkSheet: New dwelling design stage

Adjusted infiltration rate (allowing for shelter and wind speed) = (21a) x (22a)m

|      |      |      |      |      |      |      |      |      |      |      |      |
|------|------|------|------|------|------|------|------|------|------|------|------|
| 0.19 | 0.19 | 0.18 | 0.16 | 0.16 | 0.14 | 0.14 | 0.14 | 0.15 | 0.16 | 0.17 | 0.18 |
|------|------|------|------|------|------|------|------|------|------|------|------|

Calculate effective air change rate for the applicable case

If mechanical ventilation:

0.5 (23a)

If exhaust air heat pump using Appendix N, (23b) = (23a) x Fmv (equation (N5)) , otherwise (23b) = (23a)

0.5 (23b)

If balanced with heat recovery: efficiency in % allowing for in-use factor (from Table 4h) =

64.6 (23c)

a) If balanced mechanical ventilation with heat recovery (MVHR) (24a)m = (22b)m + (23b) x [1 - (23c) ÷ 100]

(24a)m= 0.37 0.36 0.36 0.34 0.34 0.32 0.32 0.32 0.33 0.34 0.35 0.35 (24a)

b) If balanced mechanical ventilation without heat recovery (MV) (24b)m = (22b)m + (23b)

(24b)m= 0 0 0 0 0 0 0 0 0 0 0 0 (24b)

c) If whole house extract ventilation or positive input ventilation from outside

if (22b)m < 0.5 x (23b), then (24c) = (23b); otherwise (24c) = (22b) m + 0.5 x (23b)

(24c)m= 0 0 0 0 0 0 0 0 0 0 0 0 (24c)

d) If natural ventilation or whole house positive input ventilation from loft

if (22b)m = 1, then (24d)m = (22b)m otherwise (24d)m = 0.5 + [(22b)m² x 0.5]

(24d)m= 0 0 0 0 0 0 0 0 0 0 0 0 (24d)

Effective air change rate - enter (24a) or (24b) or (24c) or (24d) in box (25)

(25)m= 0.37 0.36 0.36 0.34 0.34 0.32 0.32 0.32 0.33 0.34 0.35 0.35 (25)

## 3. Heat losses and heat loss parameter:

| ELEMENT                    | Gross area (m²) | Openings m² | Net Area A ,m² | U-value W/m²K                 | A X U (W/K) | k-value kJ/m²·K | A X k kJ/K |
|----------------------------|-----------------|-------------|----------------|-------------------------------|-------------|-----------------|------------|
| Windows Type 1             |                 |             | 2.85           | $\times 1/[1/(1.3) + 0.04] =$ | 3.52        |                 | (27)       |
| Windows Type 2             |                 |             | 12.65          | $\times 1/[1/(1.3) + 0.04] =$ | 15.63       |                 | (27)       |
| Walls                      | 67              | 21.2        | 45.8           | $\times 0.11 =$               | 5.04        |                 | (29)       |
| Total area of elements, m² |                 |             | 67             |                               |             |                 | (31)       |
| Party wall                 |                 |             | 19             | $\times 0 =$                  | 0           |                 | (32)       |
| Party wall                 |                 |             | 32             | $\times 0 =$                  | 0           |                 | (32)       |
| Party floor                |                 |             | 80             |                               |             |                 | (32a)      |
| Party ceiling              |                 |             | 80             |                               |             |                 | (32b)      |
| Internal wall **           |                 |             | 74             |                               |             |                 | (32c)      |

\* for windows and roof windows, use effective window U-value calculated using formula  $1/[(1/U\text{-value})+0.04]$  as given in paragraph 3.2

\*\* include the areas on both sides of internal walls and partitions

Fabric heat loss, W/K = S (A x U) (26)...(30) + (32) = 31.24 (33)

Heat capacity Cm = S(A x k ) ((28)...(30) + (32) + (32a)...(32e) = 31116 (34)

Thermal mass parameter (TMP = Cm ÷ TFA) in kJ/m²K Indicative Value: Medium 250 (35)

For design assessments where the details of the construction are not known precisely the indicative values of TMP in Table 1f can be used instead of a detailed calculation.

Thermal bridges : S (L x Y) calculated using Appendix K 7 (36)

if details of thermal bridging are not known (36) = 0.15 x (31)

Total fabric heat loss (33) + (36) = 38.24 (37)

Ventilation heat loss calculated monthly (38)m = 0.33 x (25)m x (5)

|        | Jan   | Feb   | Mar | Apr   | May   | Jun   | Jul   | Aug   | Sep   | Oct   | Nov   | Dec   |
|--------|-------|-------|-----|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| (38)m= | 30.62 | 30.31 | 30  | 28.44 | 28.13 | 26.57 | 26.57 | 26.26 | 27.19 | 28.13 | 28.75 | 29.38 |

Heat transfer coefficient, W/K (39)m = (37) + (38)m

(39)m= 68.86 68.55 68.24 66.68 66.36 64.81 64.81 64.49 65.43 66.36 66.99 67.61 (39)

# DER WorkSheet: New dwelling design stage

Heat loss parameter (HLP), W/m²K

$$(40)m = (39)m \div (4)$$

|        |  |      |      |      |      |      |      |      |      |      |      |      |      |      |
|--------|--|------|------|------|------|------|------|------|------|------|------|------|------|------|
| (40)m= | 0.86                                       | 0.86 | 0.85 | 0.83 | 0.83 | 0.81 | 0.81 | 0.81 | 0.82 | 0.83 | 0.84 | 0.85 |      |      |
|        | Average = Sum(40) <sub>1...12</sub> / 12 = |      |      |      |      |      |      |      |      |      |      |      | 0.83 | (40) |

Number of days in month (Table 1a)

|        |     |     |     |     |     |     |     |     |     |     |     |     |  |      |
|--------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|------|
|        | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |  |      |
| (41)m= | 31  | 28  | 31  | 30  | 31  | 30  | 31  | 31  | 30  | 31  | 30  | 31  |  | (41) |

## 4. Water heating energy requirement:

kWh/year:

Assumed occupancy, N

2.46

(42)

if TFA > 13.9, N = 1 + 1.76 x [1 - exp(-0.000349 x (TFA - 13.9)²)] + 0.0013 x (TFA - 13.9)

if TFA ≤ 13.9, N = 1

Annual average hot water usage in litres per day Vd,average = (25 x N) + 36

92.69

(43)

Reduce the annual average hot water usage by 5% if the dwelling is designed to achieve a water use target of not more than 125 litres per person per day (all water use, hot and cold)

|  |     |     |     |     |     |     |     |     |     |     |     |     |  |  |
|--|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|--|
|  | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |  |  |
|--|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|--|

Hot water usage in litres per day for each month Vd,m = factor from Table 1c x (43)

|        |                                     |       |       |       |       |       |       |       |       |       |       |        |         |      |
|--------|-------------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--------|---------|------|
| (44)m= | 101.96                              | 98.25 | 94.55 | 90.84 | 87.13 | 83.42 | 83.42 | 87.13 | 90.84 | 94.55 | 98.25 | 101.96 |         |      |
|        | Total = Sum(44) <sub>1...12</sub> = |       |       |       |       |       |       |       |       |       |       |        | 1112.32 | (44) |

Energy content of hot water used - calculated monthly = 4.190 x Vd,m x nm x DTm / 3600 kWh/month (see Tables 1b, 1c, 1d)

|        |                                     |        |        |        |        |       |       |        |     |        |        |        |         |      |
|--------|-------------------------------------|--------|--------|--------|--------|-------|-------|--------|-----|--------|--------|--------|---------|------|
| (45)m= | 151.21                              | 132.25 | 136.47 | 118.97 | 114.16 | 98.51 | 91.28 | 104.75 | 106 | 123.53 | 134.85 | 146.44 |         |      |
|        | Total = Sum(45) <sub>1...12</sub> = |        |        |        |        |       |       |        |     |        |        |        | 1458.42 | (45) |

If instantaneous water heating at point of use (no hot water storage), enter 0 in boxes (46) to (61)

|        |       |       |       |       |       |       |       |       |      |       |       |       |  |      |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|------|-------|-------|-------|--|------|
| (46)m= | 22.68 | 19.84 | 20.47 | 17.85 | 17.12 | 14.78 | 13.69 | 15.71 | 15.9 | 18.53 | 20.23 | 21.97 |  | (46) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|------|-------|-------|-------|--|------|

Water storage loss:

Storage volume (litres) including any solar or WWHRS storage within same vessel

0

(47)

If community heating and no tank in dwelling, enter 110 litres in (47)

Otherwise if no stored hot water (this includes instantaneous combi boilers) enter '0' in (47)

Water storage loss:

a) If manufacturer's declared loss factor is known (kWh/day):

0

(48)

Temperature factor from Table 2b

0

(49)

Energy lost from water storage, kWh/year

$$(48) \times (49) =$$

110

(50)

b) If manufacturer's declared cylinder loss factor is not known:

Hot water storage loss factor from Table 2 (kWh/litre/day)

0.02

(51)

If community heating see section 4.3

Volume factor from Table 2a

1.03

(52)

Temperature factor from Table 2b

0.6

(53)

Energy lost from water storage, kWh/year

$$(47) \times (51) \times (52) \times (53) =$$

1.03

(54)

Enter (50) or (54) in (55)

1.03

(55)

Water storage loss calculated for each month

$$((56)m = (55) \times (41)m$$

|        |       |       |       |       |       |       |       |       |       |       |       |       |  |      |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|------|
| (56)m= | 32.01 | 28.92 | 32.01 | 30.98 | 32.01 | 30.98 | 32.01 | 32.01 | 30.98 | 32.01 | 30.98 | 32.01 |  | (56) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|------|

If cylinder contains dedicated solar storage, (57)m = (56)m x [(50) - (H11)] ÷ (50), else (57)m = (56)m where (H11) is from Appendix H

|        |       |       |       |       |       |       |       |       |       |       |       |       |  |      |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|------|
| (57)m= | 32.01 | 28.92 | 32.01 | 30.98 | 32.01 | 30.98 | 32.01 | 32.01 | 30.98 | 32.01 | 30.98 | 32.01 |  | (57) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|------|

Primary circuit loss (annual) from Table 3

0

(58)

Primary circuit loss calculated for each month (59)m = (58) ÷ 365 x (41)m

(modified by factor from Table H5 if there is solar water heating and a cylinder thermostat)

|        |       |       |       |       |       |       |       |       |       |       |       |       |  |      |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|------|
| (59)m= | 23.26 | 21.01 | 23.26 | 22.51 | 23.26 | 22.51 | 23.26 | 23.26 | 22.51 | 23.26 | 22.51 | 23.26 |  | (59) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|--|------|

## DER WorkSheet: New dwelling design stage

Combi loss calculated for each month (61)m = (60) ÷ 365 × (41)m

|        |   |   |   |   |   |   |   |   |   |   |   |      |
|--------|---|---|---|---|---|---|---|---|---|---|---|------|
| (61)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | (61) |
|--------|---|---|---|---|---|---|---|---|---|---|---|------|

Total heat required for water heating calculated for each month (62)m = 0.85 × (45)m + (46)m + (57)m + (59)m + (61)m

|        |        |        |        |        |        |     |        |        |       |        |        |        |      |
|--------|--------|--------|--------|--------|--------|-----|--------|--------|-------|--------|--------|--------|------|
| (62)m= | 206.48 | 182.17 | 191.74 | 172.47 | 169.44 | 152 | 146.56 | 160.03 | 159.5 | 178.81 | 188.34 | 201.71 | (62) |
|--------|--------|--------|--------|--------|--------|-----|--------|--------|-------|--------|--------|--------|------|

Solar DHW input calculated using Appendix G or Appendix H (negative quantity) (enter '0' if no solar contribution to water heating)

(add additional lines if FGHRs and/or WWHRs applies, see Appendix G)

|        |   |   |   |   |   |   |   |   |   |   |   |      |
|--------|---|---|---|---|---|---|---|---|---|---|---|------|
| (63)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | (63) |
|--------|---|---|---|---|---|---|---|---|---|---|---|------|

Output from water heater

|   |        |        |        |        |        |     |        |        |       |        |        |         |      |
|---|--------|--------|--------|--------|--------|-----|--------|--------|-------|--------|--------|---------|------|
| (64)m=  | 206.48 | 182.17 | 191.74 | 172.47 | 169.44 | 152 | 146.56 | 160.03 | 159.5 | 178.81 | 188.34 | 201.71  |      |
| Output from water heater (annual) <sub>1...12</sub> |        |        |        |        |        |     |        |        |       |        |        | 2109.26 | (64) |

Heat gains from water heating, kWh/month 0.25 × [0.85 × (45)m + (61)m] + 0.8 × [(46)m + (57)m + (59)m]

|        |      |       |      |       |       |       |       |       |       |      |       |       |      |
|--------|------|-------|------|-------|-------|-------|-------|-------|-------|------|-------|-------|------|
| (65)m= | 94.5 | 83.91 | 89.6 | 82.35 | 82.18 | 75.55 | 74.57 | 79.05 | 78.04 | 85.3 | 87.63 | 92.91 | (65) |
|--------|------|-------|------|-------|-------|-------|-------|-------|-------|------|-------|-------|------|

include (57)m in calculation of (65)m only if cylinder is in the dwelling or hot water is from community heating

### 5. Internal gains (see Table 5 and 5a):

Metabolic gains (Table 5), Watts

|        | Jan    | Feb    | Mar    | Apr    | May    | Jun    | Jul    | Aug    | Sep    | Oct    | Nov    | Dec    |      |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (66)m= | 123.14 | 123.14 | 123.14 | 123.14 | 123.14 | 123.14 | 123.14 | 123.14 | 123.14 | 123.14 | 123.14 | 123.14 | (66) |

Lighting gains (calculated in Appendix L, equation L9 or L9a), also see Table 5

|        |       |       |       |      |   |      |     |      |       |       |       |       |      |
|--------|-------|-------|-------|------|---|------|-----|------|-------|-------|-------|-------|------|
| (67)m= | 19.56 | 17.38 | 14.13 | 10.7 | 8 | 6.75 | 7.3 | 9.48 | 12.73 | 16.16 | 18.86 | 20.11 | (67) |
|--------|-------|-------|-------|------|---|------|-----|------|-------|-------|-------|-------|------|

Appliances gains (calculated in Appendix L, equation L13 or L13a), also see Table 5

|        |        |        |        |        |        |        |        |        |        |        |        |        |      |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (68)m= | 219.44 | 221.72 | 215.98 | 203.76 | 188.34 | 173.85 | 164.17 | 161.89 | 167.63 | 179.84 | 195.27 | 209.76 | (68) |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|

Cooking gains (calculated in Appendix L, equation L15 or L15a), also see Table 5

|        |       |       |       |       |       |       |       |       |       |       |       |       |      |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (69)m= | 35.31 | 35.31 | 35.31 | 35.31 | 35.31 | 35.31 | 35.31 | 35.31 | 35.31 | 35.31 | 35.31 | 35.31 | (69) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

Pumps and fans gains (Table 5a)

|        |   |   |   |   |   |   |   |   |   |   |   |   |      |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|------|
| (70)m= | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | (70) |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|------|

Losses e.g. evaporation (negative values) (Table 5)

|        |        |        |        |        |        |        |        |        |        |        |        |        |      |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (71)m= | -98.51 | -98.51 | -98.51 | -98.51 | -98.51 | -98.51 | -98.51 | -98.51 | -98.51 | -98.51 | -98.51 | -98.51 | (71) |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|

Water heating gains (Table 5)

|        |        |        |        |        |        |        |        |        |        |        |        |        |      |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (72)m= | 127.01 | 124.87 | 120.43 | 114.38 | 110.46 | 104.93 | 100.23 | 106.25 | 108.39 | 114.65 | 121.71 | 124.88 | (72) |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|

**Total internal gains =** (66)m + (67)m + (68)m + (69)m + (70)m + (71)m + (72)m

|        |        |        |        |        |        |        |        |        |        |        |        |        |      |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|
| (73)m= | 425.96 | 423.91 | 410.48 | 388.79 | 366.74 | 345.47 | 331.64 | 337.57 | 348.69 | 370.59 | 395.78 | 414.69 | (73) |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|------|

### 6. Solar gains:

Solar gains are calculated using solar flux from Table 6a and associated equations to convert to the applicable orientation.

| Orientation:   | Access Factor<br>Table 6d |   | Area<br>m <sup>2</sup> |   | Flux<br>Table 6a |   | g_<br>Table 6b |   | FF<br>Table 6c |   | Gains<br>(W) |      |
|----------------|---------------------------|---|------------------------|---|------------------|---|----------------|---|----------------|---|--------------|------|
| Northeast 0.9x | 0.77                      | x | 2.85                   | x | 11.28            | x | 0.7            | x | 1.11           | = | 52           | (75) |
| Northeast 0.9x | 0.77                      | x | 2.85                   | x | 22.97            | x | 0.7            | x | 1.11           | = | 105.84       | (75) |
| Northeast 0.9x | 0.77                      | x | 2.85                   | x | 41.38            | x | 0.7            | x | 1.11           | = | 190.69       | (75) |
| Northeast 0.9x | 0.77                      | x | 2.85                   | x | 67.96            | x | 0.7            | x | 1.11           | = | 313.17       | (75) |
| Northeast 0.9x | 0.77                      | x | 2.85                   | x | 91.35            | x | 0.7            | x | 1.11           | = | 420.96       | (75) |

## DER WorkSheet: New dwelling design stage

|                |      |   |       |   |        |   |     |   |      |   |        |      |
|----------------|------|---|-------|---|--------|---|-----|---|------|---|--------|------|
| Northeast 0.9x | 0.77 | x | 2.85  | x | 97.38  | x | 0.7 | x | 1.11 | = | 448.79 | (75) |
| Northeast 0.9x | 0.77 | x | 2.85  | x | 91.1   | x | 0.7 | x | 1.11 | = | 419.84 | (75) |
| Northeast 0.9x | 0.77 | x | 2.85  | x | 72.63  | x | 0.7 | x | 1.11 | = | 334.7  | (75) |
| Northeast 0.9x | 0.77 | x | 2.85  | x | 50.42  | x | 0.7 | x | 1.11 | = | 232.36 | (75) |
| Northeast 0.9x | 0.77 | x | 2.85  | x | 28.07  | x | 0.7 | x | 1.11 | = | 129.35 | (75) |
| Northeast 0.9x | 0.77 | x | 2.85  | x | 14.2   | x | 0.7 | x | 1.11 | = | 65.43  | (75) |
| Northeast 0.9x | 0.77 | x | 2.85  | x | 9.21   | x | 0.7 | x | 1.11 | = | 42.46  | (75) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 36.79  | x | 0.7 | x | 1.11 | = | 175.94 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 62.67  | x | 0.7 | x | 1.11 | = | 299.69 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 85.75  | x | 0.7 | x | 1.11 | = | 410.04 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 106.25 | x | 0.7 | x | 1.11 | = | 508.06 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 119.01 | x | 0.7 | x | 1.11 | = | 569.07 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 118.15 | x | 0.7 | x | 1.11 | = | 564.96 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 113.91 | x | 0.7 | x | 1.11 | = | 544.68 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 104.39 | x | 0.7 | x | 1.11 | = | 499.16 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 92.85  | x | 0.7 | x | 1.11 | = | 443.99 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 69.27  | x | 0.7 | x | 1.11 | = | 331.22 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 44.07  | x | 0.7 | x | 1.11 | = | 210.73 | (77) |
| Southeast 0.9x | 0.54 | x | 12.65 | x | 31.49  | x | 0.7 | x | 1.11 | = | 150.57 | (77) |

Solar gains in watts, calculated for each month

(83)m = Sum(74)m ... (82)m

|        |        |        |        |        |        |         |        |        |        |        |        |        |      |
|--------|--------|--------|--------|--------|--------|---------|--------|--------|--------|--------|--------|--------|------|
| (83)m= | 227.93 | 405.53 | 600.74 | 821.23 | 990.04 | 1013.75 | 964.51 | 833.86 | 676.35 | 460.56 | 276.16 | 193.03 | (83) |
|--------|--------|--------|--------|--------|--------|---------|--------|--------|--------|--------|--------|--------|------|

Total gains – internal and solar (84)m = (73)m + (83)m , watts

|        |        |        |         |         |         |         |         |         |         |        |        |        |      |
|--------|--------|--------|---------|---------|---------|---------|---------|---------|---------|--------|--------|--------|------|
| (84)m= | 653.89 | 829.44 | 1011.21 | 1210.02 | 1356.78 | 1359.22 | 1296.15 | 1171.43 | 1025.04 | 831.16 | 671.94 | 607.72 | (84) |
|--------|--------|--------|---------|---------|---------|---------|---------|---------|---------|--------|--------|--------|------|

### 7. Mean internal temperature (heating season)

Temperature during heating periods in the living area from Table 9, Th1 (°C)

21 (85)

Utilisation factor for gains for living area, h1,m (see Table 9a)

|        |      |      |      |      |      |      |      |      |      |      |      |      |      |
|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|
|        | Jan  | Feb  | Mar  | Apr  | May  | Jun  | Jul  | Aug  | Sep  | Oct  | Nov  | Dec  |      |
| (86)m= | 0.99 | 0.95 | 0.86 | 0.65 | 0.45 | 0.31 | 0.22 | 0.25 | 0.44 | 0.78 | 0.96 | 0.99 | (86) |

Mean internal temperature in living area T1 (follow steps 3 to 7 in Table 9c)

|        |       |       |       |       |    |    |    |    |    |       |       |       |      |
|--------|-------|-------|-------|-------|----|----|----|----|----|-------|-------|-------|------|
| (87)m= | 20.38 | 20.61 | 20.85 | 20.98 | 21 | 21 | 21 | 21 | 21 | 20.94 | 20.65 | 20.34 | (87) |
|--------|-------|-------|-------|-------|----|----|----|----|----|-------|-------|-------|------|

Temperature during heating periods in rest of dwelling from Table 9, Th2 (°C)

|        |      |      |       |       |       |       |       |       |       |       |       |       |      |
|--------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (88)m= | 20.2 | 20.2 | 20.21 | 20.22 | 20.23 | 20.24 | 20.24 | 20.25 | 20.24 | 20.23 | 20.22 | 20.21 | (88) |
|--------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

Utilisation factor for gains for rest of dwelling, h2,m (see Table 9a)

|        |      |      |      |      |      |      |      |      |      |      |      |      |      |
|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| (89)m= | 0.98 | 0.94 | 0.83 | 0.61 | 0.42 | 0.27 | 0.18 | 0.21 | 0.39 | 0.73 | 0.95 | 0.99 | (89) |
|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|

Mean internal temperature in the rest of dwelling T2 (follow steps 3 to 7 in Table 9c)

|        |       |       |       |      |       |       |       |       |       |       |       |       |      |
|--------|-------|-------|-------|------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (90)m= | 19.38 | 19.72 | 20.03 | 20.2 | 20.23 | 20.24 | 20.24 | 20.25 | 20.24 | 20.17 | 19.79 | 19.34 | (90) |
|--------|-------|-------|-------|------|-------|-------|-------|-------|-------|-------|-------|-------|------|

fLA = Living area ÷ (4) =

0.4 (91)

Mean internal temperature (for the whole dwelling) = fLA × T1 + (1 – fLA) × T2

|        |       |       |       |       |       |       |       |       |       |       |       |       |      |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (92)m= | 19.78 | 20.08 | 20.36 | 20.51 | 20.53 | 20.55 | 20.55 | 20.55 | 20.54 | 20.48 | 20.13 | 19.74 | (92) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

Apply adjustment to the mean internal temperature from Table 4e, where appropriate

# DER WorkSheet: New dwelling design stage

|        |       |       |       |       |       |       |       |       |       |       |       |       |      |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
| (93)m= | 19.78 | 20.08 | 20.36 | 20.51 | 20.53 | 20.55 | 20.55 | 20.55 | 20.54 | 20.48 | 20.13 | 19.74 | (93) |
|--------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|

## 8. Space heating requirement

Set  $T_i$  to the mean internal temperature obtained at step 11 of Table 9b, so that  $T_{i,m}=(76)m$  and re-calculate the utilisation factor for gains using Table 9a

| Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|

Utilisation factor for gains,  $h_m$ :

|        |      |      |      |      |      |      |     |      |      |      |      |      |      |
|--------|------|------|------|------|------|------|-----|------|------|------|------|------|------|
| (94)m= | 0.98 | 0.94 | 0.83 | 0.63 | 0.43 | 0.28 | 0.2 | 0.23 | 0.41 | 0.75 | 0.95 | 0.99 | (94) |
|--------|------|------|------|------|------|------|-----|------|------|------|------|------|------|

Useful gains,  $h_m G_m$ ,  $W = (94)m \times (84)m$

|        |        |        |        |        |        |        |        |        |       |        |        |       |      |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|--------|--------|-------|------|
| (95)m= | 642.39 | 780.97 | 844.01 | 758.68 | 584.97 | 385.32 | 255.77 | 267.56 | 420.8 | 620.87 | 639.37 | 600.2 | (95) |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------|--------|--------|-------|------|

Monthly average external temperature from Table 8

|        |     |     |     |     |      |      |      |      |      |      |     |     |      |
|--------|-----|-----|-----|-----|------|------|------|------|------|------|-----|-----|------|
| (96)m= | 4.3 | 4.9 | 6.5 | 8.9 | 11.7 | 14.6 | 16.6 | 16.4 | 14.1 | 10.6 | 7.1 | 4.2 | (96) |
|--------|-----|-----|-----|-----|------|------|------|------|------|------|-----|-----|------|

Heat loss rate for mean internal temperature,  $L_m$ ,  $W = [(39)m \times [(93)m - (96)m]$

|        |         |         |        |        |       |        |        |        |        |        |        |         |      |
|--------|---------|---------|--------|--------|-------|--------|--------|--------|--------|--------|--------|---------|------|
| (97)m= | 1065.91 | 1040.38 | 945.58 | 774.13 | 586.3 | 385.38 | 255.77 | 267.57 | 421.47 | 655.73 | 872.89 | 1050.53 | (97) |
|--------|---------|---------|--------|--------|-------|--------|--------|--------|--------|--------|--------|---------|------|

Space heating requirement for each month,  $kWh/month = 0.024 \times [(97)m - (95)m] \times (41)m$

|        |        |        |       |       |      |   |   |   |   |       |        |        |  |
|--------|--------|--------|-------|-------|------|---|---|---|---|-------|--------|--------|--|
| (98)m= | 315.11 | 174.33 | 75.57 | 11.13 | 0.99 | 0 | 0 | 0 | 0 | 25.93 | 168.13 | 335.05 |  |
|--------|--------|--------|-------|-------|------|---|---|---|---|-------|--------|--------|--|

Total per year ( $kWh/year$ ) =  $Sum(98)_{1...12} =$  1106.23 (98)

Space heating requirement in  $kWh/m^2/year$

13.83 (99)

## 9b. Energy requirements – Community heating scheme

This part is used for space heating, space cooling or water heating provided by a community scheme.

Fraction of space heat from secondary/supplementary heating (Table 11) '0' if none

0 (301)

Fraction of space heat from community system 1 – (301) =

1 (302)

*The community scheme may obtain heat from several sources. The procedure allows for CHP and up to four other heat sources; the latter includes boilers, heat pumps, geothermal and waste heat from power stations. See Appendix C.*

Fraction of heat from Community boilers

1 (303a)

Fraction of total space heat from Community boilers

(302) x (303a) = 1 (304a)

Factor for control and charging method (Table 4c(3)) for community heating system

1 (305)

Distribution loss factor (Table 12c) for community heating system

1.2 (306)

### Space heating

Annual space heating requirement

**kWh/year**  
1106.23

Space heat from Community boilers

(98) x (304a) x (305) x (306) = 1327.48 (307a)

Efficiency of secondary/supplementary heating system in % (from Table 4a or Appendix E)

0 (308)

Space heating requirement from secondary/supplementary system

(98) x (301) x 100 ÷ (308) = 0 (309)

### Water heating

Annual water heating requirement

2109.26

If DHW from community scheme:

Water heat from Community boilers

(64) x (303a) x (305) x (306) = 2531.11 (310a)

Electricity used for heat distribution

$0.01 \times [(307a) \dots (307e) + (310a) \dots (310e)] =$  38.59 (313)

Cooling System Energy Efficiency Ratio

0 (314)

Space cooling (if there is a fixed cooling system, if not enter 0)

$= (107) \div (314) =$  0 (315)

Electricity for pumps and fans within dwelling (Table 4f):

mechanical ventilation - balanced, extract or positive input from outside

253.95 (330a)

## DER WorkSheet: New dwelling design stage

|  |                               |        |        |
|--|-------------------------------|--------|--------|
| warm air heating system fans                   |                               | 0      | (330b) |
| pump for solar water heating                   |                               | 0      | (330g) |
| Total electricity for the above, kWh/year      | $=(330a) + (330b) + (330g) =$ | 253.95 | (331)  |
| Energy for lighting (calculated in Appendix L) |                               | 345.49 | (332)  |

### 12b. CO2 Emissions – Community heating scheme

|   | Energy<br>kWh/year  | Emission factor<br>kg CO2/kWh | Emissions<br>kg CO2/year |
|---|---|-------------------------------|--------------------------|
| CO2 from other sources of space and water heating (not CHP)             |   |                               |                          |
| Efficiency of heat source 1 (%)   | If there is CHP using two fuels repeat (363) to (366) for the second fuel |                               | 89 (367a)                |
| CO2 associated with heat source 1                                       | $[(307b)+(310b)] \times 100 \div (367b) \times$                           | 0                             | = 936.47 (367)           |
| Electrical energy for heat distribution                                 | $[(313) \times$   | 0.52                          | = 20.03 (372)            |
| Total CO2 associated with community systems                             | $(363)...(366) + (368)...(372)$   |                               | = 956.49 (373)           |
| CO2 associated with space heating (secondary)                           | $(309) \times$  | 0                             | = 0 (374)                |
| CO2 associated with water from immersion heater or instantaneous heater | $(312) \times$  | 0.22                          | = 0 (375)                |
| Total CO2 associated with space and water heating                       | $(373) + (374) + (375) =$   |                               | 956.49 (376)             |
| CO2 associated with electricity for pumps and fans within dwelling      | $(331)) \times$   | 0.52                          | = 131.8 (378)            |
| CO2 associated with electricity for lighting                            | $(332))) \times$  | 0.52                          | = 179.31 (379)           |
| <b>Total CO2, kg/year</b>   | sum of (376)...(382) =  |                               | 1267.6 (383)             |
| <b>Dwelling CO2 Emission Rate</b>                                       | $(383) \div (4) =$  |                               | 15.85 (384)              |
| <b>EI rating (section 14)</b>   |   |                               | 86.41 (385)              |