



Notes:

Concrete

Grade C32 / 40 (RC 40) minimum OPC 340 kg/cubic M and a max free water cement ratio of 0.5

Blinding grade C10

20mm aggregate

75mm cover to inks at bottom, 40mm to top & sides

Suspended Ground Floor

Imposed 5 kn/sqcm

Finishes 2 kn/sqcm

Max O/w PC floor 3 kn/sqcm

Ground bearing slab.

Laid on 1200g polythene with 150mm double lapped and taped joints

200mm consolidated granular fill under slab

Brickwork.

20 n/sqmm min strength bricks in 1:1:6 mortar

Reinforcement in ground beams.

Provisional

H20 bars 30 kg/m run

H10 links 10 kg/m run

P1	Preliminary	7 Dec 15
----	-------------	----------

revisions

C J Dewhurst Ltd

27 St James's Avenue,
Hampton Hill,
Windsor,
Windsor,
WY13 2JH
Tel: 07888 821 422
e-mail: chj@dewng.com

CJD

The Cumberland Lawn Tennis Club
25 Alvenley Gardens
London NW6 1JD

Ground Floor Slab GA

Scale:	1:50 @ A1	Date:	Dec 15	Job No:	8872
Drawn No:	E-003	Rev'n:	P1		