

mirage LED IP65

Ceiling recessed LED luminaire for outdoor applications



Optics

- Light output options:
 - 2000 lumens (23W)
- Wide beam symmetrical distribution
- Clear flat acrylic diffuser in bezel or acrylic feature optic
- Anodised aluminium reflector

Body

- Extruded and cast aluminium
- IP65 IK10 rated protection
- Finished in Anthracite Grey
- To suit ceiling thickness 5 – 50mm
- Dali dimming as standard



Acrylic feature glass

Order Codes

Mirage LED IP65

2000 lumen (23W)

Clear diffuser

M65AY164K

2000 lumen (23W)

Acrylic feature glass

M65BY164K


Options

3000K

Replace 4 with 3

i.e. M65AY163K

Dimensions




Ø	H	L	CAØ	KG
202	132	174	185	2.8

LED Performance

Colour Temp	Ra (CRI)	Life Expectancy	Colour Consistency
4000K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 3 SDCM
3000K	≥ 80	L ₇₀ (50,000hrs)	MacAdam 3 SDCM

Photometric Performance



23W 2000 lumen
• LOR = 100%

To Specify

IP65 Recessed LED luminaire with aluminium body and clear diffuser or part screened feature optic. With wide beam distribution – as Whitecroft Lighting MIRAGE LED IP65.