

F10 Brick/ block walling

To be read with Preliminaries/ General conditions.

MATERIALS SPECIFICATION

External walls shall consist of building elements and materials that achieve A or A+ rating, under BRE's Green Guide to Specification categorisation.

TYPES OF WALLING

- 110 CLAY FACING BRICKWORK TO EXTERNAL LEAF OF CAVITY WALL - NEW BUILD GENERALLY
- Bricks: To BS EN 771-1.
 - Manufacturer: Engels Baksteen (NL)
 - UK supplier: Traditional Brick & Stone Limited.
 - Product reference: Mystique EH921.
 - Recycled content: Submit proposals.
 - Special shapes: Sill bricks as shown on drawings - as section F30.
 - Mortar: As section Z21.
 - Standard: To BS EN 998-2.
 - Mix: 1:1:6 cement:lime:sand.
 - Additional requirements:
 - Coloured mortar CPI Euro Mix, natural light grey ref. M3ANK100 or similar approved
 - Damp proof course brickwork as clause 385 - location as per drawings - No external lightening tapes, conduits or cabling to be fixed to the cladding .
 - Bond: Half lap stretcher .
 - Joints: Bucket handle 4mm recessed .
 - Features: generally as shown on architects drawings
 - Full brick reveals to all openings
 - Brick slip clad soffits to all openings (stretchers on elevation .