



T1 = TIMBER STUD PARTITIONS PAINT FINISH (150mm) min. 43dB rated acoustic partition to be constructed by 50x100 C6 timber stud at 350c/c with two layer of 12.5mm Gyproc SoundBloc RAPID boards each side and 50mm ROCKWOOL FLEXI insulation between studs. Allow to prepare for decoration each side.

T2 = TIMBER STUD PARTITIONS PAINT AND TILE FINISH (168mm) min. 43dB rated acoustic partition to be constructed by 50x100 C6 timber stud at 350c/c with one layer of 18mm plywood boards at wet-room side and two layer of 12.5mm Gyproc SoundBloc RAPID boards at the other side timber studs and 50mm ROCKWOOL FLEXI insulation between studs. Allow for waterproofing lining boards in preparation for tile finish at wet-roomside and allow for decoration on other side.

| REV | DATE | BY | DESCRIPTION | CHK |
|-----------------------------|------|----|-------------|-----|
| DRAWING STATUS: INFORMATION | | | | |

| | |
|----------------|--|
| CLIENT: | CLIENT |
| LEAD DESIGNER: | P-U-R-A, LTD |
| PROJECT: | 12-14 Northington Street, WC1 2NW, London. |
| DRAWING TITLE: | FIRST FLOOR PLAN AS PROPOSED |

| | |
|---------------|----------|
| SCALE: | 1:50 |
| DESIGN/DRAWN: | AL |
| CHECKED: | CH |
| DATE: | 12.11.15 |
| PROJECT NO.: | 0995 |
| DRAWING NO.: | 20-101 |
| REV.: | F |

© Copyright to all designs, notes and drawings remains with P-U-R-A, LTD subject to written authorisation.
 • All dimensions in mm unless noted otherwise.
 • All materials to be used shall be of the highest quality.
 • Their accuracy cannot be guaranteed and therefore cannot be used for fabrication, manufacture or construction.
 • Contractor to verify and to be responsible for all requirements and restrictions due to local rules.
 • To report there is any discrepancy in the drawings to P-U-R-A, LTD in time to specify alterations.
 • This drawing is to be read together with all other relevant drawings.
 • Do not scale from this drawing.

