

NOTES:

COPYRIGHT RESERVED BY BAMFORD-MUMBY LID T/A
AB ASSOCIATES.
DO NOT SCALE THIS DRAWING.
BO NOT USE THIS DRAWING FOR ANY PURPOSE OTHER
THAN DEFINED BY THE DRAWING STATUS
CONTRACTOR TO CHECK ALL DIMENSIONS ON SITE PRIOR
TO COMMENCEMENT OF WORKS. ANY DISCREPANCIES TO
BE RAISED WITH THE ABA WHEDIATELY.

## LEGEND:

AREA TO BE LICENSED

CO2 Extinguisher



Foam Extinguisher



Water Extinguisher



Wet Chemical



Fire Blanket

1/2 HR FR SQ

1/2 Hour fire resistant self closing door with smoke seals and intumescent strips

Fire exit doors fitted with emergency push bar facility

513) Sign - Fire door keep shut

POINT OF CUSTOMER ACCESS

FIRE ALARM

A Fire Alarm system will be installed to BS5839 Part 1 2013 Code of practice for system design, installation, commissioning and maintenance, comprising of devices as indicated.

FAP

FIRE ALARM PANEL

MH

MAGNETIC DOOR HOLDER

MANUAL CALL POINT HEAT DETECTOR

K S

SMOKE DETECTOR

VOID DETECTOR SOUNDER

INDICATOR FOR VOID DETECTOR

V

**(K)** SOUNDER BEACON

INTERFACE H = HVAC

d

D