

C.2. DX condenser units

PUHZ-RP-YKA - OUTDOOR UNITS		PUHZ-RP200YKA	PUHZ-RP250YKA	PUHZ-RP200YKA x2	PUHZ-RP250YKA x2
MODEL REFERENCE					
NOISE (dBA)	Heating/Cooling (silent)	59 / 58 (55)	59 / 58 (55)	59 / 58 (55)	59 / 58 (55)
WEIGHT (kg)		135	141	135	141
DIMENSIONS (mm)	Width	1050	1050	1050	1050
	Depth	330 + 30	330 + 30	330 + 30	330 + 30
	Height	1338	1338	1338	1338
ELECTRICAL SUPPLY		380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz	380-415v, 50Hz
PHASE		3	3	3	3
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	6.5 / 6.7	8.2 / 8.34	12.55 / 12.95	16.88 / 17.16
	Heating/Cooling (UK)	5.79 / 5.7	7.3 / 7.09	11.17 / 11.01	15.02 / 14.59
STARTING CURRENT (A)		5	5	5	5
RUNNING CURRENT (A)	[Max] Heating/Cooling	8.63 / 8.94 [19]	11.01 / 11.23 [21]	8.63 / 8.94 [19]	11.01 / 11.23 [21]
FUSE RATING (BS88) - HRC (A)		20	25	20	25
MAINS CABLE No. Cores		5	5	5	5
MAX PIPE LENGTH (m)		120	120	120	120
MAX HEIGHT DIFFERENCE (m)		30	30	30	30
CHARGE R410A (kg) - 30m		7.1	7.7	7.1	7.7

Page 78

UHZ-RP250YKA

MODE	SPL(dB)	LINE
COOLING	58	○—○
HEATING	59	●—●



