



KEY	
	RED LINE BOUNDARY / HOARDING LINE (bcs)
	NEW GRANITE SETTS SAWN THEN BUSH HAMMERED TOP WITH SAWN SIDES 200/250/300L x 100W x 150D COLOURS: MILLENNIUM MAUVE - 85% MILLENNIUM PINK - 15% (JOINT WIDTH = 10-15mm)
	3no. ROWS NEW GRANITE SETT EDGING TO ROADWAY SAWN THEN BUSH HAMMERED TOP WITH SAWN SIDES 200/250/300L x 100W x 150D COLOURS: MILLENNIUM MAUVE - 85% MILLENNIUM PINK - 15% (JOINT WIDTH = 10-15mm)
	NEW GRANITE WITH 6mm HIGH UPSTAND, FINE PICKED FINISH 1000L x 300W x 200D COLOUR: ROYAL WHITE (JOINT WIDTH = 6mm)
	NEW GRANITE FLUSH KERB FINE PICKED FINISH 1000L x 300W x 200D COLOUR: ROYAL WHITE (JOINT WIDTH = 10-15mm)
	NEW PORPHYRY PAVING RIVEN FINISH 400-600L x 200W x 55D COLOUR TO MATCH EXISTING (JOINT WIDTH = 6mm)
	NEW GRANITE SETTS SAWN THEN BUSH HAMMERED TOP WITH SAWN SIDES 200/250/300L x 100W x 75D COLOURS: MILLENNIUM MAUVE - 85% MILLENNIUM PINK - 15% (JOINT WIDTH = 6mm)
	NEW GRANITE SETTS SAWN THEN BUSH HAMMERED TOP WITH SAWN SIDES 200/250/300L x 100W x 150D COLOURS: MILLENNIUM MAUVE - 65% MILLENNIUM PINK - 20% ALBION GREY - 15% (JOINT WIDTH = 10-15mm)
	NEW GRANITE SETTS WITH GRASS SEEDED JOINTS, SAWN THEN BUSH HAMMERED TOP WITH SPLIT SIDES. 200/250/300L x 100W x 75D COLOURS: MILLENNIUM MAUVE - 85% MILLENNIUM PINK - 15% (JOINT WIDTH = 10-15mm)
	RECLAIMED (FROM SITE) ROUGH-TOP GRANITE SETTS 100-300L x 90-140W x 150D APP. COLOURS AS FOUND. (JOINT WIDTH = 10-15mm)
	RECLAIMED (FROM SITE) SAWN THEN FLAMED SURFACE GRANITE SETTS 100-300L x 90-140W x 150D APP. COLOURS AS FOUND. (JOINT WIDTH = 10-15mm)
	RECLAIMED (FROM SITE) FLAMED SURFACE GRANITE SETTS WITH SEEDED JOINTS 100-300L x 90-140W x 150D APP. (JOINT WIDTH = 10-15mm)
	RECLAIMED (FROM SITE) STOCK BRICK COPING & CLADDING 225L x 105W x 65D APPROX. COLOURS AS FOUND (JOINT WIDTH = 10-15mm)
	NEW LEICESTER MULTI CREAM STOCK BRICK COPING 223L x 107W x 68D (JOINT WIDTH = 10-15mm)
	NEW SOLID UNIT GRANITE SEATS, FLAMED FINISH TO ALL VISIBLE FACES, 494L x 466W ON PLAN COLOUR: MILLENNIUM MAUVE (JOINT WIDTH = 6mm)
	NEW SOLID GRANITE SEATS, FLAMED FINISH TO ALL VISIBLE FACES. 900L x 800W ON PLAN COLOUR: MILLENNIUM MAUVE (JOINT WIDTH = 6mm)
	NEW GRANITE CORDUROY TACTILE PAVING UNITS BUSH HAMMERED FINISH 900L x 400W x 65D COLOUR: MILLENNIUM MAUVE (JOINT WIDTH = 6mm)
	STEPS WITH COMBINATION GRANITE CLADDING UNIT. TREAD: 900L x 445W x 50D NOSING: 900L x 55W x 55D RISER: 900L x 115W x 50D MILLENNIUM MAUVE GRANITE TREAD AND RISER WITH SMOKEY BLACK GRANITE NOSING.
	FLAME TEXTURED MILLENNIUM MAUVE SOLID GRANITE SETTS WITH 55 x 55mm SMOKEY BLACK GRANITE NOSING. UPPER STEP: 670L x 400W x 160D LOWER STEP: 670L x 450W x 185D LWR. LANDING: 670L x 450W x 50D (JOINT WIDTH = 6mm)
	FLAME TEXTURED MILLENNIUM MAUVE SOLID GRANITE SETTS WITH 55 x 55mm SMOKEY BLACK GRANITE NOSING. UPPER STEP: 900L x 400W x 160D LOWER STEP: 900L x 450W x 185D (JOINT WIDTH = 6mm)
	EXTRA-LONG FLAME TEXTURED MILLENNIUM MAUVE SOLID GRANITE SETTS WITH 55 x 55mm SMOKEY BLACK GRANITE NOSING. CUT TO LENGTH ON SITE. UPPER STEP: 1200L x 400W x 160D LOWER STEP: 1200L x 450W x 185D (JOINT WIDTH = 6mm)
	SMOKE VENTS IN PAVEMENT REFER TO DAVID MORLEY ARCHITECTS DRAWINGS FOR SIZES, DETAIL, AND SPEC.
	MOVEMENT JOINT LOCATION WITH MASTIC SEALANT, EXPRESSED AT PAVEMENT SURFACE. MASTIC COLOUR: C18-SANITARY GREY TO ENGINEER'S SPECIFICATION.
	RAISED CORTEN STEEL EDGING 6mm THICK x 275 x 450H WITH 30mm WIDE FLAT RETURN ALONG TOP EDGE. NOTE: EDGING TERMINATES ON EITHER SIDE OF FOUNDATION
	FLUSH CORTEN STEEL EDGING 6mm THICK x 275 x 450H WITH 30mm WIDE FLAT RETURN ALONG TOP EDGE. NOTE: EDGING TERMINATES ON EITHER SIDE OF FOUNDATION
	SLOT DRAIN - HIDDEN THROAT STAINLESS STEEL WITH 10mm THROAT OPENING IN PAVING ABOVE THROAT. SLOT DRAIN UNITS TO ENGINEERS SPEC.
	SLOT DRAIN - VISIBLE THROAT STAINLESS STEEL WITH 10mm THROAT OPENING IN PAVING ABOVE THROAT. SLOT DRAIN UNITS TO ENGINEERS SPECIFICATION.
	EDGE OF CONCRETE LEGGE BELOW HARD & SOFT FINISHES
	BROXPAP 'DERBY' BX45 2550 QUAD RECYCLING UNIT 1830L x 535W x 1100H FINISH & COLOUR TBC BY CLIENT
	GRADE 316 STAINLESS STEEL SHEFFIELD CYCLE STAND (TO MATCH EXISTING) Ø50mm, 1000L x 750H
	LAMP COLUMN LOCATION. NOTE: ONLY FOUNDATION INSTALLED UNDER VIADUCT WORKS. LAMP COLUMNS TO BE INSTALLED UNDER COAL DROPS WORKS.
	CORTEN STEEL LIGHTING BOLLARD TYPE, SIZE, FITTING AND FINISH ALL TO HOARE LEA DESIGN AND SPECIFICATION.
	TIMBER VEHICULAR RESTRAINT MOUNTED ON CONCRETE BASE 1400L x 330W x 400H EUROPEAN OAK TBC BY CLIENT
	TIMBER VEHICULAR RESTRAINT MOUNTED ON CONCRETE BASE 1400L x 330W x 400H EUROPEAN OAK TBC BY CLIENT
	TIMBER VEHICULAR RESTRAINT MOUNTED ON CONCRETE BASE 2100L x 330W x 400H EUROPEAN OAK TBC BY CLIENT
	TIMBER BENCH (NO ARMRESTS) MOUNTED ON CONCRETE BASE 1500L x 650W x 400H EUROPEAN OAK TBC BY CLIENT
	TIMBER BENCH (NO ARMRESTS) MOUNTED ON CONCRETE BASE 1800L x 650W x 400H EUROPEAN OAK TBC BY CLIENT
	TIMBER BENCH WITH 2no. STAINLESS STEEL ARM RESTS, MOUNTED ON CONCRETE BASE 2400L x 650W x 400H EUROPEAN OAK TBC BY CLIENT
	TIMBER BENCH WITH 2no. STAINLESS STEEL ARM RESTS, MOUNTED ON CONCRETE BASE 3000L x 650W x 400H EUROPEAN OAK TBC BY CLIENT
	TIMBER BENCH WITH 2no. STAINLESS STEEL ARM RESTS, MOUNTED ON CONCRETE BASE 3000L x 650W x 400H EUROPEAN OAK TBC BY CLIENT
	GRADE 316 STAINLESS STEEL HANDRAIL TO EAST STEPS, ROOT FIXED NOMINAL Ø50mm, 1000L x 900H
	GRADE 316 STAINLESS STEEL HANDRAIL TO WEST STEPS, ROOT FIXED NOMINAL Ø50mm, 1000L x 900H
	GRADE 316 STAINLESS STEEL HANDRAIL TO J.O.G STEPS, ROOT FIXED NOMINAL Ø50mm, 8250L x 900H
	LINE OF BALUSTRADE REFER TO HEATHERWICKS DWGS FOR DETAIL AND SPECIFICATION.
	ACCESS COVERS REFER TO ALD DRAWINGS ALD659_SL211 SL213 INC. AND ALD ACCESS COVER SCHEDULE ALD659_SCH003 FOR DETAILS
	VP210 AUTOMATIC BOLLARD CONTROL CABINET AND ENTRY COLUMN SYSTEM. REFER TO ENGINEERS DETAILS FOR FURTHER INFORMATION.
	VP200 AUTOMATIC BOLLARD BY ATG ACC REFER TO ENGINEERS DETAILS FOR FURTHER INFORMATION.
	HERITAGE BOLLARDS. TLA TO CONFIRM SPECIFICATION.
	HEDGE PLANTING. REFER TO DAN PEARSON ASSOCIATES DRAWINGS FOR DETAIL AND SPEC.
	SHRUB PLANTING REFER TO DAN PEARSON ASSOCIATES DRAWINGS FOR DETAIL AND SPEC.
	MOVEABLE PLANTERS (INDICATIVE) REFER TO DAN PEARSON ASSOCIATES DRAWINGS FOR NUMBER AND DETAIL.
	SOUTHERN VIADUCT WALL BRICK REINFORCEMENT PIER, TO PRICE & MYERS DETAIL AND SPECIFICATION.
	AREA OF INFILL WORKS TO BE COMPLETED UNDER FUTURE BRIDGE WORKS PROGRAM

All dimensions to be verified on site. Figured dimensions to take precedence over those scaled. Any areas indicated on this drawing are for guidance only, no responsibility is taken for their accuracy.

This drawing is the property of Applied Landscape Design Limited. Copyright is reserved by them and the drawing is issued on the condition that it is not copied, reproduced, retained or disclosed to any unauthorized person, either wholly or in part without the written consent in writing of Applied Landscapes.

© 2016 Applied Landscape Design Limited. All rights reserved.

CDM/H&S

NOTES / KEY:
Refer to ALD drawings HL101, HL102, & HL103 for detailed landscape layouts.

REFERENCE DRAWINGS/DOCUMENTS		
REVISIONS		
C02	Northern end of Viaduct brought into scope. Layout updated to reflect changes instructed under CRFs 01, 02, 03, 05, 06, and 08. Drawing re-issued for construction.	15.04.16
C01	Slot drain position along spur road revised; 2no. slot drains along main wall and low wall revised from hidden to exposed. In-abeysance area revised. Drawing issued for construction.	07.12.15
P02	Numerous updates following TLA comments.	18.09.15
P01	First issue for contractors proposals.	25.06.15
Rev.	Update	Date
CLIENT:		
LANDSCAPE ARCHITECT:		
The Threshing Barn Bignell Park Barns Chesterton Oxfordshire OX26 1TD Tel: 01869 248776 Fax: 01869 327513 Email: mail@appliedlandscapes.co.uk		
PROJECT:		
VIADUCT, KXC		
DRAWING TITLE:		
HARD LANDSCAPE GENERAL ARRANGEMENT		
drawn: AB	checked: AnO	
scale: 1:200 @ A1	date: 25.06.15	
status: CONSTRUCTION	xref file ref: ALD659_HLbase	
PROJECT NO. 659/14	DRAWING NUMBER: GA001	REVISION: C02

ORIGINAL A1 SIZE SHEET