



G.06B

S/O 2100mm x 1010mm  
 30 minute fire door  
 Bronze finish  
 NBS: L20/410A  
 Door Type: Based on AB. Proportions have been changed to setting out of G.47A.

Ironmongery:

Quantity	Item Number	Description
3.00 ea	BF8066NCB	Allgood Hardware 100x75x3mm Triple knuckle concealed bearings, button tipped hinges, jig drilled for No 10 woodscrews CE marked to EN 1935 4-7-6-1-1-4-0-13 Certifire approved CF287 for use on 90 minute timber fire doors and 240 minute metal fire doors.
1.00 ea	BF9133S	Allgood Hardware 288x45x32mm concealed overhead door closer with finished track & arm for single action doors adjustable power 2-4, closing force, latch action & backcheck Certifire approved & CE Marked to BS EN1154: 3-8-3/4-1-1-4
1.00 ea	BF7281F60 *	Allgood Hardware 92x60mm backset HL series profile cylinder mortice nightlatch case only Stainless Steel low friction latch & Anti thrust bolts with Unique griptight follower heavy sprung for levers rounded forend & strike Certifire approved CF347 for use on 90 minute timber fire doors and 240 minute metal fire doors.
1.00 ea	BX7419CM *	Cylinder & Modric turn UMK 40 / 40
1.00 ea	BF2301	Allgood Hardware 38x47mm heavy circular floor door stop
2.00 ea	BF8449	Allgood Hardware 76mm circular 'Fire door keep shut' symbol
1.00 ea	XX9133FP	Allgood Hardware intumescent pack for use with 9133S concealed door closers

Remarks:

Stand Alone Access Controlled Lever Set for supply by others. (Optyma)  
 We are running with 72mm centre locks.  
 Door closer retained to maintain integrity of Access Control system on account of room size.

INTUMESCENT PACK  
 REQUIRED TO ALL  
 IRONMONGERY