


Preliminary Basement Wall Design ($F_{cu} = 35 \text{ N/mm}^2$)Earth density = 18 kN/m^3 (Say $\theta = 0^\circ$ $k = 0.42$ Surcharge 20 kN/m^2 Treat wall as free standing cantilever

M.c base of wall (xx)

$$= 18 \times 0.42 \times 2.95^3 \times 1.4/6 + 20 \times 0.42 \times 2.95^2 \times 1.6/2$$

$$= 103.8 \text{ kNm/m}$$

cont'd/

Michael Blacker Partnership

Michael S. Blacker C.Eng. F.I.Struct.E. Andrew Blacker B.Sc.(Hons) C.Eng. M.I.C.E.

CONSULTING STRUCTURAL & CIVIL ENGINEERS

No1 MARK STREET, REIGATE SURREY RH2 0BL

E-MAIL engs@blacker.co.uk

TELEPHONE 01737 244886

FACSIMILE 01737 224556

PROJECT

5 Hermit Place
London NW6 4BZ

DRG TITLE

DRG No.

Job No. 4201

Sht. No. 02A

Date Dec '14

Wall design cont'd

$$d = 250 - 35 - 10 = 205 \text{ mm}$$

$$K = 103.8 / 10^3 \times 0.205^2 \times 35 = 0.07$$

$$A = 103.8 / 0.87 \times 0.5 \times 0.94 \times 0.205 = 1279 \text{ mm}^2/\text{m}$$

Provide H16 @ 150 mm c/s (1340 mm²/m) O.F. (Vert)
+ H10 @ 200 mm c/s - horiz E.F (Horiz)

check for M on inner wall face if wall treated
as propped cantilever:

$$M = 9 \times 20 \times 0.42 \times 2.95^2 \times 1.6 / 128 \\ + 0.0596 \times 18 \times 0.42 \times 2.95^3 \times 1.4 / 2 \\ = 16.3 \text{ kNm/m}$$

$$d_1 = 250 - 25 - 6 = 219 \text{ mm}$$

$$A_1 = 16.3 / 0.87 \times 0.5 \times 0.94 \times 0.219 = 183 \text{ mm}^2/\text{m}$$

Provide H12 @ 200 mm c/s - vert. (566 mm²/m)

Summary:

Vert. reinf: H16 @ 150 mm c/s - Outer Face

H12 @ 200 mm c/s - Inner Face

Horiz reinf: H10 @ 200 mm c/s - Each Face

$$\Delta \text{ top of wall: } 1) \text{ from earth} = \frac{25.6 \text{ WL}^3}{384 \text{ EI}}$$

Michael Blacker Partnership

Michael S. Blacker C.Eng. F.I.Struct.E. Andrew Blacker B.Sc.(Hons) C.Eng. M.I.C.E.

CONSULTING STRUCTURAL & CIVIL ENGINEERS

No1 MARK STREET, REIGATE SURREY RH2 0BL

E-MAIL engs@blacker.co.uk

TELEPHONE 01737 244886

FACSIMILE 01737 224556

PROJECT

5 Hermit Place
London, NW6 4BZ

DRG TITLE

DRG No.

Job No. 4201


Sht. No. 04

Date Feb '15

check approx deflection (max) on inside face of wall
when wall is propped at top and with surcharge = 1.5 kN/m^2

$$\Sigma \text{ earth load on wall} = 32.9 \text{ kN/m (Pg 03)}$$

$$\Sigma \text{ surcharge} = 1.86 \text{ " (")}$$



$$\text{Approx. } \Delta \text{ due to earth} = 0.0047 WL^3/EI$$

$$= 0.0047 \times 32.9 \times 2.95^3 \times 10^9 / 1.83 \times 4.7906 \times 10^{10}$$


$$= 0.045 \text{ cm}$$

$$\text{Approx. } \Delta \text{ due to surcharge} = 0.0054 WL^3/EI$$

$$= 0.0054 \times 1.86 \times 2.95^3 \times 10^9 / 1.83 \times 4.7906 \times 10^{10}$$

$$= 0.003 \text{ cm}$$

$$\therefore \Sigma \text{ Deflection} = 0.048 \text{ cm} \quad \text{negligible}$$



$$\frac{8.5}{3550} \times 30.50 = 7.3$$

Volume per meter of deflected triangle

$$1 \times \frac{0.73 \times 3.55}{2} = 1.3 \text{ m}^3$$

Max potential vertical movement against retaining wall

$$\frac{1.645}{0.13} = 12.65 \text{ mm}$$

Potential vertical movement under edge of footing

$$\frac{12.65 \times 0.345}{1.645} = 2.65 \text{ mm}$$

This is acceptable

BUT cantilever case should never occur as finished "Box" is a propped cantilever

From sheet 04 max deflection with surcharge = 0.48mm which can be ignored

$$\begin{array}{r} 1300 \\ 225 \\ 120 \\ \hline 1645 \end{array}$$