



### Hard Landscape Legend

- Proposed site boundary
- Proposed Willow play structures
- Existing flag paving to be retained. New reinforced grey concrete block flag paving 450x600x63mm to be laid alongside existing paving as required to complete footpath. To be laid butt jointed with concrete base at 150mm staggered bond as supplied by Marshalls
- Proposed Keyblok paving 200x100x60mm, colour Charcoal, laid flexible butt jointed, as supplied by Marshalls, or similar
- Proposed exposed aggregate concrete surface at 100mm depth laid to manufacture specification as supplied by Pepcon ltd
- Proposed Breedon gravel to be laid to supplier specification as supplied by Breedon-special-aggregates.co.uk
- Existing asphalt surface
- Proposed pre-cast bespoke concrete planters, 1.2m high. Free draining into ground to avoid need for additional drainage
- Re-used granite kerbs
- Proposed bench locations, to be FSC 'Inline Seat' in hardwood and steelwith black powder coated finish to metal framework as supplied by Woodscape or similar
- Proposed 1.1m high metal railings as supplied by Jacksons or similar
- Proposed 1.1m high metal gate, coated black as supplied by Jacksons or similar
- Proposed visitor Sheffield cycle stands, galvanised as supplied by Broxap or similar
- External finish levels
- Proposed surface edging to be level laid with a single row of granite conservation aggregate setts in charcoal, to be 100 x 100mm as supplied from Marshalls or similar
- Proposed locations for exterior lighting, to be Kirium Mini as supplied by DW Windsor or similar. To be coordinated with an M & E consultant
- Proposed locations for exterior lighting, to be Aventis eyelid as supplied by DW Windsor or similar. To be coordinated with an M & E consultant

### Soft Landscape Legend

- Existing trees to be retained and protected during construction
- Proposed tree planting within soft landscape. See detail
- Proposed specimen shrub planting
- Proposed *Buxus* (box) hedge planting to be planted in a single row at 300mm centres and maintained at 500mm height
- Proposed native hedge planting to be planted in a double staggered row 300mm apart and at 500mm centres in each row. To be maintained at 1m height
- Proposed mixed planting to receive 75mm bark mulch after planting operations
- Proposed drive to be 38mm Pre-Grown Golpla Grass Paver and 150mmCellweb to be laid to suppliers specification as supplied by geosyn.co.uk
- Proposed grass areas to receive good quality amenity grass turves laid in line with good horticultural practices

C	09.05.16	Amend planter details	JS
B	08.04.16	Client comments	JS
A	22.02.16	Update for VE	JS
Rev	Date	Details	Drawn

Ecology  
Archaeology  
Arboriculture  
Landscape Architecture

ACD at these offices:  
Rodbourne Rail Business Centre, Grange Lane,  
Malmesbury, SN16 0ES  
Tel: 01666 825646

Courtyard House, Mill Lane, Godalming, GU7 1EY  
Tel: 01483 425714

Suite 6, Crescent House, Yonge Close, Eastleigh, SO50 9SX  
Tel: 02382 026 300  
email: mail@acdenv.co.uk  
www.acdenvironmental.co.uk

**Lovell Partnerships Limited**

scheme: Regent's Park Estates  
Rydell Water (Former One Stop)

client: Lovell Partnerships Ltd  
drawing: Hard Landscape Proposals  
date: September 2015  
scale: 1:100@A1  
drawing no: LOV20033-12C  
drawn: JNT    checked: JS

Copyright of ACD Environmental Ltd. All rights described in Chapter IV of the Copyright, Designs and Patents Act 1988 have been generally asserted: 2011. Copyright of this plan remains with ACD until all fees have been paid in full.