

door number	location	structural opening *	width	height	Fire	Leaf Dimension	notes					
BS	DB 01	Pub. Store room	N/A	N/A	N/A	N/A	Retain existing					
	DB 02	Pub. Store room										
	DB 03	Pub. Cellar										
	DB 04	Pub. Cold store										
GF	DG 01	Pub. Cellar/Store room/Boiler	N/A	N/A	N/A	N/A	Retain existing					
	DG 02	Pub. Cellar/Store room/Boiler					Retain existing					
	DG 03	Pub. Entrance					Retain existing					
	DG 04	Pub. Entrance										
	DG 05	Pub. Lounge										
	DG 06	Pub. WC Male Lobby										
	DG 07	Pub. Emergency escape										
	DG 08	Pub. Store room										
	DG 09	Pub. Disabled WC										
	DG 10	Pub. WC Female										
	DG 11	Pub. WC Male										
1F	ED 01	Unit 1. Entrance	900	2100	FD30S	826w x 2040h x 44thk	Painted solid core 4 paneled door + architrave + door stop; fitted with smoke seal; fitted with intumescent seal; fitted with split locks to BS 3621 (can go out without a key but cannot get back in without a key); conform to PAS 24; self closing					
	ED 02	Unit 2. Entrance										
	D1 01	Unit 1. Bedroom						FD20				
	D1 02	Unit 1. Bedroom										
	D1 03	Unit 1. Kitchen/Dining/Living										
	D1 04	Unit 1. Bathroom						FD20	826w x 2040h x 44thk	Traditional 4 panel painted solid core door leaf with painted solid timber lipping + painted solid timber frame + traditional architrave + door stop		
	D1 05	Unit 2. Bathroom										
	D1 06	Unit 2. Bedroom						900	2100	FD20	826w x 2040h x 44thk	Flush painted solid core door leaf with painted solid timber lipping + painted solid timber frame + architrave + door stop
	D1 07	Unit 2. Kitchen/Dining/Living						1000	2100	FD20	926w x 2040h x 45thk	Flush painted timber door with glass panel + painted solid timber frame + architrave + door stop
	D1 08	Unit 2. Hot water tank cupboard						900	2100	FD20	826w x 2040h x 44thk	Traditional 4 panel painted solid core door leaf with painted solid timber lipping + painted solid timber frame + traditional architrave + door stop
D1 09	Pub. Kitchen	900	2100	FD20	826w x 2040h x 44thk	Traditional 4 panel painted solid core door leaf with painted solid timber lipping + painted solid timber frame + traditional architrave + door stop						
D1 10	Pub. Stair Function Room	900	2100	FD30	826w x 2040h x 44thk	Traditional 4 panel painted solid core door leaf with painted solid timber lipping + painted solid timber frame + traditional architrave + door stop						
2F	ED 03	Unit 3. Entrance	900	2100	FD30S	826w x 2040h x 44thk	Painted solid core 4 paneled door + architrave + door stop; fitted with smoke seal; fitted with intumescent seal; fitted with split locks to BS 3621 (can go out without a key but cannot get back in without a key); conform to PAS 24; self closing					
	ED 04	Unit 4. Entrance										
	ED 05	Unit 5. Entrance										
	D2 01	Unit 3. Kitchen/Dining/Living						FD20				
	D2 02	Unit 3. Bedroom										
	D2 03	Unit 3. Bedroom										
	D2 04	Unit 3. Ensuite bathroom						-				
	D2 05	Unit 3. Bathroom										
	D2 06	Unit 4. Bedroom						FD20	826w x 2040h x 44thk	Traditional 4 panel painted solid core door leaf with painted solid timber lipping + painted solid timber frame + traditional architrave + door stop		
	D2 07	Unit 4. Bedroom										
	D2 08	Unit 4. Kitchen/Dining/Living										
	D2 09	Unit 4. Utility Room										
D2 10	Unit 4. Bathroom											
D2 11	Unit 4. Hot water tank cupboard											
D2 12	Unit 4. Hot water tank cupboard	900	2100	FD30	826w x 2040h x 44thk	Painted solid core 4 paneled door + frame + architrave + door stop; fitted with smoke and intum. seal						
3F	D3 01	Unit 5. Kitchen/Dining/Living	900	2100	FD20	826w x 2040h x 44thk	Traditional 4 panel painted solid core door leaf with painted solid timber lipping + painted solid timber frame + traditional architrave + door stop					
	D3 02	Unit 5. Bedroom										
	D3 03	Unit 5. Bedroom										
	D3 04	Unit 5. Bedroom										
	D3 05	Unit 5. Bedroom										
	D3 06	Unit 5. Ensuite bathroom										
	D3 07	Unit 5. Hot water tank cupboard										

* All dimensions must be checked on site.

** Min 300mm clear distance from leading edge of the door leaf at the pull side

*** Fire rating dependent on fire stopping at floor slabs within risers; either FD30 riser doors with fire stop at floor or FD60 riser doors without fire stop at floor

General notes:

1 Read in conjunction with WD370 /371 /372

2 All ironmongery to be satin stainless steel finish

3 All door handles to be fitted at height between 900mm to 1100mm above finished floor level + minimum 45mm projection from face of door

4 Fire signages to Building Control Approval

Revision	Date	Reason	Initial
/	07.06.16	DETAIL DESIGN	GM

mark fairhurst ARCHITECTS
48A Union Street, London, SE1 1TD T 0207 407 7070 E info@mark-fairhurst.co.uk

PROJECT: Cock Tavern, 23 Phoenix Road, London NW1 1HB

DRAWING TITLE: Internal Door Schedule

SCALE: NTS DATE: 07.06.16

PROJECT NO. 1250 DRAWING NO. WD 350

STATUS: PRELIMINARY

BY: JU

REV: /