

## **Sustainability and Energy Statement**

**9, Goodge Street, London W1T 2PE**

Prepared by Ivan Ball

Bluesky Unlimited  
39 Marsh Baldon  
Oxfordshire  
OX44 9LP

[www.blueskyunlimited.co.uk](http://www.blueskyunlimited.co.uk)

**23<sup>rd</sup> June 2016**



**Table of Contents**

|  |           |
|--|-----------|
| <b>Executive Summary</b>   | <b>3</b>  |
| <b>1.0 Introduction</b>  | <b>4</b>  |
| <b>2.0 Planning policies</b>                                       | <b>5</b>  |
| <b>3.0 Assessment methodology</b>                                  | <b>9</b>  |
| <b>4.0 Proposal</b>  | <b>9</b>  |
| <b>5.0 Energy Efficiency</b>                                       | <b>10</b> |
| <b>5.1 Demand Reduction (Be Lean and Be Clean)</b>                 | <b>10</b> |
| • Passive design measures  |           |
| • Active design measures   |           |
| <b>5.2 Establishing Energy Demand and Carbon Dioxide Emissions</b> | <b>13</b> |
| • SAP calculations   |           |
| <b>5.3 Renewable Technologies (Be Green)</b>                       | <b>15</b> |
| <b>5.4 Summary of Calculations</b>                                 | <b>19</b> |
| <b>6.0 Climate Change Adaption and Water Resources</b>             | <b>20</b> |
| • Water efficiency measures  |           |
| <b>7.0 Materials and Waste</b>                                     | <b>22</b> |
| <b>8.0 Construction Process and Site Management</b>                | <b>24</b> |

## Executive Summary

This Sustainability and Energy Statement considers the sustainability and energy issues relating to the development at 9, Goodge Street, London W1T 2PE.

The site currently accommodates a 4-storey building with retail use at ground floor and three residential apartments on the upper floors. The proposal is to demolish the upper floors and erect four new stories comprising three new apartments, whilst retaining the ground floor and basement as a betting shop. The front wall will be retained.

The Statement contains an energy demand assessment showing how selected energy efficiency measures have been incorporated into the development design and considers those renewable technologies, which may be appropriate.

SAP calculations have been prepared for a sample of the new apartments using the planning drawings and an agreed construction specification and these have been used to test a number of design scenarios to ensure the apartments meet the emissions reductions target required by the planning policy.

It is proposed to install 3, 327W photovoltaic panels onto the flat roof of the upper apartment. These will be gently inclined on rear of the flat roof and will not be visible from ground level.

|  | Total                    | % Reduction   |
|--|--------------------------|---------------|
|  | kg CO <sub>2</sub> /year |               |
| Total TER emissions to the new apartments        | <b>2,619</b>             | -             |
| Total DER emissions after energy efficiency      | <b>2,509</b>             | <b>4.20%</b>  |
| Emissions after energy efficiency and renewables | <b>2,032</b>             | <b>22.41%</b> |

The Code for Sustainable Homes has been withdrawn by the Government and whilst the new apartments will achieve the energy, emissions and water reductions targets previously required by Code Level 4 it is not proposed that the apartments will achieve FULL Code Certification.

## 1.0 Introduction

Bluesky Unlimited has been commissioned by Hammersmith Estates to prepare a Sustainability and Energy Statement in support of the partially demolition and erection of a four-storey extension to 9, Goodge Street, London W1T 2PE. The Statement demonstrates how the works meet the requirements of national, regional and local planning policy and guidance in relation to sustainability and provides evidence to confirm compliance or where the works exceed the required standards.

The building has been designed and will be constructed to reduce energy demand and carbon dioxide emissions. The objective is to reduce the energy demand to an economic minimum by making investment in the parts of the building that have the greatest impact on energy demand and are the most difficult and costly to change in the future, namely the building fabric. Once a cost effective structure has been designed, renewable technologies will be considered for installation to provide heat and/or electricity.

The following hierarchy will be followed:

- Lean                      reduce demand and consumption
- Clean                     increase energy efficiency
- Green                    provide low carbon renewable energy sources

The report has been prepared by Ivan Ball of Bluesky Unlimited who are sustainability consultants.

### Study Area

The site currently contains a 4-storey building and provides accommodation for a betting shop on ground and basement floors with three apartments on the upper floors.

The site is located within the Goodge Street Neighbourhood Centre and the Charlotte Street Conservation Area.

Whilst the building is not listed there are listed buildings within the proximity of the site.

## 2.0 Planning Policy Context

### National Policy

The UK Government published its sustainable development strategy in 1999 entitled “A better quality of life: A strategy for sustainable development in the UK”. This sets out four main objectives for sustainable development in the UK:

- Social progress that recognises the needs of everyone.
- Effective protection of the environment.
- Prudent use of natural resources.
- Maintenance of high stable levels of economic growth and employment.

Sustainable Communities: Building for the Future, known colloquially as the Communities Plan was published in 2003. The Plan sets out a long-term programme of action for delivering sustainable communities in both urban and rural areas. It aims to tackle housing supply issues in parts of the country, low demand in other parts and the quality of our public spaces. The Communities Plan describes sustainable communities as: Active, inclusive and safe, well run, environmentally sensitive, well designed and built, well connected, thriving, well served and fair for everyone.

The most relevant national planning policy guidance on sustainability is set out in:

- National Planning Policy Framework - 2012

NPPF Core Planning Principle 17 states;

*“support the transition to a low carbon future in a changing climate, taking full account of flood risk and coastal change, and encourage the reuse of existing resources, and encourage the use of renewable resources (for example, by the development of renewable energy)”*

---

## **Regional and Local Policies**

### **London Plan, adopted July 2015**

Within this Statement the following Policies have been addressed:

#### **Policy 5.2 – Minimising carbon dioxide emissions**

A) *Development proposals should make the fullest contribution to minimising carbon dioxide emissions in accordance with the following energy hierarchy:*

- 1 *Be lean: use less energy*
- 2 *Be clean: supply energy efficiently*
- 3 *Be green: use renewable energy*

D) *As a minimum, energy assessments should include the following details:*

- a *calculation of the energy demand and carbon dioxide emissions covered by the Building Regulations and, separately, the energy demand and carbon dioxide emissions from any other part of the development, including plant or equipment, that are not covered by the Building Regulations (see paragraph 5.22) at each stage of the energy hierarchy*
- b *proposals to reduce carbon dioxide emissions through the energy efficient design of the site, buildings and services*
- d *proposals to further reduce carbon dioxide emissions through the use of on-site renewable energy technologies.*

#### **Policy 5.3 - Sustainable design and construction**

B) *Development proposals should demonstrate that sustainable design standards are integral to the proposal, including its construction and operation, and ensure that they are considered at the beginning of the design process.*

## **London Borough of Camden**

The Camden Core Strategy 2010-2015 adopted in 2011 and the Camden Development Policies document (adopted 2010) provide the policy framework.

The following policies are specifically relevant to this topic area and have been edited for clarity and relevance.

### **CS13 – Tackling climate change through promoting higher environmental standards**

#### *Reducing the effects of and adapting to climate change*

*The Council will require all development to take measures to minimise the effects of, and adapt to, climate change and encourage all development to meet the highest feasible environmental standards that are financially viable during construction and occupation by:*

- a) *ensuring patterns of land use that minimise the need to travel by car and help support local energy networks;*
- b) *promoting the efficient use of land and buildings;*
- c) *minimising carbon emissions from the redevelopment, construction and occupation of buildings by implementing, in order, all of the elements of the following energy hierarchy:*
  1. *ensuring developments use less energy,*
  3. *generating renewable energy on-site; and*
- d) *ensuring buildings and spaces are designed to cope with, and minimise the effects of, climate change.*

*The Council will have regard to the cost of installing measures to tackle climate change as well as the cumulative future costs of delaying reductions in carbon dioxide emissions*

### **Development Policies DP22 – Promoting sustainable design and construction**

*The Council will require development to incorporate sustainable design and construction measures.*

*Schemes must:*

- a) *demonstrate how sustainable development principles, including the relevant measures set out in paragraph 22.5 below (this states that the Council will have regard to costs and feasibility), have been incorporated into the design and proposed implementation; and*
- b) *incorporate green or brown roofs and green walls wherever suitable.*

*The Council will promote and measure sustainable design and construction by:*

- c) expecting new build housing to meet Code for Sustainable Homes Level 3 by 2010 and Code Level 4 by 2013 and encouraging Code Level 6 (zero carbon) by 2016.\**

*The Council will require development to be resilient to climate change by ensuring schemes include appropriate climate change adaptation measures, such as:*

- f) summer shading and planting;*
- g) limiting run-off;*
- h) reducing water consumption;*
- i) reducing air pollution; and*
- j) not locating vulnerable uses in basements in flood-prone areas.*

\* The Ministerial Statement made by the Government on 27<sup>th</sup> March 2015 announced the withdrawal of the Code for Sustainable Homes and has stated that Local Authorities should not impose specific Code requirements on new applications with immediate effect.

In addition the Government has set a maximum carbon dioxide emissions reduction target to the equivalent of Code Level 4, i.e. 19% of Building Regulations maximum (Part L – 2013).

Therefore whilst many of the commitments and initiatives contained within this Statement may form part of a Code Assessment it is not proposed to provide FULL Code Certification to the new apartments.

This Statement assumes the homes will need to reduce carbon dioxide emissions by 19%, which was the standard required by the now revoked Code Level 4.



### 3.0 Assessment Methodology

The energy demand and carbon emissions from the apartments have been established using agreed building specifications and detailed planning drawings. A calculation based upon the SAP methodology has been used to allow different construction strategies to be tested.

#### Emission Factors

The CO<sub>2</sub> emission factors, where applicable, used throughout this report have been taken from the Building Regulation Approved Document L.

| Fuel                      | Kg CO <sub>2</sub> /kWh |
|---------------------------|-------------------------|
| Natural Gas               | 0.216                   |
| Grid supplied electricity | 0.519                   |
| Displaced electricity     | 0.519                   |

### 4.0 Proposal

The proposal is for the demolition of the upper floors and the erection of four new stories comprising three new apartments.

The floor area of the new apartments is as follows;

| Unit Type   | No.      | Area           | Total Area     |
|---|----------|----------------|----------------|
|   |          | m <sup>2</sup> | m <sup>2</sup> |
| 1-Bedroom apartment (first and second floors)     | 2        | 38.0           | 76.0           |
| 2-Bedroom maisonette apartment (third and fourth) | 1        | 86.2           | 86.2           |
| <b>Total</b>                                      | <b>3</b> |                | <b>162.2</b>   |

## **5.0 Energy Efficiency**

### **5.1 Demand Reduction (Be Lean and Be Clean)**

#### **Design**

The energy performance of a building is affected by its design, construction and use and whilst occupant behaviour is beyond the remit of this statement, better design and construction methods can significantly reduce the life cycle emissions of a building and assist the occupant to reduce consumption.

It is possible to exceed Building Regulations requirements (Part L) through demand reduction measures alone, which typically include a combination of passive design measures (e.g. building design and efficient building fabric) and active design measures (e.g. variable speed motors).

#### **Passive Design Measures**

The passive design measures proposed include;

##### **Passive Solar Gain and Daylighting**

The proposal is for the demolition of the upper floors and the reconstruction to provide three new apartments. The orientation of the openings on the elevations is constrained within the context of the arrangement of the existing building. However, Living Rooms and Bedrooms are all provided with large window openings and therefore have good standards of natural daylighting.

The front of the existing building is orientated towards the north-west and the rear towards the south-east. All apartments therefore have access to direct sunlight at some point throughout the day.

##### **Natural Ventilation**

The apartments will have opening windows to allow for natural ventilation. Mechanical extract ventilation will be provided to appropriate rooms.

## Efficient Building Fabric

### Building Envelope

U-values of the building envelope must meet Building Regulations Part L standards; further improvements to U-values will reduce the development heating requirements, favourably impacting in reducing energy demand.

The building is constructed in traditional materials with high thermal mass. The construction of the new elements will largely follow the existing aesthetic but will introduce modern insulation to the external walls and roof. The external walls will be built with 300mm cavity wall construction with fully filled cavities. Where the front wall is being retained this will be dry lined and provide with PIR insulation.

The following table sets out the elemental U-values targeted for the construction:

| Element             | Part L Limiting U-values | Proposed U-values  |
|---------------------|--------------------------|--------------------|
|                     | W/m <sup>2</sup> K       | W/m <sup>2</sup> K |
| External Walls      | <b>0.30</b>              | <b>0.17</b>        |
| Retained front wall | -                        | <b>0.26</b>        |
| Flat Roof           | <b>0.20</b>              | <b>0.12</b>        |
| Dormer cheeks       | <b>0.20</b>              | <b>0.12</b>        |
| Windows             | <b>2.00</b>              | <b>1.50</b>        |

### Air Leakage

Large amounts of heat are lost in winter through air leakage from a building (also referred to as infiltration or air permeability) often through poor sealing of joints and openings in the building

The Building Regulations set a minimum standard for air permeability of 10 m<sup>3</sup> of air per hour per m<sup>2</sup> of envelope area, at 50Pa for new construction. It is assumed this standard can be improved upon and for the purposes of this assessment an air tightness of 4 m<sup>3</sup> per hour per m<sup>2</sup> is targeted for the new apartments.

---

## **Ventilation**

As a result of increasing thermal efficiency and air tightness, Building Regulations Approved Document F18 was also revised in 2006 to address the possibility of overheating and poor air quality. Mechanical ventilation will be used in appropriate rooms to control air quality although maximum use will be made of natural ventilation for summer night-time cooling.

**Active Design Measures** will include;

## **Efficient Lighting and Controls**

Throughout the scheme natural lighting will be optimised.

Approved Document L requires three in four light fittings (75%) to be dedicated low energy fittings. The development will exceed this and all light fittings will be of a dedicated energy efficient type.

Any common area lighting will be fitted with time controls and light sensors to ensure illumination is restricted to required times.

## 5.2 Establishing Carbon Dioxide Emissions

### SAP Calculations

Detailed working drawing design has not yet been carried out and the sample SAP calculations have been prepared based upon the detailed planning drawings and an assumed specification.

Whilst the Code for Sustainable Homes has been withdrawn the policy requires new development to achieve the energy efficiency standard equivalent to Code Level 4, i.e. a 19% reduction in emissions compared to Building Regulations.

A SAP calculation has been prepared for one of the 1-bedroom mid-floor apartments and for the 2-bedroom top-floor maisonette.

The following tables summarises the results from the SAP calculations:

| 1-Bed Apartment (second-floor)<br>38.0 m <sup>2</sup> | CO <sub>2</sub><br>TER | CO <sub>2</sub><br>DER |
|---|------------------------|------------------------|
|   | kg/m <sup>2</sup> /yr  | kg/m <sup>2</sup> /yr  |
| Space heating   | 3.97                   | 2.87                   |
| Water heating   | 9.92                   | 9.47                   |
| Electricity for pumps and fans                        | 1.03                   | 2.25                   |
| Electricity for lighting                              | 2.74                   | 2.74                   |
| <b>Total</b>  | <b>17.66</b>           | <b>17.33</b>           |

| 2-Bed Maisonette Apartment (third and fourth-floor)<br>86.2 m <sup>2</sup> | CO <sub>2</sub><br>TER | CO <sub>2</sub><br>DER |
|--|------------------------|------------------------|
|  | kg/m <sup>2</sup> /yr  | kg/m <sup>2</sup> /yr  |
| Space heating  | 5.94                   | 4.97                   |
| Water heating  | 6.16                   | 5.62                   |
| Electricity for pumps and fans   | 0.46                   | 0.99                   |
| Electricity for lighting   | 2.25                   | 2.25                   |
| <b>Total</b>   | <b>14.81</b>           | <b>13.83</b>           |

### Total Carbon Dioxide Emissions

Using the above information the total emissions from the three apartments following the energy efficiency measures detailed can be calculated as follows:

| Unit Type                                | Area           | TER CO <sub>2</sub>    | DER CO <sub>2</sub>    |
|--|----------------|------------------------|------------------------|
|  | m <sup>2</sup> | kg CO <sub>2</sub> /yr | kg CO <sub>2</sub> /yr |
| 1-bed apartment (first and second-floor) | 76.0           | 1,342                  | 1,317                  |
| 2-bed maisonette apartment               | 86.2           | 1,277                  | 1,192                  |
| <b>Totals</b>                            | <b>162.2</b>   | <b>2,619</b>           | <b>2,509</b>           |

The total site emissions from the apartments based on the TER are assessed as:

- **2,619 kg CO<sub>2</sub> per year**

The total site emissions from the apartments based on the DER are assessed as:

- **2,509 kg CO<sub>2</sub> per year**

The reduction in site CO<sub>2</sub> emissions as a result of the energy efficiency measures is assessed as;

- **110 kg CO<sub>2</sub> per year, which equates to a reduction of 4.20%**

### 5.3 Renewable Technologies (Be Green)

The energy demand established above has been used to test the viability of various renewable and low carbon technologies as follows.

This section determines the appropriateness of each renewable technology and considers the ability of each technology to comply with the planning requirements as set out above in Section 2.0.

The Government's Renewable Obligation defines renewable energy in the UK. The identified technologies are;

- Small hydro-electric
- Landfill and sewage gas
- Onshore and offshore wind
- Biomass
- Tidal and wave power
- Geothermal power
- Solar

The use of landfill or sewage gas, offshore wind or any form of hydroelectric power is not suitable for the site due to its location.

The remaining technologies are considered below;

#### **Wind**

Wind turbines are available in various sizes from large rotors able to supply whole communities to small roof or wall-mounted units for individual dwellings.

The Government wind speed database predicts local wind speeds at Goodge Street to be 4.9 m/s at 10m above ground level and 5.6 m/s at 25m above ground level. This is below the level generally required for commercial investment in large wind turbines and in addition the land take, potential for noise and signal interference make a large wind turbine unsuitable for this development.

### **Combined Heat and Power and Community Heating**

Combined heat and power (CHP) also called co-generation is a de-centralised method of producing electricity from a fuel and 'capturing' the heat generated for use in buildings. The plant is essentially a small-scale electrical power station. The production and transportation of electricity via the National Grid is very inefficient with over 65% of the energy produced at the power station being lost to the atmosphere and through transportation.

Consequently CHP can demonstrate significant CO<sub>2</sub> savings and although not necessarily classed as renewable energy (depending on the fuel used) the technology is low carbon.

For a CHP plant to be economic it needs to operate for as much of the time as possible (usually deemed to be in excess of 14 hours per day) and therefore the size of the units are usually based upon the hot water load of the buildings with additional boilers meeting the peak space heating demand.

A development of three apartments provides insufficient heat demand to efficiently run a communal heating system or CHP and therefore these systems are not proposed.

### **Ground Source Heat Pumps**

Sub soil temperatures are reasonably constant and predictable in the UK, providing a store of the sun's energy throughout the year. Below London the groundwater in the lower London aquifer is at a fairly constant temperature of 12° C.

Ground source heat pumps (GSHP) extract this low-grade heat and convert it to usable heat for space heating.

GSHP operates on a similar principle to refrigerators, transferring heat from a cool place to a warmer place. They operate most efficiently when providing space heating at a low temperature, typically via under floor heating or with low temperature radiators.

The pumps require electricity for their operation and the resultant reduction in CO<sub>2</sub> is not as significant as with other renewables.

There are generally two types of installation being a bore-hole (open loop) and a closed loop system. Open loop bore holes extract energy from ground water located deep below the surface and discharge the water back to the ground reservoir whereas closed loop systems circulate a fluid around a series of boreholes or horizontal 'slinky' and extract heat from the ground.



There is insufficient ground area to accommodate a horizontal 'slinky' or compact collector system for each of the apartments and a bore-hole system would need to be installed through the ground floor accommodation.

This is impractical and therefore this technology is not proposed.

## **Solar**

### **(i) Solar Water Heating**

Solar hot water panels use the sun's energy to directly heat water circulating through panels or pipes. The technology is simple and easily understood by purchasers.

Solar hot water heating panels are based generally around two types, which are available being 'flat plate collectors' and 'evacuated tubes'.

Flat plate collectors can achieve an output of up to 1,124 kWh/annum\* and evacuated tubes can achieve outputs up to 1,365 kWh/annum \*\*

Panels are traditionally roof mounted and for highest efficiencies should be mounted plus or minus 30 degrees of due south. Evacuated tubes can be laid horizontally on flat roofs but flat plate collectors need to be installed at an incline of circa 30 degrees.

Solar hot water panels are considered an appropriate technology and the flat roof over the upper apartment allows an evacuated tube panel to be installed to each apartment.

Solar hot water panels could be used but their use would require a change in the boiler type from a gas combination boiler, which has been used for the SAP modelling to a conventional boiler with a hot water cylinder. This will impact on space planning within the apartments.

### **(ii) Photovoltaics**

Photovoltaic panels (PV) provide clean silent electricity. They generate electricity during most daylight conditions although they are most efficient when exposed to direct sunlight or are orientated to face plus or minus 30 degrees of due south.

PV panels can be integrated into many different aspects of a development including roofs, walls, shading devices or architectural panels.

The planning policy requires emissions to be reduced by 19% compared to Building Regulations (Part L – 2013). The energy efficiency measures incorporated into the development reduce emissions by 110 kg CO<sub>2</sub> per year. Therefore a balance of 388 kg CO<sub>2</sub> per year needs to be achieved by other means.

This could be accommodated by an installation of 3 x 327W photovoltaic panels, which would reduce emissions by 477 kg CO<sub>2</sub> per year. When combined with the energy efficiency measures incorporated into the scheme a total reduction of **587 kg CO<sub>2</sub> per year** could be achieved, which equates to a reduction of **22.41%**.

The panels could be installed on the rear section of the gently inclined flat roof of the building.

They could be installed flush with the roof and being on the rear elevation they would not detrimentally impact on the aesthetic of the development.

### **Air Source Heat Pumps (ASHP)**

Air sourced heat pumps operate using the same reverse refrigeration cycle as ground source heat pumps, however the initial heat energy is extracted from the external air rather than the ground. These heat pumps can be reversed to provide cooling to an area although this reduces the coefficient of performance of the pumps.

ASHP tend to have a lower coefficient of performance (CoP) than GSHP and with the emissions factor for electricity being 2.61 times that of gas (emissions factor is the weight of CO<sub>2</sub> emitted per kWh) installations with CoPs of less than this figure show little real saving in CO<sub>2</sub> emissions.

The efficiency of ASHPs can be significantly reduced where there is a high hot water demand compared to the total demand. They are therefore not appropriate for the apartments.

### **Other Technologies**

New technologies are becoming available, which do not 'fit' into one of the above categories but which need to be considered. One such system is flue gas heat recovery units. These devices are used in conjunction with gas-fired boilers and recover the heat exhausted through the boiler flue.

#### 5.4 Summary of Calculations and Proposals for Low-carbon and Renewable Technologies

The maximum permissible CO<sub>2</sub> emissions (TER) as a result of Part L of the Building Regulations are calculated as **2,619 kg CO<sub>2</sub> per year**, with actual DER emissions calculated as **2,509 kg CO<sub>2</sub> per year**.

The local planning policy requires a reduction in emissions (DER) of at least 19%, which is the reduction required by the now revoked Code for Sustainable Homes Level 4.

Various technologies are considered above and whilst wind turbines, combined heat and power, ground source or air source heat pumps are not considered appropriate the use of solar hot water heating or photovoltaic panels are considered feasible and appropriate. However, the use of solar hot water panels would require a change to a conventional heating system with hot water cylinders. This would detrimentally impact on space planning within the apartments and therefore the use of photovoltaic panels is preferred.

##### **Be Lean**

The construction standards proposed include U-values, which demonstrate good practice and improve upon those required by the Building Regulations. Air tightness standards are targeted at a 60% improvement upon the minimum required by the Building Regulations.

The emissions are reduced from the maximum by **110 kg CO<sub>2</sub> per year**, which equates to a reduction of **4.20%**.

##### **Be Green**

It is proposed to install 3 x 327W photovoltaic panels on the south-east orientated, rear roof of the building. Whilst being constructed as flat roof, the roof is actually laid to a gentle slope and therefore the panels can be laid flush with the roof surface. They will therefore not be detrimental to the appearance of the development. The panels will reduce emissions by **477 kg CO<sub>2</sub> per year**.

**When combined with the energy efficiency measures incorporated into the scheme the total reduction in emissions is 587 kg CO<sub>2</sub> per year, which equates to a reduction of 22.41%.**

## 6.0 Climate change adaption and Water resources

### **Sustainable Drainage Systems (SUDS)**

The Environment Agency Flood Maps show the site is located within Flood Zone 1.

The surface water system will not be altered from the existing disposal system.

### **Surface Water Management**

Consideration has been given to the use of grey water recycling. However, this will require tanks to be install into the apartments. This will lead to excessive costs and when coupled with customer's resistance to the appearance of the recycled water does not currently make them a viable option. They have therefore not been included in the proposals.

### **Water efficiency measures**

In excess of 20% of the UK's water is used domestically with over 50% of this used for flushing WCs and washing (source: Environment Agency). The majority of this comes from drinking quality standard or potable water.

The water efficiency measures included in this development will ensure that the water use target of 105 litres per person per day is achieved using the measures described below.

Water efficient devices will be fully evaluated, and installed, wherever possible. The specification of such devices will be considered at detailed design stage and each will be subject to an evaluation based on technical performance, cost and market appeal, together with compliance with the water use regulations.

The following devices will be incorporated within each apartment:

- Water efficient taps.
- Water efficient toilets.
- Low output showers.
- Flow restrictors to manage water pressures to achieve optimum levels.
- Water meters to all premises with guidance on water consumption and savings.

Water consumption calculations have been carried out using the Water Efficiency Calculator provided by the BRE. Although not perfect this calculator gives a good indication of the probable water use in the dwelling, although this is largely dependent on the way on which occupants use their homes.

Below is a typical specification, which would achieve the 105 Litres per person per year target.

| Schedule of Appliance Water Consumption |                         |              |
|---|-------------------------|--------------|
| Appliance                               | Flow rate or capacity   | Total Litres |
| WC                                      | 4/2.6 litres dual flush | 14.72        |
| Basin                                   | 1.7 litres/min.         | 5.98         |
| Shower                                  | 8 litres/min            | 24.00        |
| Bath                                    | 160 litres              | 25.60        |
| Sink                                    | 4 litres/min            | 14.13        |
| Washing Machine                         | Default used            | 16.66        |
| Dishwasher                              | Default used            | 3.90         |
|   |                         | 104.99       |

## **7.0 Materials and Waste**

The BRE Green Guide to Specification is a simple guide for design professionals. The guide provides environmental impact, cost and replacement interval information for a wide range of commonly used building specifications over a notional 60-year building life. The proposal involves the extension and refurbishment of an existing building. For new materials the construction specification will prioritise materials within ratings A+, A or B.

Preference will be given to the use of local materials & suppliers where viable to reduce the transport distances and to support the local economy. A full evaluation of these suppliers will be undertaken at the next stage of design.

In addition, timber would be sourced, where practical, certified by PEFC or an equivalent approved certification body and all site timber used within the construction process would be recycled.

All insulation materials will have a zero ozone depleting potential

### **Construction waste**

A Site Waste Management Plan will be prepared which will monitor and report on waste generated on site into defined waste groups in compliance with the SWMP regulations 2008.

The Plan will indicate the setting of targets to promote resource efficiency in accordance with guidance from WRAP, Envirowise, BRE and DEFRA.

The overarching principle of waste management is that waste should be treated or disposed of within the region where it is produced.

Construction operations generate waste materials as a result of general handling losses and surpluses. These wastes can be reduced through appropriate selection of the construction method, good site management practices and spotting opportunities to avoid creating unnecessary waste.

The Construction Strategy will explore these issues, some of which are set out below:

- Proper handling and storage of all materials to avoid damage.
- Efficient purchasing arrangements to minimise over ordering.
- Segregation of construction waste to maximise potential for reuse/recycling.
- Suppliers who collect and reuse/recycle packaging materials

Construction waste is a key element to be considered in achieving a reduction in all waste – it is estimated that some 40% of all waste is construction related.

### **Domestic Waste and Recycling**

Domestic waste has been considered in the proposed development in the following way:

- External space is provided for storing recyclable materials, for collection by the Authority, within the boundary of the site.
- The external space for recyclable material is of sufficient size to accord with Local Authority procedures.
- Internal storage for recyclables is provided at a capacity in excess of 30 litres.
- The Home Owners Guide will be provided to residents giving information about the location of the nearest recycling bank.

## **8.0 Construction Process and Site Management**

Where best practice guidance is available dealing with construction methods and standards these will be adopted.

### **Considerate Constructors**

The site will be registered with the Considerate Constructors Scheme, which addresses both limiting the effect on the community and the effects on the environment. The applicant is committed to demonstrate best site management practices, and if practical to go beyond this. The CC scheme monitors the contractor's performance against the eight point Code for Considerate Practice.

### **Construction Site Impacts**

To ensure good relations with the local community, the developers will ensure that they keep local people informed of works, which might affect them, and provide a method for comments, complaints and required remedial action to be communicated to the developer.

Site management procedures will be put in place to monitor water consumption and CO<sub>2</sub> emissions arising from site activities.