

GROUND FLOOR LEVEL ATTENUATION TANK. CREATED OR SIMILAR. TO ACCEPT UP TO 16.5M³

- PERKINS+WILL
KEY PLAN
- 1 BED
 - 2 BED
 - 3 BED
 - AMENITY
 - CIRCULATION
 - Exterior
 - HORIZONTAL CIRCULATION
 - OFFICE/COMMERCIAL
 - PARKING
 - RESIDENTIAL
 - RETAIL
 - SERVICE
 - SERVICE & SUPPORT
 - Studio
 - VERTICAL CIRCULATION

DRAFT
ISSUE CHART

D	WEEKLY ISSUE 4	21/04/17
C	WEEKLY ISSUE 3	21/04/17
B	WEEKLY ISSUE 2	21/04/17
A	WEEKLY ISSUE 1	21/04/17
CD		

150 HOLBORN
150 Holborn, London, United Kingdom
DAR AL-HANDASAH

Job Number	33524
Drawn	Author
Checked	Checker
Approved	Approver

TITLE
Ground Floor
SHEET NUMBER
A04-00
Copyright © 2016 Perkins+WILL

NOTE!
GROUND FLOOR ATTENUATION TANK TO BE MADE UP OF 500mm OR 1000mm DEEP "STORMCELL" CRATES BY POLYPIPE. WRAPPED IN FLEECE & MEMBRANE.
MAINTENANCE TO BE AGREED WITH MANUFACTURER. HOWEVER IT IS IMPORTANT TO PROVIDE SUITABLE SILT TRAPS TO PREVENT THE STORAGE VOLUME FROM BE REDUCED.
SUITABLE FLOW CONTROLS ARE TO BE PROVIDED ON THE OUTLET OF THE TANK BEFORE CONNECTING TO THE SITE'S DRAINAGE SYSTEMS.

150 HOLBORN.
GRD. FLOOR
ATTENUATION
VOLUMES.

cnm Clarke Nicholls Marcel
CIVIL & STRUCTURAL ENGINEERS

1036010-SK-D.105.