

PROPOSALS

It is proposed to construct a new three and two storey rear extension containing a basement set slightly higher than the existing 4 storey mid terrace's basement. Allowing for a new basement floor slab, insulation and screed finish the excavated depth will therefore be similar to the existing building, thus avoiding the need for underpinning.

The new extension is to be set across the full width of the site and will be about similar rear extensions to the period properties on either side.

The works will also incorporate a sunken terrace across the rear of the two storey extension, all as shown on the cross section shown over.

Subject to trial pit information the adjoining rear extensions may need underpinning. Initially if underpinning is required, there will be a small increase in load where the London clay will be replaced with



34b York Way
King's Cross
London N1 9AB
T: 020 7833 0666

Consulting Civil and
Structural Engineers
Project Managers

E: info@roseassoc.co.uk

Studio 10
Dimsdale House
80a Fore Street Hertford
Hertfordshire SG14 1BY
T: 01992 210145

PROJECT: 69 KENTISH TOWN ROAD

LONDON

NW1 8NY

Section: HEAVE ASSESSMENT

Job No: 16063

Calculations: DR

Date: AUGUST 2015


Page No: 02

concrete. This increase in load will induce downward settlement over the long term. The second phase will be to bulk excavate for the proposed basement. The removal of the London clay to depth will trigger long term upward movement, termed elastic heave.

These two effects will be considered and their cumulative effect gauged against the guidelines laid down by Burland. Movement should not be greater than category slight, i.e., less than 5mm.

PROJECT:	69 KENTISH TOWN ROAD	
	LONDON	
	NW1 8NY	
Section:	HEAVE ASSESSMENT	
Job No:	16063	
Calculations:	DR	
Date:	AUGUST 2015	Page No: 03

CROSS SECTION SHOWING PROPOSED WORKS



PROJECT:	69 KENTISH TOWN ROAD	
	LONDON	
	NW1 8NY	
Section:	HEAVE ASSESSMENT	
Job No:	16063	
Calculations:	DR	
Date:	AUGUST 2015	Page No: 04

PALDMETERS

Bulk density of London clay $\gamma_c = 1900 \text{ kg/m}^3$

Bulk density of mass concrete $\gamma = 2400 \text{ kg/m}^3$

Nett increase in load when replacing London clay with mass concrete, $2400 - 1900 = 500 \text{ kg/m}^3$
OR 4.9 kN/m^2

PHASE I.

Worst case if adjacent properties underpinned
Extra over load to be carried by London clay

$4.9 \times 0.6 \text{ width} \times 2.5 = 7.4 \text{ kN/m}$ which is very low.

short term consolidation, ie undrained or immediate settlement

Depth to sands and gravels from BGS borehole ref. TQ285E5 c 52m

Refer to figure 3:6 over. with pins 600 wide

$$H/B = 52 / 0.6 = 87.$$

$$\mu_0 = 0.76.$$

$$D/B = 2500 / 600 = 4.2.$$

$$\mu_1 = 2.1.$$

$$L/B = 12500 / 600 = 21.$$

Foundation pressure $q = 4.9 / 0.6 = 8.2 \text{ kN/m}^2$
(additional)

PROJECT:	69 KENTISH TOWN ROAD	
	LONDON	
	NW1 8NY	
Section:	HEAVE ASSESSMENT	
Job No:	16063	
Calculations:	DR	
Date:	AUGUST 2015	Page No: 05




Fig.3.6 Diagrams for the factors μ_0 and μ_1 used in the calculation of the immediate average settlement of uniformly loaded flexible areas on homogeneous isotropic saturated clay, after Janbu, Bjerrum and Kjaernsli (1956)

PROJECT:	69 KENTISH TOWN ROAD	
	LONDON	
	NW1 8NY	
Section:	HEAVE ASSESSMENT	
Job No:	16063	
Calculations:	DR	
Date:	AUGUST 2015	Page No: 06.

Hence undrained settlement given by:-

$$s = \frac{qBI_v}{E_v}$$

$$= \frac{8.2 \times 0.6 \times 0.7 \times 2-1}{35} = 0.22 \text{mm}$$

Where Young's modulus for London clay typically falls in the range of 20-50 Mpa for an overconsolidated clay.

Average value \therefore 35 Mpa

This small short term settlement due to consolidation is entirely predictable and will be overcome by elastic recovery within the clay during and after bulk excavations and the creation of the proposed basement.

PHASE II

Heave assessment following construction of proposed basement

The technique used to determine the extent of elastic recovery in the overconsolidated London clay due to a reduction in pore water pressure is to use the formula for immediate settlement, but this acts in reverse.

PROJECT:	69 KENTISH TOWN ROAD	
	LONDON	
	NW1 8NY	
Section:	HEAVE ASSESSMENT	
Job No:	16063	
Calculations:	DR	
Date:	AUGUST 2015	Page No: 07.

Total excavation, maximum condition 2 m

Consider conservative load appraisal :-

self wt of clay removed $2.1 \times 19 = 39.9$

Add basement slab $0.2 \times 24 = 4.8$

Screed and insulation $= 1.7$

Dead load from ground floor $= 0.5$

Dead load from roof ignoring
green roof build up $= 0.5$

Allowance for new external walls.

$$2.0 \times 4.8 \text{ ht} \times 2 \text{ m} \div 5.3 \text{ (b) say} = 3.6$$

$$\text{Allowance for internal walls say } 2 \times 0.5 = 1.0$$

Ignore new elevation for now.

Hence left reduction in bearing
pressure once building erected

$$\underline{\underline{27.8 \text{ kN/m}^2}}$$

For the footprint of the buildup and the
sunken garden

Take Length $L = 12.5 \text{ m}$

Take width $B = 5.3 \text{ m}$

Consider the system as flexible as the
clay heave recovery will tend to create a
"dumpling" between the neighboring
properties

Work undertaken by Terzaghi also
recommends that calculated thickness H

should not exceed AB. This represents an upper bound.

Since $H = 52m$ and $AB = 4 \times 5.3 = 21.2m$

use $H = 21.2m$

$$H/B = 21.2 / 5.3 = 4.0$$

$$\mu_1 = 0.9$$

$$L/B = 12.5 / 5.3 = 2.4$$

$$\mu_2 = 0.94$$

$$D/B = 2.1 / 5.3 = 0.4$$


Hence predicted heave given by:

$$S_{\text{heave}} = \frac{27.8 \times 0.9 \times 0.94 \times 5.3}{35} \approx 3.6mm < 5.0mm.$$


The effect of this heave will be experienced by the subject property and the neighboring properties

work undertaken by Burland considers the effect of angular distortions as the cause of potential structural damage. If all the properties were to rise by 3.6mm there would be no damage. In reality this is not the case as the influence of heave on the clay diminishes with distance the further you move away from the excavated area.

PROJECT:	69 KENTISH TOWN ROAD	
	LONDON	
	NW1 8NY	
Section:	HEAVE ASSESSMENT	
Job No:	16063	
Calculations:	DR	
Date:	AUGUST 2015	Page No: 09



PROJECT:	69 KENTISH TOWN ROAD	
	LONDON	
	NW1 8NY	
Section:	HEAVE ASSESSMENT	
Job No:	16063	
Calculations:	DR	
Date:	AUGUST 2015	Page No: 10



Hence predicted heave recovery at Party wall positions causing angular distortion in neighbouring properties @ 0.758. = $0.75 \times 3.6 \text{mm} = 2.7 \text{mm}$

Since $2.7 \text{mm} < 5.0 \text{mm}$

BURLAND CLASSIFICATION SLIGHT