



Detail in question

External

- Existing in-situ cast structural concrete
- Low modulus silicone seal with backing rod
- Silver anodised aluminium angle
- EPDM bonded to structural concrete slab to provide airtight barrier
- 50mm silver anodised aluminium box section transom profile with pressure plate fixing and silver anodised cap
- Side opening AOV SG unit with friction stays Motor integrated in frame or in bespoke housing behind frame, for open area requirements refer to Wintech's specification

- 50mm silver anodised aluminium transom profile
- Injected foam insulation
- Phenolic insulation as P10/210A
- Vapour barrier bonded to inside of mullions
- line of concrete slab

- Silver anodised aluminium balustrade with 5mm thick 50mm deep fins fixed back to mullions
- Kingspan K18 composite panel with 20mm phenolic insulation, integral vapour control layer and 12.5mm plasterboard as K10/175G

Internal

(25) 131 Original ER detail

1 PLAN DETAIL 1:5

All dimensions must be checked on site and not scaled from this drawing. © Conran and Partners Limited

Rev	Date	Reason	By	Checked	Rev	Date	Reason	By	Checked
-	22.05.12	Draft Tender Issue	TG	AS					
A	01.06.12	Tender Issue	TG	AS					
B	31.08.12	Stage D	AS	AS					
C	04.12.12	Cladding Construction Issue	AS	AS					
D	30.04.13	Smoke vent updated	AS	AS					

Notes
The cladding configuration shown is based on structural dimensions taken from the original design drawings.
Structural dimensions are subject to confirmation by site survey.
For applicability of fritting please refer to the window schedule for each individual window number.
To be read in conjunction with Wintech's cladding specification

Project: Centre Point
Client: Almacantar
Drawing title: JD-15
End Jamb Detail - Openable
Scale 1:5@A3 Date: May 2012 Drawn by: TG
Project number: 2332 Drawing No: (25)131 Rev: D
Status: CONSTRUCTION Checked by: AS

CONRAN+ PARTNERS
Architects Designers
LONDON OFFICE
Conran Building
22 Shad Thames,
London SE1 2YU
Telephone +44 (0) 20 7403 8899
Email cp@conran.com

T:\2332 Centre Point\02-Sheets\25 Series External Wall\2332(25)131_JD-15_End Jamb_Openable.dgn

2332

Conran