

Lighting Specification: Replacement Infoband on the BT Tower

<u>Product Description and Specification</u>

- Display overall width: 59000mm +/- depending on mounting solution
 - o Each section will be small enough to be handled by one person
- Display overall height: 4800mm
 - Each section to be no more than 1200mm or 1600mm sections for handling as noted above
- Display depth: dependent on product and installation method
- Pixel pitch: 30mm +/- to deliver an even distribution of pixels
 - o (approximate resolution 1920 x 160)
- The screen will be installed as a circle (Diameter is 18.78m)
- Brightness: Outdoor brightness of no greater than 6000NIT
- Refresh Rate of Display: Minimum 2400Hz
- Viewing Angle Vertical: 120 degrees, angle up and down to be confirmed by manufacturer
- Viewing Angle Horizontal: Minimum 120 degrees, angle right and left to be confirmed by manufacturer
- LED diodes to be Nichia
- IP Rating: 67+
- Remote power and data.
 - NOTE: The display will be subject to extreme weather conditions including sun, wind, rain, snow, heat and cold. Ideally the display product will be able to be powered and controlled from remote distribution boxes that will be IP67 and can be isolated from direct effects of the weather (wind and rain).

С

- Warranty: 5 years +
- Spare Parts: 2% to 5% of components





Detail Specification **Notes** Display width 59000mm 59 Metres Display height 4800mm 4.8 Metres Determined by structure and Display depth TBD installation Pixel Pitch 30+ LED brand/manufacturer Nichia Viewing Angle 120 degrees Vertical minimum Down angle is priority Viewing Angle 120 degrees Horizontal minimum Upto 6000NIT Brightness 2400Hz Refresh Rate Processing 16bit IP Rating 67+ To be remotely Power and Data located Distribution to the display modules Power Remote location via cable Distribution to the display modules Data Remote location via cable Warranty 5 years + 2% plus Spare Parts

Yours sincerely,

Pod Bluman



