

Issued to Skanska, G&T and DP9 16.12.16

Planning condition 6

To be read in conjunction with drawings 464_90_315, 464_SK_1902, 464_SK_1930, 464_SK_1931 and 464_SK_1932.

- **Crushed stone gravel** laid between the staff cycle store and the entrance/exit gate on Guilford Place. To be laid in eggcrate system, layout as shown on the drawing together with interfaces with other landscape components.
Sub-base: Compacted granular fill, Type 1
Surface course: Crushed stone (Irish Buff Quartzite Aggregate), size 20mm. Compacted thickness 100mm



Plastics eggcrate system, 40mm thickness

Substrate: 150mm thick MOT Type 1. Compact and grade to required finished falls to prevent ponding and to achieve the required relationships with adjacent paving/edges, kerbs, finishes, etc.

- **Concrete Slab Paving** to be laid between entrance/exit gate on Guilford place and secondary staff entrance door.
Standard pimple texture precast concrete paving, corduroy/textured surface where show on the drawings. Colour, size and pattern to match paving on public realm.
Full bedding, in general areas: 25mm compacted sand, Type 1 granular sub base over geotextile layer.
Bedding on concrete: Full bed of 3:1, sand: cement
Joints 2-4mm wide, dry mortar brushed in.
- **Tar bound/spray gravel** finish in cycle store area up to metal access gate. To be installed over concrete slab laid to falls.
Surface course: Crushed stone gravel, size 5mm. Colour/type to match gravel surface in adjoining areas.