

(https://purifiedair.com)

UV-O Range

<	එ	lacktriangle	-

Our UV-O range includes:

- UV-O 500 which canhandle up to 1 m3/sec of air flow
- UV-O 1000 which can handle up to 2 m3/sec of air flow

The UV-O range uses UV-C technology to produce ozone and hydroxyl free radicals to oxidise cooking odours through a process of ozonolysis.

Unlike other UV-C systems, our UV-O units are located outside of the kitchen extract duct and are connected via a spigot and small diameter ducting.

Although it is widely accepted that the best way to apply UV-C light is directly in-line with the air stream itself, performance will be impacted as the lamps get dirty.

With our UV-O units the air flow does not come from the exhaust duct but from the ambient air around the unit, which is filtered on entry. This means that it is able to provide a uniform supply of ozone and hydroxyl free radicals into the extract system with an extremely low pressure loss.

For optimum performance we would recommend between 2 & 6 seconds of dwell time to allow the ozone to work effectively upon the malodorous gasses within the duct.

This unit's tried and tested UV-C technology allows for the siting of commercial kitchens in locations such as residential areas and shopping centres, where previously planning permission may not have been granted. After extensive research and development Purified Air are able to devise the best combination of lamps to provide the most effective odour control.

KEY FEATURES

- Easy to install
- Compact design
- Can be retro-fitted into existing duct
- Virtually no pressure loss
- No monthly maintenance needed.









Specialists Since 1984

Purified Air is a multi-faceted company, with manufacturing, specialist design, contracting and maintenance divisions within the commercial kitchen exhaust filtration and odour control spheres.

We are constantly striving to improve our technology through innovative R&D ensuring that we not only retain our loyal customer base but keep it growing as well.

As one of Europe's leading environmental control specialists we offer a diverse range of products and systems worldwide.

CONTACT US (HTTPS://PURIFIEDAIR.COM/CONTACTUS/) Technical Specifications

UV-O 500 UV-O 1000

Electrical Supply: 200/240V 50Hz 200/240V 50Hz 200/240V 50Hz

Max Power Consumption: 120 Watts 700 Watts

Max Air Volume: up to 1m3/sec up to 2m3/sec

UV-O 500 UV-O 1000

Dimensions: H 300mm / W 605mm / D 200mm H 350mm / W 1568mm / D 363mm

Weight: 10.5 Kg 50 Kg

PURIFIED AIR

Q

Purified Air Ltd, Lyon House, Lyon Rd, Romford, ESSEX, RM1 2GB, UK

C

0800 018 4000

 $\overline{}$

info@purifiedair.com (mailto:info@purifiedair.com)

HELPFUL LINKS

Home(https://purifiedair.com/)

Commercial Kitchen Filtration(https://purifiedair.com/commercial-kitchen-filtration/)

Servicing(https://purifiedair.com/servicing/)

Terms and Conditions(https://purifiedair.com/terms-and-conditions/)

Privacy Policy(https://purifiedair.com/privacy-policy/)

Contact us(https://purifiedair.com/contact-us/)

PRODUCTS

Oil Smoke and Grease Control(https://purifiedair.com/our-products/esp-range/)

Odour Control(https://purifiedair.com/our-products/odour-control/)

Resources(https://purifiedair.com/resources/)

FOLLOW US

You can find us in all of the usual social places

in (https://www.linkedin.com/company/purified-air?

trk=hb_tab_compy_id_2955966)

<u> (https://twitter.com/Purifiedair)</u>

(https://www.youtube.com/watch?v=JGHPLzdJMiM)







© 2017 Purified Air. All rights reserved.