









FPP-V
preSelect
FPU-V
preSelect
PPP-V
preSelect

TOP HUNG AND PIVOT WINDOWS **preSelect**

-   - A new generation of top hung and pivot windows with two separate opening functions of sash: top hung and pivot. Separate opening functions provide sash stability and increase safety. The outward opening function enables the sash to be opened in any position from 0 to 35 degrees enabling easy approach to the edge of the open windows, which increases the usable area and provides unlimited view to the outside. The pivot function enables the sash to be rotated through 180° and is used when cleaning the outer pane or operating an awning blind. Innovative hardware system guarantees the use of only one way of opening and complete stability of the sash in outward as well as in pivot opening function. Opening method can be switched using the preSelect sliding switch positioned in the middle of the frame accessible when the window is open.
-   **U3** - Comfort of operation when using the handle located at the bottom of the sash. Elegant handle is equipped with a two step micro-opening facility.
-   **15-55°** - Easy cleaning of the outer pane and setting the awning blind with the use of blocking sash bolt when rotated through 180 degrees.
- Available as standard with energy-saving glazing U3.
- Increased resistance to burglary - TopSafe system.
- A wide range of accessories.
- Suitable for roof pitches from 15 to 55 degrees, special version of windows from 15 to 85 degrees.



FPP-V preSelect

-  - Automatic air inlet V40P
-  - highest quality pine wood, glued in layers, vacuum impregnated
-  - wood painted twice with ecological acrylic lacquer in natural colour





FPU-V preSelect

-  - Automatic air inlet V40P
-  - highest quality pine wood, glued in layers, vacuum impregnated,
-  - with three coats of polyurethane varnish ideal for creating a durable and smooth finish in white on the frame surface. Designed for rooms with periodically elevated humidity levels (kitchens, bathrooms)



PPP-V preSelect

-  - Efficient air inlet V35
-  - multi chamber white PVC profile with reinforced steel core. Also available in golden oak or pine veneer
-  - the material does not absorb moisture, the window is durable and resistant to corrosion. Designed for rooms where elevated humidity level stays for long time (bathrooms, laundry rooms)

TOP HUNG AND PIVOT WINDOWS													
windows external dimensions [cm]	55x78	55x98	66x98	66x118	78x98	78x118	78x140	94x118	94x140	114x118	114x140	134x98	78x160
effective glazing area [m ²]	0.22	0.29	0.38	0.47	0.47	0.59	0.72	0.75	0.92	0.95	1.16	0.92	0.85
size symbol	01	02	03	04	05	06	07	08	09	10	11	12	13
FPP-V U3 preSelect	-	+	+	+	+	+	+	+	+	+	+	+	+
FPU-V U3 preSelect	-	+	+	+	+	+	+	+	+	+	+	+	+
PPP-V U3 preSelect	-	+	+	+	+	+	+	+	+	-	-	-	-