

FLASHINGS

Flashings are essential for the correct installation of window in the roof. Precisely designed flashing details ensure durable and neat fit with the roofing material used. The purpose of flashing is to ensure good drainage away of rainwater and melting snow from the window and to provide protection from the wind. In FAKRO product range there are many types of flashing solutions, which are made of aluminum sheet, protected by polyester lacquer. The basic colour is grey - brown RAL 7022, by which the window matches perfectly any standard roofing colour.



Standard flashings allow to install windows in the most popular types of roofing materials:



ES_
for flat roof coverings up to 10mm thickness (2x5mm)



EZ_
for profiled roof coverings (up to 45mm profile depth)



EH_
for high profile roof coverings (up to 90mm profile depth)



EHV-AT^{Thermo}
provides thermal insulation of roof windows above the surface of battens



EL_
for slated roof coverings up to 10mm thickness (2x5mm)



EG_
for slated roof coverings with thickness 24-32mm



EFW
flat roof system

FLASHINGS FOR CENTRE PIVOT WINDOW, TOP HUNG AND PIVOT WINDOWS

window dimensions [cm] size symbol	55x78 01	55x98 02	66x98 03	66x118 04	78x98 05	78x118 06	78x140 07	94x118 08	94x140 09	114x118 10	114x140 11	134x98 12	78x160 13
ESV for flat roof coverings	+	+	+	+	+	+	+	+	+	+	+	+	+
EZV-P for profiled roof coverings	+	+	+	+	+	+	+	+	+	+	+	+	+
EHN-P for high profile roof coverings	+	+	+	+	+	+	+	+	+	+	+	+	+
EHV-AT^{Thermo}*	+	+	+	+	+	+	+	+	+	+	+	+	+
ELV for slated roof coverings	+	+	+	+	+	+	+	+	+	+	+	+	+
EGV for thick slated roof coverings	+	+	+	+	+	+	+	+	+	+	+	+	+
EFW flat roof system	-	+	-	+	+	+	+	+	-	+	-	-	-

*flashing for flat, profiled and high profiled roof coverings (up to 90mm profile depth)

FLASHING FOR JOINING WINDOWS IN COMBINATIONS

Flashing systems are ready made flashing combinations for joining windows in the groups: horizontally, vertically, and in a block. The distance between the windows joined horizontally and vertically is normally 10cm. If external shutters are installed on windows installed vertically, a gap of at least 20cm is required. There are seven modules in the FAKRO combination system to cater for any layout you may require.



B2/1
horizontal combination



B1/2
vertical combination



B2/2
block combination

THE MOST POPULAR-FLASHING COMBINATIONS FOR PROFILED ROOF COVERINGS

window dimensions [cm] size symbol	55x78 01	55x98 02	66x98 03	66x118 04	78x98 05	78x118 06	78x140 07	94x118 08	94x140 09	114x118 10	114x140 11	134x98 12	78x160 13
B2/1	+	+	+	+	+	+	+	+	+	+	+	+	+
B1/2	+	+	+	+	+	+	+	+	+	+	+	+	+
B2/2	+	+	+	+	+	+	+	+	+	+	+	+	+