

Refer to enlarged

bathroom/ensuite/WC

Refer to enlarged

bathroom/ensuite/WC

<u>Finishes Legend :</u> <u>External and Separating Wall Lining Types:</u>

Soundbloc on Vapour Control layer. All joints to be taped and jointed, giving a smooth and seamless finish ready for decoration.

Type P1M. As type P1, but with outer layer replaced with 15mm Gyproc Soundbloc Moisture Resistant plasterboard.

Type P2. Typical Gypwall Quiet IWL Separating Wall - 2 layers of 15mm British Gypsum Soundbloc or similar to each side. All joints to be taped and jointed, giving a smooth and seamless finish ready for

Type P2M. As type P2, but with outer layer replaced with 15mm Gyproc Soundbloc Moisture Resistant plasterboard ('wet' side). Type P2M2. As type P2, but with outer layers replaced with 15mm Gyproc Soundbloc Moisture Resistant plasterboard (both sides) Type P3 / P3A. Independent wall lining. Generally to cores - Width Varies, depending on wall height - 70 / 92mm Gyplyner 'IWL' at

600mm centres with 1 layer of 15mm British Gypsum Gyproc

15mm Gyproc SounBloc Moisture Resistant plasterboard ('wet' side).

SoundBloc. Fully filled with unfaced mineralwool with min. density 10kg/m3 between studs. All joints to be taped and jointed, giving a smooth and seamless finish, ready for decoration. Type P3M / P3A-M. As type P3, but with outer laver replaced with

Kooltherm K12 board - insulation notched where required) with 32.5mm Kooltherm K118 (20mm rigid insulation with 12.5mm Plasterboard with integrated VCL). All joints to be taped and jointed, giving a smooth and seamless finish, ready for decoration. 32.5mm

Kooltherm K118 to window returns.

seamless finish, ready for decoration.

Type P4M. Thermal Lining to existing buildings to Wet areas (upper floors) - Gyplyner Universal GL1 channels at 600mm centres with 32.5mm timber studs, 82.5mm Kooltherm K12 board - insulation notched where required with 12.5mm Gyproc Wallboard Moisture Resistant. All joints to be taped and jointed, giving a smooth and

Type P5 & P5M. SVP Boxing. 2 no. layers 15mm SoundBloc plasterboard, on 60mm Gypframe studwork generally to syp casings. All joints to be taped and jointed, giving a smooth and seamless finish, ready for decoration. Pipework to be wrapped in 50mm unfaced mineral wool. NB. 15mm Soundblock MR to replace outer layer of boxing in 'Wet' areas (Bathrooms, WCs, Utility Cupboards, Kitchens, etc). Boxings to be fully filled with insulation when adjoining solid party

no. layer of 15mm British Gypsum Duraline (both sides). All joints to be taped and jointed, giving a smooth and seamless finish ready for

iointed, giving a smooth and seamless finish ready for decoration

Type P8. Thermal Independant Wall Lining with Drained cavity (generally to existing buildings - Basements) - Gyplyner IWL at 600mm centres with 1 layer of 12.5mm British Gypsum Gyproc Wallboard on 92 I studs. Fully filled with unfaced mineralwool, density 10kg/m3 between studs. All joints to be taped and jointed, giving a smooth and seamless finish, ready for decoration.

Type P8M. As type P8, but with Wallboard replaced with 12.5mm roc Wallboard Moisture Resistant plasterboard.

Type P9. Load-bearing studwork to external Wall (Rosalind Franklin) 2 no. layers of 15mm British Gypsum Soundbloc on Vapour Control layer. All joints to be taped and jointed, giving a smooth and seamless Type P9M. As type P9, but with Soundbloc replaced with 15mm Gyproc Soundbloc Moisture Resistant plasterboard.

Type P10 Separating Wall Gypwall Quiet IWL (Pavilions) - 2 no. layer Type P6. Separating Wall Gypwall Quiet IWL (Community Facility) - 2 of 15mm British Gypsum Soundbloc or similar to each side. All joints to be taped and jointed, giving a smooth and seamless finish ready for Gyproc Soundbloc Moisture Resistant plasterboard (both sides)

Type P10M. As type P10, but with one side of Soundbloc replaced

with 15mm Gyproc Soundbloc Moisture Resistant plasterboard ('wet'

Type P11. As type P4, but with additional membrane Newton Lath or similar fixed directly to masonry wall to the height of approx 1200mm

from the FFL. Slots to be incorporated to top and bottom of the lining Type P12 & P12M, Approx. 215mm Existing brickwork, 35mm cavity created by GypLyner Universal system, 25mm Isover Apr 1200 mineral wool in cavity, 1 no. layer of 15mm Gyproc Soundbloc (Moisture resistant for P12M)

Internal Partitions:
Type P20. Internal Partition width 97mm. 70mm Gypframe 'C' studs at max. 600mm centres with 1 layer of 12.5mm British Gypsum Gyproc SoundBloc to both sides. All joints to be taped and jointed, giving a smooth and seamless finish, ready for decoration.

Type P20M. As type P20, but with one side of SoundBloc replaced with 12.5mm Gyproc Soundbloc Moisture Resistant plasterboard ('wet'

Type P20M2. As type P20, but with both layers replaced with 12.5mm Type P21. Internal Partition width 155mm. 92mm Gypframe 'C' studs at max. 600mm centres with 1 layer of 12.5mm British Gypsum Gyproc SoundBLoc on 18mm Plywood to both sides. All joints to be taped and jointed, giving a smooth and seamless finish, ready for

Gyproc Soundbloc Moisture Resistant plasterboard (both sides) Type P22. Timber stud braced wall. 100mm timber studs at 600mm centres with 1 layer of 18mm Plywood to each side and 1 layer of 12.5mm Gyproc SoundBloc plasterboard to both sides. All joints to be Type P25M.As type P25, but with 'wet' side plasterboard replaced with taped and jointed, giving a smooth and seamless finish, ready for

Type P22M. As type P22, but with one side of SoundBloc replaced with 12.5mm Gyproc Soundbloc Moisture Resistant plasterboard ('wet

Type P23. Timber stud braced wall. 140mm timber studs at 600mm centres with 1 layer of 18mm Plywood to both sides and 1 layer of 12.5mm Gyproc SoundBloc plasterboard to both sides. All joints to be taped and jointed, giving a smooth and seamless finish, ready for

Type P23M.As type P23, but with one side SoundBloc replaced with

12.5mm Gyproc Soundbloc Moisture Resistant plasterboard ('wet' Type P24. Internal Partition width 122mm. 70mm Gypframe 'C' studs at max. 600mm centres with 2 layers of 12.5mm British Gypsum Gyproc SoundBLoc to each side. All joints to be taped and jointed,

Type P21M2. As type P21, but with both layers replaced with 12.5mm

Type P25. Timber Stud Wall (Queen Mothers Hall) 100mm Stud Wall with 1 layer of 12.5mm British Gypsum Gyproc Wallboard. All joints to

> be taped and jointed, giving a smooth and seamless finish ready for 2.5mm Gyproc Wallboard Moisture Resistant board. Type P26M Tile Finish on 12.5mm Glasroc "Tilebacker" MR on the 'wet area' side on 92mm Gypframe studs. 18mm Plywood in

Sypframe service support plate brackets. As Required by Mixer 12.5mm Soundblock to Non "wet Side". All joints taped and sealed according to manufacturers recommendations, giving a smooth and seamless finish, ready for decoration.

Refer to Dry Lining Details 1 - 3 for P-number drawings

(9000-DRG-00GN-DE030 - DE033) Specifications outlined in P-number descriptions and

details to be reviewed in conjunction with waterproofing

specialist to determine suitability for indicated position.

at max. 600mm centres with 1 layer of 12.5mm British Gypsum Wallboard to one side. All joints to be taped and jointed, giving a smooth and seamless finish, ready for decoration.

Type P40M. As type P40 but with the layer of Plasterboard replaced with Gyproc Moisture Resistant plasterboard to 'wet' area. Type P41. Typical Sacrificial Wall - Gyplyner Universal GL1 channel with offset of 35mm at 600mm centres (GL2 fixing brackets) with 1 layer of 12.5mm British Gypsum wallboard. All joints to be taped and

jointed, giving a smooth and seamless finish, ready for decoration. Type P41M. As type P41 but with the layer of Plasterboard replaced with Gyproc Moisture Resistant plasterboard to 'wet' area. Type P42. Typical Sacrificial Wall (Generally for 40mm Drainage runs) - Gyplyner Universal GL1 channel with offset of 75mm at 600mm centres (GL2 fixing brackets) with 1 layer of 12.5mm British

and seamless finish, ready for decoration. **Type P42M.** As type P42 but with the layer of Plasterboard replaced with Gyproc Moisture Resistant plasterboard to 'wet' area. ype P43. Typical Sacrificial Wall (Generally for WC Drainage runs) Type P48/P49. Assumed plaster repair or Lime Plaster repair

Gyplyner Universal GL1 channel with offset of 125mm at 600mm

centres (GL9 fixing brackets) with 1 layer of 12.5mm British Gypsum

wallboard. All joints to be taped and jointed, giving a smooth and

seamless finish, ready for decoration.

Gypsum wallboard. All joints to be taped and jointed, giving a smooth

Type P44. Lining to cavity brick, separating walls - 1 layer of 12.5mm British Gypsum wallboard on 10mm adhesive dabs on 8mm parge coat (Gyproc Soundcoat Plus). All joints to be taped and jointed.

giving a smooth and seamless finish, ready for decoration. Type P44M. As type P44 but with the layer of Plasterboard replaced with Gyproc Moisture Resistant plasterboard to 'wet' area. Type P45 - Typical Lining to RC, blockwork columns, walls 12.5mm Gyproc SoundBloc on dabs. All joints to be taped and

jointed, giving a smooth and seamless finish ready for decoration **Type P45M -** As type P45 but with outer layer replaced by 12.5mm SoundBloc MR Board on dabs. All joints to be taped and jointed, giving a smooth and seamless finish ready for decoration Type P46. Plaster to Leisure Area (not to pool). Thistle HardWall by

British Gypsum, nom. 11-12mm. Type P47. Tiling to pool Area. Microtec Fibre reinforced floor adhesive (Ardex X 77) or similar. Thickness varies depending on tile types (to pool specialist's specification)

respectively to existing Walls. Extent of existing damage to be

prior to commencement of work.

assessed on site - removal to be agreed. New plaster to match

existing. Plaster to be feathered with existing and made good. If type

of plaster does not correspond as noted, please contact the architect

manufactures recommendations. Type P53. Assumed existing plasterboard on studwork - Remove and replace plasterboard on both sides with 12.5mm British Gypsum Wallboard.

Moisture Resistant plasterboard to 'wet' area.

taped and jointed, giving a smooth and seamless finish, ready for

Type P50M. As type P50 but with the one side of Plasterboard

eplaced with Gyproc Moisture Resistant plasterboard to 'wet' area.

Type P51. Drained Cavity with Gyplyner Universal (Generally within

Type P51M. As type P51 but with Plasterboard replaced with Gyproc

basements) with 10mm Cavity membrane & 15mm Plaster finish to

Basements) GL1 channel with 1 layer of 12.5mm British Gypsum

wallboard, fully filled with insulation (mineral wool). All joints to be

taped and jointed, giving a smooth and seamless finish, ready for

Type P52. Drained Cavity with mesh system (generally within

DIMENSION AT ORIGINAL SHEET SIZE ontractors must check all dimensions on site. Only figured dimensions are to be worked from Discrepancies must be reported to the Architect before proceeding. This drawing is Copyright

KEY PLAN

NOTE:

General Notes

standard details.

ALL DIMENSIONS WITH * (STAR) ARE ANTICIPATED AND SHOULD BE CHECKED AND CONFIRMED ON SITE PRIOR TO CONSTRUCTION

1. All types noted below are based on the British Gypsum range. 'Similar and approved' products will be considered by the client. Any alterations to the specifications below are to be approved by the client PRIOR to order.

2. Drylining drawings are to be read in conjunction with all relevant AQP GA and M&E consultant drawings.

3. Moisture resistant plasterboard is to be used in all wet areas (Kitchens Bathrooms, En-suites and Utility Cupboards), Areas requiring moisture resistant board are identified with the 'M' prefix in the partition type. Tiled surfaces: MR Plasterboard to be replaced with 12.5mm Glasroc H Tilebacker boards.

4. 18mm WBP plywood support patresses on proprietary service plates are to be provided in the following areas:

i. Kitchens (Full height) ii.Bathrooms (A band between 300-1800mm) iii.Living Rooms (1500mm(wide) x 1035mm(high) behind wall mounted TV positions, exact locations to be agreed on site with

5. Additional noggings/supports etc are to be provided as necessary for radiators, kitchen units, wall mounted TVs, shower mixers &

6.Deflection head details are indicated at partition heads giving min. vertical deflection allowance of 25mm. Extra deep flange channels and packing to be provided in accordance with manufacturers

7.All necessary beads etc. to be provided. General Internal Suspended Ceiling [Newbuild]:

12.5mm Wallboard in 'dry areas' and 12.5mm moisture resistant wallboard in 'wet areas'. Gypframe MF8 strap hangers to be fixed to u/s of concrete soffit with Gypframe M12 soffit cleats. Proprietary primary and secondary support grids to be provided at centres in accordance with manufacturers standard details. All perimeter

British Gypsum Casoline MF ceiling system finished with 1 no.

channels etc. to be provided in accordance with manufacturers standard details. All joints to be taped and jointed, giving a smooth and seamless finish, ready for decoration.

FOR CONSTRUCTION

	REVISION	DR'N	CH'KD	DATE
C1	Issued for Construction	NV	TW	23/12/2016
	P Number Key Updated	NV	TW	27/02/2017
C2	Lintel Information Added			
	Setting Out Information Added			
СЗ	PNumbers updated. Window Ref & niches added. Layout Updated following client comments.	NV	TW/KC	20/04/2017
	Internal partition Moved/Revised	MRR	кс	13/06/2017
C4	Annotation Added/Revised			
	Door and window frame sizes revised			
				-
		_		



MOUNT ANVIL LTD



KIDDERPORE AVENUE

Chapel

Level UG Proposed GA Plan

SCALE 1:50 @ A1 DATE June 2017 DRAWING No. **DRAWN BY** MRR

15 230 9000-DRG-03CH-UG010

A&Q PARTNERSHIP (LONDON) LTD THE LUX BUILDING, 2-4 HOXTON SQUARE, LONDON N 1 6 NU Tel: 020 7613 2244 Fax: 020 7613 2642 Email:london@aqp.co.uk ARCHITECTURE DESIGN MASTERPLANNING INTERIORS