



Data Sheet

Optigrün-Separation- and Protection Mat RMS 300

<i>Product- description</i>	Material:	Regenerative syntetic fibre (PP/PES/Acrylic)
	Nominal thickness:	approx. 2,8 mm
	Surface weight:	300 g/m ²
<i>Technical data and Properties:</i>	Production:	Mechanical solidification
	Strength class:	II
	Detector examined:	yes
	UV resistant:	no
	Colour:	multicoloured
<i>Delivery form:</i>	Roll width:	2,40 m
	Roll length:	50 m
	Surface area:	120 m ²
	Bulk weight:	approx. 36 kg
<i>Application:</i>	Separation and protection areas Watersaving vlies (approx. 2 l/m ²)	
<i>Storage:</i>	dry laying	
<i>Disposal:</i>	In clean, recyclable condition	
<i>Process of Installation:</i>	Follow laying instructions With 10 cm overlap	
<p><i>The mentioned data act as guidelines discovered in the company-owned Laboratory that our supplier would want to obtain. The values underlie a Manufacturing tolerance of approximately 8-10%. Included in this product information are data corresponding to the technical information at the time of writing. It remains reserved with Optigrün to supplement and change new knowledge at any given time so that the properties of the products can be modified.</i></p>		