

CEIBRIT Roof Slate | Contessa



Contessa, Spanish natural slate is selected from quarries with a reputation for supplying reliable, cost effective roofing slates. Available in textures from regular to rugged, Contessa slates offer the variety of choice to create your desired characterful roof.

Our long standing relationships ensure regularity of supply and consistency of quality. As with all natural slate Contessa require grading and sorting on site before fixing.



Quality

Contessa slates are selected with the UK climate in mind and samples are regularly tested to the following national standards:

British Standard

BS EN 12326-1: 2014 product specification for roofing slate.

- Exhibited the top Class W1 (≤ 0.6) for water absorption
- Exhibited the top Class T1 for thermal cycle resistance
- Exhibited the top Class S1 for sulphur dioxide exposure resistance
- Good flexural strength both transversely and longitudinally
- Acceptable non-carbonate carbon content

Description	Pre-holed natural slate with visible stable pyrites and normal texture				
Appearance	Blue black and grey shades with varied surface finishes				
Thickness	4-7mm	4-7mm	4-7mm	4-7mm	4-7mm
Dimensions mm	400x200	400x250	500x250	500x300	600x300
Typical quantity per crate	1000	900	800	520	500
Average weight per slate Kg	1.21	1.51	1.80	2.27	2.73
Approx. weight per crate Kg	1210	1361	1437	1180	1366
Slates per m ²	30.96	24.77	19.91	15.76	12.7
Weight Kg per m ²	37.46	37.46	35.76	35.76	34.7
Accreditation	BS EN 12326				
Minimum roof pitch					
Moderately exposed location	30°	30°	25°	20°	25°
Severely exposed location	30°	30°	30°	22.5°	30°

Cembrit Ltd
57 Kellner Road
London
SE28 0AX

Tel: +44 (0)20 8301 8900
Fax: +44 (0)20 8301 8901
sales@cembrit.co.uk

Branch listings

1 London	T +44 (0)20 8301 8900
2 Southampton	T +44 (0)23 8064 4211
3 Bovey Tracey	T +44 (0)1626 835722
4 Llandow	T +44 (0)1446 773777
5 Normanton	T +44 (0)1924 890890

