



BRICK UP THE OPENING IN THE PARTY WALL.

TRIPLE UP THE FLOOR JOISTS UNDER THE EXISTING PARTITION AS DETAIL 7 ON DRG. N° 2995/20.

340 x 340 CONCRETE PADSTONE ON NEW BRICK PIER UNDER x 225 DEEP.

EXISTING BRICK PIER TO BE CUT BACK - NEW LINTELS OVER SEE THE FIRST FLOOR PLAN.

2 N° 340 x 215 CONCRETE PADSTONES BUILT OFF NEW PIERS UNDER (SEE BASEMENT PLAN) USED TO SUPPORT A 203 x 203 x 46 U.C. LINTEL OVER BASEMENT OPENING.

2 N° 90 x 90 x 8mm THK. STEEL POSTS BOLTED TO U.C. USING 4 N° M16 GRADE 8-8 BOLTS.

DETAIL 1

2

340mm

2 N° 305 x 89 x 41 R.S.C.'s CASED IN CONCRETE AS SECTION 2-2.

2

3

3

203 x 203 x 46 U.C.

NOSSINGS

CUT BACK DOUBLE S. TO BEAM

4 N° 150 CONCRETE BELOW

N° 6

560 x 100 x 225 x 225 x 150

EXISTING

CUT OUT INSTALL TO THE DRAWING

2 N° 150 CONCRETE

440 x 225 BRICK PADSTONE 90 x 8

N° 7

2000 mm DP. 3000 mm DP.

DETAIL

NEW TIMBER Floor 150 x 50

102.15