

# XAL

## MINO 20 IP54

### 856-1143616O

DATE	
PROJECT	
REMARK	
TYPE	
QUANTITY	

#### Quickinfo

##### GENERAL

Ceiling / Wall
Surface
anodised aluminium
400 lm
450 lm/m
IP54

##### LED

4000 K
CRI $\geq 80$
L70 / 50000 h
initial $\leq 3$ MacAdam

##### OPTICAL

PMMA Cover Opal
-----------------

##### PHYSICAL

length 918 mm
width 18 mm
height 41 mm



##### ELECTRICAL

8 W
non DIM
EEI B
53 lm/W



ultra low-profile luminaire made of extruded aluminium; light tight final end caps made of aluminium; no visible screws; angular design; aluminium surface etched and plain anodised; suitable for wall or ceiling mounting; lighting profile (end cover pre-assembled) available in advance for installation; remaining lamp components mounted without tools; LED circuit board inserted in homogeneously illuminated cover in satinised PMMA; light colour 4000 K; Binning  $\leq 3$  MacAdam; CRI  $\geq 80$ ; min. 70% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; due to special material composition with increased transmission and diffusion; + 15% luminous efficiency compared to standard opal covers; luminaire with pre-assembled 300mm connection cable and HVL connector; protection rating IP54; PC I; without control device.;

#### Light Distribution



# XAL

## MINO 20 IP54

### 856-11436160

#### CONVERTER

One of these is required

#### LED CONVERTER

TYPE	L · W · H (MM)	ORDERCODE
16 W 220-240V AC	121-45-16	0 0 2 - 6 0 1 3 3
40 W 110-277V AC	163-43-32	0 0 2 - 6 0 1 3 5
75 W 110-240 V AC	185-63-41	0 0 2 - 6 0 1 4 0
150 W 110-240V AC	222-68-39	0 0 2 - 6 0 1 5 1



#### CABLES (For 16W converter)

#### POWER CABLE LENGTHENING

LENGTH (MM)	ORDERCODE
1500	0 0 2 - 5 9 9 9 5
2500	0 0 2 - 5 9 9 9 6
4000	0 0 2 - 5 9 9 9 7

#### CABLES (For 40W+ converter)

#### POWER CONNECTION CABLE

LENGTH (MM)	ORDERCODE
1500	0 0 2 - 5 9 9 9 1
2500	0 0 2 - 5 9 9 9 2
4000	0 0 2 - 5 9 9 9 3



#### CONNECTION BOX

#### CONNECTION BOX IP55

L · W · H (MM)	ORDERCODE
85-85-42	0 0 2 - 5 9 9 9 0

