

XAL

MINO 20 IP54

856-1141616O

DATE	
PROJECT	
REMARK	
TYPE	
QUANTITY	

Quickinfo

GENERAL

Ceiling / Wall	
Surface	
anodised aluminium	
130 lm	
450 lm/m	
IP54	

LED

4000 K	
CRI ≥ 80	
L70 / 50000 h	
initial ≤ 3 MacAdam	

OPTICAL

PMMA Cover Opal	
-----------------	--

PHYSICAL

length 314 mm	
width 18 mm	
height 41 mm	



ELECTRICAL

3 W	
non DIM	
EEI A	
53 lm/W	



ultra low-profile luminaire made of extruded aluminium; light tight final end caps made of aluminium; no visible screws; angular design; aluminium surface etched and plain anodised; suitable for wall or ceiling mounting; lighting profile (end cover pre-assembled) available in advance for installation; remaining lamp components mounted without tools; LED circuit board inserted in homogeneously illuminated cover in satinised PMMA; light colour 4000 K; Binning ≤ 3 MacAdam; CRI ≥ 80 ; min. 70% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; due to special material composition with increased transmission and diffusion; + 15% luminous efficiency compared to standard opal covers; luminaire with pre-assembled 300mm connection cable and HVL connector; protection rating IP54; PC I; without control device.;

Light Distribution



XAL

MINO 20 IP54

856-11416160

CONVERTER

One of these is required

LED CONVERTER

TYPE	L · W · H (MM)	ORDERCODE
16 W 220-240V AC	121-45-16	0 0 2 - 6 0 1 3 3
40 W 110-277V AC	163-43-32	0 0 2 - 6 0 1 3 5
75 W 110-240 V AC	185-63-41	0 0 2 - 6 0 1 4 0
150 W 110-240V AC	222-68-39	0 0 2 - 6 0 1 5 1



CABLES (For 16W converter)

POWER CABLE LENGTHENING

LENGTH (MM)	ORDERCODE
1500	0 0 2 - 5 9 9 9 5
2500	0 0 2 - 5 9 9 9 6
4000	0 0 2 - 5 9 9 9 7

CABLES (For 40W+ converter)

POWER CONNECTION CABLE

LENGTH (MM)	ORDERCODE
1500	0 0 2 - 5 9 9 9 1
2500	0 0 2 - 5 9 9 9 2
4000	0 0 2 - 5 9 9 9 3



CONNECTION BOX

CONNECTION BOX IP55

L · W · H (MM)	ORDERCODE
85-85-42	0 0 2 - 5 9 9 9 0

