


LOFT

MAIN-FLOOR



No. Notes

- Dimensions to be verified on site. Only figured dimensions to be used. No dimensions are to be scaled from printed drawings. Any areas indicated on this drawing are for guidance only. No responsibility is taken for their accuracy.
- There is a risk of injury or death in construction if the works are not properly planned and supervised. The contractor must not undertake any element of the work without first having carried out the necessary risk assessments and prepared detailed method statements.
- This note is to inform the Client of their duties under CDM regulations to appoint a Principal Designer in writing unless the Client acts as PD. A Health & Safety file must be prepared and kept on site. General Notes for BC
- requirements
- 30min fire rating to loft door and reception door closer. 30min fire rating to flat entrance door with
- 60min fire rating to all hallway areas incl walls to stairs, floors and ceilings to hallway. room doors.
- flat. 30min fire rating & insulation to all ductwork runs within circulation area of
- Fire stopping Contractors Design Portion 30min fire rating to hall storage cupboard. Hard-wired, interlinked, mains-operated
- the flats as stipulated in Approved Document Part B1 Volume 2 Buildings other than dwelling houses. be provided within the circulation areas of smoke alarms with battery back-up shall

Dwg. type: Design Intent	London	23 Dartmouth Park Hill	Job: Flat 3	Proj: Refurbishment	Dwg: Proposed Plans	- Flatining I saue
		ᆽ				171024

1701

210 size drawing number

> revision date

Dwg. status: Preliminary

1:100