

GGL/GPL Conservation Roof Window



The VELUX Conservation roof window provides all the technically superior features of a VELUX Roof Window in a traditional black conservation style including glazing bar/s. The GGL centre-pivot and GPL top-hung windows are manufactured in high quality natural pine with a clear lacquered pine internal finish.

The Centre-pivot (GGL) is manually operated and is recommended by VELUX for higher reach windows. To watch an illustration of how the window operates click here.

The Top-hung (GPL) is manually operated and is recommended by VELUX for lower

level installation and is ideal for shallower roof pitches. It is also suitable for escape purposes. To watch an illustration of how the window operates click here.





Centre-pivot
Tiles 15-90°
Tiles (recessed) 20-90°
Plain tiles 25-90°
Slate (recessed) 20-90°

Top-hung
Tiles 15-55°
Tiles (recessed) 20-55°
Plain tiles 25-55°
Slate (recessed) 20-55°

TOP HUNG - For roof pitches from 55°-75°, please specify special springs when ordering.



Features/Benefits

- Ventilation bar with dust and insect filter Allows fresh air to enter the room while the window is securely closed
- Friction springs Allows easy operation of window
- Sash rotates 180° from inside Allows easy and convenient cleaning
- Barrel bolt Allows the window to be locked in two positions – At 180° for secure cleaning of the exterior pane internally – At 5° to allow extra ventilation



Operation

GGL – The window is operated manually using the full width control bar on the ventilation flap along the top of the sash. GPL – The sash which is top-hung is opened and closed using the bottom handle and can remain open in any position up to 45°

To watch an illustration of how the window operates click here.



(--50) glazing Double glazed, toughened outer pane.

Also available in;

(--60) glazing Double glazed, laminated inner pane,

toughened outer pane with Easy-to-clean coating, enhanced noise reduction.

(--70) glazing Double glazed, laminated inner pane,

toughened outer pane.

For further information regarding VELUX glazing options click here.



Cladding

 NCS standard colour (Black), Nearest RAL standard colour: 9005.

For further advice on maintenance please click here.

Maintenance

10 year VELUX guarantee on windows and flashing kits.

The pane should be cleaned with a soft, clean, lint-free cloth

or non-abrasive sponge. The rest of the window can be cleaned with ordinary household cleaners. The filter can

be removed and either washed or replaced.

• 3 year guarantee on blinds, shutters, awnings and electrics.

Click here for further information regarding the VELUX guarantee.


Interior finish option GGL

· White paint finish.


GPL

· White paint finish.

Best practice installation



Sizes (cm)



Technical data - GGL/GPL Conservation

			-	
Size	Window Options	Exterior Frame	Visible Glass	Lining Rebate
		WxH	exf	kxl
CK04	GGL	550 x 978	371 x 783	495 x 919
CK06	GGL	550 x 1178	371 x 983	495 x 1119
FK06	GGI	660 x 1178	481 x 983	605 x 1119

Size	Window Options	Exterior Frame	Visible Glass	Lining Rebate
		WxH	exf	kxl
MK06	GGL	780 x 1178	601 x 983	725 x 1119
MK08	GGL, GPL	780 x 1398	601 x 1203	725 x 1339
UK04	GGL	1340 x 978	1161 x 783	1285 x 919

VELUX GGL UK04 SD5W2 Conservation 134x98cm

Images from outside below. The first one the 138x98cm dimension window proposed. The second just shows a conservation window in wider context as it is - discreet and flat to the roof. The third picture is generic and not to scale - it just shows the type of window and how the centre pivots.







VELUX GGL UK04 3570 Conservation Centre Pivot Roof Window 134x98cm

Description

The VELUX conservation range of roof windows are classic windows that blend tastefully into the roof of your old building with a vertical centre bar and black finish exterior. These windows have all the great features and superior insulation of our standard roof windows, making them the perfect choice for your renovation project.

- Centre-pivot opening
- One pull of the top control bar allows background ventilation, one further pull opens the window
- Black external profiles and glazing bar.
- Rotate 180° and lock in place for cleaning of outer pane