

Summary Of Structural Assessment And Strengthening Works Required

The capacity of the existing structural elements have been checked against the required loadings to the Eurocodes. Below is a summary of the assessment identifying any elements which require strengthening as part of the refurbishment works:

Existing Timber Spine Beam Assessment:

The spine wall has been removed at ground floor level so the existing timber floor beams at each level have been assessed.

Bending Stresses @ 230% capacity => strengthening required  
Deflection @ 200% limit => strengthening required

Refer to S-0001.1-Detail 1

Existing Timber Floor Joist Assessment:

The existing floor joists vary in both depth and width, typically they are 160x60 at 380 c/c. They have been assessed for their maximum span.

Bending Stresses @ 98% capacity  
Deflection @ 160% limit => strengthening required

Refer to S-0001.1-Detail 1

Existing Stair Beam Assessment:

The stair wall is not supported below first floor level so the existing timber floor beams at each level have been assessed.

Bending Stresses @ 140% capacity => strengthening required  
Deflection @ 200% limit => strengthening required

Refer to S-0001.5-Detail 6

Existing Floor Beam Assessment:


The existing timber floor beam at each level have been assessed.

Bending Stresses @ 110% capacity => strengthening required  
Deflection @ 200% limit => strengthening required

Refer to S-0001.4-Detail 4

Existing Floor Movements:

From survey spot levels the existing floor structure has settled/deflected by up to 100mm at each floor level. Strengthening Works are required to ensure to further settlement occurs



TYPICAL FLOOR PLAN 1ST TO 3RD

NOTES


engenuiti

+44 (0)20 7089 5760  
www.engenuiti.com

2 Mallings Place  
Tower Bridge Road  
London SE1 3JB  
United Kingdom

project name			
7 Denmark Street			
sketch title			date
Proposed Structural Details			20/11/2017
project no	sketch no	rev	by
879	03-XX-LB-S-0001.0	01	RK

- This option provides the required strengthening to the existing spine beam while minimising impact on the historic finishes.
- This option does require the existing floor beams to be trimmed and re-supported on the new steelwork
- Option A is considered to have the least impact on the historic building fabric while achieving the required structural strengthening



**Detail 1: Spine Beam & Joist Strengthening Requirements, 1:10**

**Structural Strengthening Requirements:**

- The existing spine wall beam can not be justified to support the required residential loadings to current standards therefore strengthening is required.
- The existing floor joists require strengthening due to comply with current standards and allow for levelling of existing floors
- Generally all structural strengthening proposed will reduce deflections and movements within the building to protect the historic structure and materials from further damage
- Steel beams to bear onto padstones in masonry party walls



**Figure 1, Spine Wall Strengthening Location (Indicative)**

NOTES

engenuiti

+44 (0)20 7089 5760  
www.engenuiti.com

2 Mailings Place  
Tower Bridge Road  
London SE1 3JB  
United Kingdom


project name 7 Denmark Street			
sketch title Proposed Structural Details			date 20/11/2017
project no 879	sketch no 03-XX-LB-S-0001.1	rev 01	by RK



Strengthening steel beams to existing timber spine wall beams allow for kitchen waste pipe to run through to riser beyond - steel beams to be strengthened locally around penetration

Existing and proposed joists to be strengthened locally with steel plates to allow for kitchen waste pipe to run within floor zone - plates to be screw fixed to joists

Service penetration to mid depth of joists



Proposed service riser location

**Detail 2: Spine Beam & Joist Service Penetration, 1:10**

**Structural Strengthening Requirements:**

- The strengthening is required to allow the waste pipe from the proposed kitchen island unit to run through the floor zone. The island unit is required to avoid any damage to historic wall finishes
- The service run for the kitchen waste pipe will effect a maximum of 3 joists and the spine beam at each level



**Figure 2, Spine Wall Strengthening Location (Indicative)**


NOTES

engenuiti

+44 (0)20 7089 5760  
www.engenuiti.com

2 Mailings Place  
Tower Bridge Road  
London SE1 3JB  
United Kingdom

project name		7 Denmark Street	
sketch title		Proposed Structural Details	
project no		879	
sketch no		03-XX-LB-S-0001.2	
rev		01	
date		20/11/2017	
by		RK	



### Detail 3: Floor Beam To Be Re-supported, 1:10

#### Structural Strengthening Requirements:

- The strengthening is required to the bearing of the floor beams to justify the connection for required residential loadings to current standards



Figure 3, Floor Beam To Be Re-supported (Indicative)

NOTES

engenuiti

+44 (0)20 7089 5760  
www.engenuiti.com

2 Mailings Place  
Tower Bridge Road  
London SE1 3JB  
United Kingdom

project name 7 Denmark Street			
sketch title Proposed Structural Details			date 20/11/2017
project no 879	sketch no 03-XX-LB-S-0001.3	rev 1	by RK