




Technical Hotline  
+44 (0)1268 563720

# Boxes

## PVC Boxes

19MM  
SURFACE

32MM  
SURFACE



**2120WHI** 10  
FOR 1, 2 AND 3 GANG  
PLATESWITCHES

With earth terminal  
**DIMENSIONS**  
87 x 87mm  
**FIXING CENTRES**  
60.3mm

Knockouts 'cut-out' provided in top and bottom for 16mm oval PVC conduit. 20mm round 'push-out' type knockout in base for cable entry. Fixing holes are also provided for mounting to wall or over BS 4568-2 small circular boxes.  
BS 5733:2010

**2180WHI** 10  
1 GANG  
**2181WHI** 10  
1 GANG

**DIMENSIONS**  
87 x 87mm  
**FIXING CENTRES**  
60.3mm

**KNOCKOUTS**  
**2180:** One 'push-out' for 20mm oval conduit in top, one 'cut-out' for 20mm or 25mm oval conduit and one 20mm round 'push-out' in the base.  
**2181:** One 'push-out' for 20mm round conduit in top and one 20mm round 'push-out' in base.  
BS 5733:2010

**2182WHI** 5  
2 GANG  
**2183WHI** 5  
2 GANG

**DIMENSIONS**  
87 x 148mm  
**FIXING CENTRES**  
120.6mm

**KNOCKOUTS**  
**2182:** Two 'push-outs' for 20mm oval conduit in top, two 'cut-outs' for 20mm or 25mm oval conduit and one 20mm round 'push-out' in base  
**2183:** One 'push-out' for 20mm round conduit in top and one 20mm round 'push-out' in base.  
BS 5733:2010

**K2181WHI** 10  
FOR 1 GANG LOGIC PLUS™ POWER ACCESSORIES  
**K2183WHI** 5  
FOR 2 GANG LOGIC PLUS™ POWER ACCESSORIES  
**K2185WHI** 5  
FOR 3 GANG LOGIC PLUS™ POWER ACCESSORIES

### KNOCKOUTS

**K2181:** One 'cut-out' for 20mm round conduit in top face, one 'cut-out' for 20mm or 25mm oval conduit in lower face and one 20mm round 'push-out' in the base.

**K2183 and K2185:** One 'cut-out' for 20mm round conduit in top face, two 'cut-outs' for 20mm or 25mm oval conduit in lower face and one 20mm round 'push-out' in the base. Both boxes are suitable for fitting over 1 gang and 2 gang BS 4662 flush steel boxes respectively.

### DIMENSIONS

1 gang: 87 x 87mm  
2 gang: 87 x 148mm  
3 gang: 87 x 208mm

### FIXING CENTRES


1 gang: 60.3mm  
2 gang: 120.6mm  
3 gang: 180.9mm  
BS 4662:2006  
where applicable

## Moulded Boxes

ARCHITRAVE  
SURFACE

16MM  
SURFACE

30MM  
SURFACE



**K2151WHI** 10  
1 GANG  
ARCHITRAVE BOX  
**K2152WHI** 5  
2 GANG  
ARCHITRAVE BOX

Earth terminal fitted in base of boxes.

**DIMENSIONS**  
1 gang: 87 x 33 x 16mm  
2 gang: 148 x 33 x 16mm  
**FIXING CENTRES**  
1 gang: 60.3mm  
2 gang: 120.6mm  
BS 5733:2010

**K2160WHI** 10  
FOR 1, 2 AND  
3 GANG LOGIC PLUS™ PLATESWITCHES  
**K2161WHI** 5  
FOR 4 AND 6 GANG  
LOGIC PLUS™  
PLATESWITCHES

Earth terminal fitted in base of boxes. Knockouts provided in sides and bases.

**DIMENSIONS**  
1 gang: 87 x 87mm  
2 gang: 87 x 148mm  
**FIXING CENTRES**  
1 gang: 60.3mm  
2 gang: 120.6mm  
BS 5733:2010

**K2140WHI** 10  
FOR 1 GANG  
LOGIC PLUS™  
POWER ACCESSORIES  
**K2142WHI** 5  
FOR 2 GANG  
LOGIC PLUS™  
POWER ACCESSORIES  
**K2153WHI** 5  
FOR 3 GANG  
LOGIC PLUS™  
POWER ACCESSORIES

Knockouts in base and sides for cable entry  
K2142 and K2153 are suitable for fitting over 1 gang and 2 gang BS 4662 flush steel boxes respectively

**DIMENSIONS**  
1 gang: 87 x 87mm  
2 gang: 87 x 148mm  
3 gang: 87 x 208mm  
**FIXING CENTRES**  
1 gang: 60.3mm  
2 gang: 120.6mm  
3 gang: 180.9mm  
BS 5733:2010

## Boxes

### Moulded Boxes

32MM

SURFACE

44MM

SURFACE

DRY LINING

35MM

FLUSH

MI CABLE BOXES

37MM

SURFACE



**2140WHI** 10  
FOR 1 GANG  
POWER ACCESSORIES  
SQUARE CORNERS

Knockouts are provided in base and sides for cable entry

**DIMENSIONS**

1 gang: 87 x 87mm

2 gang: 87 x 148mm

**FIXING CENTRES**

1 gang: 60.3mm

2 gang: 120.6mm

BS 5733:2010

**2031WHI** 10  
FOR 1 GANG  
POWER ACCESSORIES  
SQUARE CORNERS

Knockouts in base and sides for cable entry.

**DIMENSIONS**

87 x 87mm

**FIXING CENTRES**

60.3mm

BS 5733:2010

**QFB1WHI** 20  
1 GANG  
**QFB2WHI** 10  
2 GANG

All round flange for a flush fit. One piece moulded lug automatically snaps into place. No rear projections. Clamp device on cable entry. Will accommodate partition thickness between 6mm and 16mm. Earth terminal facility.  
BS 4662:2006

**QFB/IG1** 20  
1 GANG WITH  
INTUMESCENT GASKET  
**QFB/IG2** 10  
2 GANG WITH  
INTUMESCENT GASKET

**QFB/IG1 & QFB/IG2**

Pre-fitted with intumescent gaskets to give fire protection, in accordance with BS 476-2:1987. In a fire situation, a chemical reaction will occur with the intumescent material. The void behind the wiring device will be filled, providing protection against the passage of fire.

BS 4662:2006

**K2131WHI** 5  
1 GANG  
10 CLAMPS  
**K2132WHI** 5  
2 GANG  
12 CLAMPS

Clamps accept 20mm sealing pots.

**DIMENSIONS**

1 gang: 92 x 92mm

2 gang: 92 x 152mm

**FIXING CENTRES**

1 gang: 60.3mm

2 gang: 120.6mm


BS 5733:2010

DUAL BOX  
38MM  
SURFACE

40MM  
SURFACE

FLANGE BOXES  
45MM  
FLUSH

Mounting  
Patresses  
SURFACE



**K2025WHI** 5  
FOR MOUNTING  
TWO 1 GANG  
LOGIC PLUS™  
ACCESSORIES

This box has two slots in base with 60.3mm and 120.6 fixing centres for fitting over BS 4226 flush boxes. Knockouts provided for cable entry.

Includes integral dividing fillet.

**DIMENSIONS**

86 x 172 mm

BS 5733:2010

**K2031WHI** 10  
FOR 1 GANG  
LOGIC PLUS™  
POWER ACCESSORIES  
**K2172WHI** 5  
FOR 2 GANG  
LOGIC PLUS™ 50 AMP  
DP SWITCHES

Knockouts provided in sides and base.

**K2172:** Earth terminal fitted in base of box.

**DIMENSIONS**

K2031: 87 x 87mm

K2172: 87 x 148mm

**FIXING CENTRES**

K2031: 60.3mm

K2172: 120.6mm

BS 5733:2010

**K2061WHI** 5  
1 GANG  
**K2062WHI** 5  
2 GANG

**DIMENSIONS**

K2061: 88 x 88mm

K2062: 88 x 148mm

**FIXING CENTRES**

K2061: 60.3mm

K2062: 120.6mm

BS 5733:2010

**K2134WHI** 10  
1 GANG 20MM DEEP  
FOR LOGIC PLUS™  
ACCESSORIES  
**K2133WHI** 10  
2 GANG 20MM DEEP  
FOR LOGIC PLUS™  
ACCESSORIES

**FIXING CENTRES**

1 gang: 60.3mm

2 gang: 120.6mm

BS 5733:2010