



CEILING ACCESSORIES

RANGE INTRODUCTION

MK Electric offers a comprehensive range of white ceiling accessories for all requirements. Included in the range are enhanced 'safety' lampholders.

Unlike most other 'safety' lampholders, when the lamp is removed Shockguard Plus automatically shields the contact by means of a specially designed shutter and it remains that way until a lamp is replaced.

Therefore when no lamp is in place contact pins are totally isolated, eliminating danger of electrocution.

FEATURES & BENEFITS

EASE OF INSTALLATION

Pendant sets incorporate a heat resistant lampholder, ceiling rose with a transparent base and clear terminal markings for ease of identification. Terminals are grouped in line with neutral, loop-in and earth terminals.

SAFETY

Shockguard Plus has a specially designed shutter that automatically shields the lamp contacts, therefore eliminating the danger of electrocution.

RELIABILITY

All products are 100% tested before delivery for confidence, so a 'fit and forget' installation can be achieved. Fully compliant with the relevant British Standards BS 7895 for bayonet lampholders with enhanced safety and BS EN 61184.

DURABILITY

Manufactured from the highest quality materials to give a high gloss finish, which is both scratch and colour fade resistant.

Ceiling Accessories

Ceiling Switches

6 AMP
SURFACE

WITHOUT
MOUNTING BLOCKS
FLUSH

50A
FLUSH

Mounting Blocks and Cords



K3191WHI

6A SP ONE-WAY
1.5M WHITE CORD WITH
WHITE ACORN

K3191D1WHI

6A SP ONE-WAY
2M WHITE CORD
AND 1X GRAPHITE BANGLE

K3192WHI

6A SP TWO-WAY
1.5M WHITE CORD
AND WHITE ACORN

K3192D1WHI

6A SP TWO-WAY
2M WHITE CORD
AND 1X GRAPHITE BANGLE

Supplied with mounting blocks.
Earth terminal is riveted in base of
mounting blocks.

BANGLE DIAMETER

50mm

These switches do not have to be
derated when used with fluorescent or
inductive loads.

FIXING CENTRES

50.8mm

BS EN 60669-1:1999

5

3190RCWHI

6A SP TWO WAY
2M RED CORD WITH RED ACORN
PULL TO MAKE OR PULL TO
BREAK (MOMENTARY SWITCH
ACTION)

3190RCD1WHI

6A SP TWO-WAY
3M RED CORD
AND 2X RED BANGLE

Supplied with mounting blocks.

BANGLE DIAMETER

50mm

BS EN 60669-1:1999

5

5

5

5

K3131WHI

6A SP TWO-WAY

3151WHI

16A DP ONE-WAY

Mounting blocks are not supplied. Use
K2051WHI or K2056WHI.

Suitable for installation in small circular
conduit boxes to BS EN 61386-1:2008
See page 354.

Ceiling switch cords are 1.5m minimum
length.

These switches do not have to be
derated when used with fluorescent or
inductive loads.

FIXING CENTRES

50.8mm

BS EN 60669-1:1999

5

5

3164WHI

50A DP ONE-WAY
WITH NEON
1.5M WHITE

8329SSWHID1T9

2M WHITE CORD WITH JOINT
UNION AND GRAPHITE BANGLE

MOUNTING BOXES

Surface Moulded

2140WHI, 2180WHI

2031WHI (extra wiring space)

Flush Steel

877ZIC (for full load applications)

Surface Metal

2211ALM, 2213ALM

Fitted with a mechanical 'OFF' indicator.
The switch fully complies with the
requirements within BS 7671 IET Wiring
Regulations with respect to safety
isolation for maintenance purposes
and provides a full 3mm contact gap
when 'OFF'.

DIMENSIONS

86 x 86mm

BANGLE DIAMETER

50mm

FIXING CENTRES

60.3mm

BS EN 60669-1:1999

5

5

K2051WHI

MOUNTING BLOCK
FOR 6A OR 16A
SWITCHES

K2056WHI

MOUNTING BLOCK
WITH NEON
FOR 6A OR 16A
SWITCHES

8329SSWHIT9

1.5M WHITE CEILING
SWITCH CORD COMPLETE
WITH ACORN AND ONE PIECE
JOINT UNION

9420SST9

2M RED CEILING SWITCH
CORD COMPLETE WITH TWO
RED ACORNS AND ONE PIECE
JOINT UNION

9420SSD1

3M RED CEILING SWITCH CORD
COMPLETE WITH 2 X RED
BANGLES AND JOINT UNION

K2051WHI and K2056WHI

Earth terminal riveted in base.

DIAMETER

76mm not including Neon Lens

FIXING CENTRES

50.8mm

BS EN 60669-1:1999

10

5

10

1

10




Technical Hotline
+44 (0)1268 563720

Ceiling Accessories

WIRING DEVICES
WHITE


Ceiling Roses

Lampholders



Unlike most 'safety' lampholders, when a lamp is removed Shockguard Plus automatically seals the contact by means of specially designed shutter and it remains that way until the lamp is replaced.

This means that with no bulb in place there is no danger of electrocution from exposed contacts, as the contact pins are fully shielded.



The MK Ceiling Rose has a transparent base, precut aperture and clear markings for ease of installation. Terminal layout allows cables to be cut to the same length and the earth terminal is positioned for easier cable access.

K1161WHI
FOUR TERMINALS
LINE, NEUTRAL,
LOOP-IN AND EARTH

K1163WHI
CEILING ROSE HALO

Incorporate tunnel type terminals, which accommodate 3 x 2.5mm² cables and allow for off centre cable entries, transparent terminal block and equal length wire stripping.

Suitable for fittings of up to 5kgs. Heavier fittings must be installed using independent support eg. ceiling hook. The ceiling roses are suitable for mounting over BS EN 61386-1:2008 circular conduit boxes.

DIAMETER
(Cover) 86mm
DEPTH
(Cover) 34mm3
BS 67:1987

The Ceiling Rose Halo gives a neat finish should the ceiling be damaged.

10 **K1170WHI**
BC PENDANT LAMPHOLDER
WITH AUTOMATIC CORDGRIP
AND STRAIGHT SKIRT

10 **K1171WHI**
BC PENDANT LAMPHOLDER
WITH AUTOMATIC CORDGRIP
AND PROTECTIVE SKIRT

10 **K1180WHI**
STRAIGHT SKIRT FOR
MK LAMPOLDERS

10 **K1181WHI**
PROTECTIVE SKIRT FOR
MK LAMPOLDERS

All MK lampholders are heat resistant to category T2 of BS EN 61184 and are therefore capable of operation with lamp cap temperatures up to 210°C. BS EN 61184:1997 T2 Rated.

Ceiling Accessories

Lampholders

SG TYPE



1150WHI

1150WHI
BC PENDANT
SG TYPE LAMPHOLDER

10

Shockguard SG Type lampholders automatically shield contacts by means of a shutter when the lamp is removed. All MK SG Type lampholders are heat resistant to category T2 of BS EN 61184 and are therefore capable of operation with lamp cap temperatures up to 210°C.
BS EN 61184:1997
BS 7895:1997

Pendant Sets

SG TYPE



K1186WHI

K1189WHI

K1186WHI
150MM PENDANT SET
K1189WHI
230MM PENDANT SET

10

10

K1186WHI and **K1189WHI** incorporate a lampholder (K1170WHI), heat resisting PVC insulated and sheathed flexible 0.75mm² two core circular cable complying with BS EN 50525-2-11 and a ceiling rose fitted with line, neutral, loop-in and earth terminals (K1161WHI). This assembly will support a light fitting of up to 3kgs.

Batten Lampholders

SG TYPE



K1172WHI



1152WHI



1174WHI



1154WHI

K1172WHI
BC ANGLED
1174WHI
HEAT RESISTANT TAILS,
LIVE, NEUTRAL, LOOP-IN
AND EARTH TERMINALS

10

10

All MK lampholders are heat resistant to category T2 of BS EN 61184 and are therefore capable of operation with lamp cap temperatures up to 210°C.
1174WHI also incorporates heat resistant wires connecting the terminals in the base to the lampholder. It has terminals mounted in the base and knockouts which accommodate 3 x 2.5 mm² cables and allow for off centre cable entries.
BS EN 61184:1997 T2 Rated.

1152WHI
SG TYPE
ANGLED BATTEN
LAMPHOLDER
HEAT RESISTANT TAILS,
LIVE, NEUTRAL, LOOP-IN
AND EARTH TERMINALS
1154WHI
SG TYPE
BATTEN LAMPHOLDER
HEAT RESISTANT TAILS,
LIVE, NEUTRAL, LOOP-IN
AND EARTH TERMINALS

10

10

10

Shockguard SG Type lampholders automatically shield contacts by means of a shutter when the lamp is removed. All MK SG Type lampholders are heat resistant to category T2 of BS EN 61184 and are therefore capable of operation with lamp cap temperatures up to 210°C.
1152WHI and **1154WHI** also incorporate heat resistant wires connecting the terminals in the base to the lampholder.
BS EN 61184:1997 T2 Rated.
BS 7895:1997



Oxford University Images/ David Williams

CASE STUDY

THE MALTHOUSE, OXFORD UNIVERSITY – MK PORTFOLIO

Oxford University Estates Services, who are responsible for managing over 350 buildings and properties for the university, have their offices located at The Malthouse in central Oxford.

Their fully functional office space has been refurbished utilising a variety of MK products including Prestige 3D Compact and Integrated USB sockets, which were selected due to their superior manufacturing quality, reliability and functionality.

